

Edition 1.02
16.10.03

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

Date of print: 28.03.04

Content

	Page
Preface	
Structure of the Standard	
Comparison of the structure of the standards for (Maritime) ECDIS and Inland ECDIS	
Section 1 Performance standard.....	1
Section 2 Data standard.....	11
Appendix A Object catalogue.....	15
Annex A Codes for producers and waterways	103
Appendix B Product specification	105
Annex A Use of the object catalogue	111
Section 3 Presentation standard	129
Appendix A Presentation library.....	133
Section 4 Operational and performance requirements, test methods and required test results	157
Appendix A Measures to ensure software quality.....	173
Appendix B System configurations	181
Section 5 Glossary of terms	185

Preface

Reflections and experiments have been made in several countries of the European Union (EU) to use telematics for the support of inland navigation. This aim was especially pursued in the scope of the EU research and development project INDRIS. A pilot project on the Rhine river was started in Germany in 1998 under the name of ARGO. In ARGO and INDRIS, the radar image on the display in the skipper's wheelhouse is overlaid by an electronic chart. This is an approach to higher safety and more efficiency of inland navigation.

It turned out in the discussions that only an internationally agreed procedure will be successful, since a skipper cannot be expected to employ different equipment in each country. This was the reason why the internationally introduced *Electronic Chart Display and Information System (ECDIS)* - originally developed for maritime navigation - was also considered for inland navigation. The latest versions of the IMO, IHO and IEC standards for ECDIS were introduced in 1996. ECDIS is a well matured system now. The idea was to adopt ECDIS for inland navigation and to supplement some distinct inland features, but not to change the original ECDIS standard. In this way, it will be possible to have compatibility between the original - Maritime - ECDIS and Inland ECDIS. This is important for the estuaries of the rivers, where sea vessels as well as inland vessels navigate.

The *Concerted Action on Inland Navigation*, an institution of the 4th Framework Programme for Transport Research and Development of the European Union, appointed a Working Group and an Inland ECDIS Expert Group in 1998 with the development of an Inland ECDIS Standard. The experience of ARGO and INDRIS had to be taken as the basis for the new standard.

The Expert Group had the following members:

- Mr. Christian Krajewski (chairman), Mr. Kersten Gevers, Mr. Eric Rottmann, Mr. Hermann Haberkamp, Dr. Arne Driescher (from 2000), Dr. Reinhard Zimmermann (until 1999) of Germany,
- Mr. Peter Kluytenaar (deputy chairman), Mrs. Lea Kuiters, Mr. Ron Wardenier (until 2000) of The Netherlands and
- Mr. Bernd Birkhuber of Austria.

The Expert Group submitted its first proposal on 1 January 1999.

In the year 2000, the competent committees of the Central Commission for the Navigation on the Rhine (CCNR) in Strasbourg installed an Ad-hoc Working Group for Inland ECDIS with the order to draft the Inland ECDIS Standard of CCNR.

The CCNR Ad-hoc Working Group had the following members:

- Mr. Max Bühler (chairman) and Mr. Peter Sauter of Switzerland,
- Mr. Hermann Haberkamp, Mr. Christian Krajewski, Mr. Konrad Steinkämper and Mrs. Claudia Oberheim of Germany,
- Mr. Alfons Van Reusel of Belgium
- Mr. Jean-Pierre Saunier, Mr. Alberto Dos Santos and Mr. André Kanschine of France,
- Mr. Nico Koedam, Mr. Peter Stuurman and Mr. Cas Willems of The Netherlands,
- Mr. Reinhard Vorderwinkler of Austria and
- Mr. Volker Orlovius (Chief Engineer) of the CCNR.

The Ad-hoc Working Group started with the results of the Expert Group as the basis for their further work.

Since the 4th Framework Programme of the European Union ended in the year 2000, the Expert Group reported to the Ad-hoc-Working Group of CCNR afterwards.

Strasbourg, 6 April 2001

Christian Krajewski

Chairman of the Expert Group


Max Bühler

Chairman of the Ad-hoc Working Group

Volker Orlovius

Chief Engineer of CCNR

Structure of the Inland ECDIS Standard



Comparison of the structures of the standards for (Maritime) ECDIS and Inland ECDIS**(Maritime) ECDIS**

IMO A.817(19) Performance Standards for ECDIS, November 1995
 Appendix 1: Reference Documents
 Appendix 2: SENC Information
 Appendix 3: Navigational Elements and Parameters
 Appendix 4: Areas for which special conditions exist
 Appendix 5: Alarms and Indicators

IHO S-57: Transfer Standard for Digital Hydrographic Data, Edition 3.0, November 1996

Part 1: General Introduction
 Part 2: Theoretical Data Model
 Part 3: Data Structure

Appendix A: IHO Object catalogue
 Introduction
 Chapter 1: Object Classes
 Chapter 2: Attributes

Annex A: IHO Codes for Producing Agencies
 Annex B: Cross Reference

Appendix B: Product specifications
 Appendix B.1: ENC Product Specification
 Annex A: Use of The Object Catalogue for ENC
 Annex B: Example of CRC Coding
 Appendix B.2: Data Dictionary Product Specification

IHO S-52 Specification for Chart Content and Display Aspects of ECDIS, Edition 5, December 1996

Appendix 1: Guidance on Updating the ENC
 Annex A: Definition and Acronyms
 Annex B: Current Updating Practice for Paper Charts
 Annex C: Estimate of Data Volume

Appendix 2: Colour & Symbol Specifications for ECDIS
 Annex A: IHO ECDIS Presentation Library
 Part I: Use of the Presentation Library
 Part II: Mariners Navigation Objects
 Part III: Supplementary Features
 Annex B: Calibration of Colour CRTs
 Annex C: Maintaining the Calibration of Colour CRTs
 Appendix 3: Glossary of ECDIS-Related Terms

IEC 1174: ECDIS - Operational and Performance Requirements,
 Methods of Testing and Required Test Results, December 1996

Inland ECDIS (Edition 1.02, 16.10.2003)**Section 1:** Performance Standard**Section 2:** Data Standard

Appendix A: Object Catalogue
 1: Introduction
 2 - 4: Object Classes
 5 - 6 : Object Attributes

Annex A: Codes for Producers and Waterways

Appendix B: Product Specification
 Annex A: Use of the Object Catalogue

Section 3: Presentation Standard

Appendix A: Presentation Library

Section 4: Operational and Performance Requirements,
 Methods of Testing and Required Test Results
 Appendix A: Software Quality Assurance
 Appendix B: System Configurations
Section 5: Glossary of Terms

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 1

Performance Standard for Inland ECDIS

Contents

1	Introduction (Primary Functions and Performance)	3
2	Definitions	4
2.1	Terms.....	3
2.2	References	4
3	Contents, Provision and Updating of Chart Information	4
3.1	Contents and provision of Inland ENCs	4
3.2	Updates	5
4	Presentation of Information	5
4.1	Display requirements	5
4.2	Display ranges (scales)	6
4.3	Image positioning and orientation	6
4.4	Display of SENC information.....	6
4.5	Display of radar information.....	7
4.6	Display of other navigational information	7
4.7	Colours and symbols	7
4.8	Data and display accuracy	7
5	Operation	8
5.1	Information mode.....	8
5.2	Navigation mode.....	8
5.3	Operation controls	9
6	Connections with other Equipment	9
7	Indications and Alarms	9
7.1	Built in Test Equipment (BITE)	9
7.2	Malfunctions	9
8	Fall Back Arrangements	9
8.1	Insufficient accuracy of the SENC-positioning	9
8.2	Defects.....	9
9	Power Supply in Navigation Mode	10

1 Introduction (Primary Functions and Performance)

- a) Inland ECDIS shall contribute to safety and efficiency of inland shipping and thereby to protection of the environment.
- b) Inland ECDIS shall reduce the navigational workload as compared to traditional navigation and information methods.
- c) Inland ECDIS (Operating System Software, Application Software and Hardware) shall have a high level of reliability and availability at least of the same level as other means of navigation, for the navigation mode as specified in Section 4 of this standard.
- d) Inland ECDIS can be designed for information mode only or for both, information mode and navigation mode.
- e) Inland ECDIS shall use chart information as specified by Sections 2 and 3 of this Standard.
- f) Inland ECDIS shall facilitate simple and reliable updating of the Inland ENC.
- g) Inland ECDIS shall provide appropriate alarms or indications with respect to the information displayed or malfunction of the equipment.
- h) Inland ECDIS shall meet the requirements of this performance standard.

2 Definitions

2.1 Terms (see also section 5 of this Standard: Glossary)

For the Inland ECDIS performance standard the following definitions apply:

- a) **Inland ECDIS** means an electronic chart display and information system for inland navigation, displaying selected information from an Inland System Electronic Navigational Chart (Inland SENC) and, optionally, information from other navigation sensors.
- b) **Inland Electronic Navigational Chart (Inland ENC)** means the database, standardised as to content, structure and format, issued for use with Inland ECDIS. The Inland ENC complies with the IHO standards S-57 and S-52, enhanced by the additions and clarifications of this standard for Inland ECDIS. The Inland ENC contains all essential chart information and may also contain supplementary information that may be considered as helpful for navigation.
- c) **Inland System Electronic Navigational Chart (Inland SENC)** means a database, resulting from the transformation of the Inland ENC by Inland ECDIS, for appropriate use, updates to the Inland ENC by appropriate means and other data added by the skipper. It is this database that is actually accessed by the Inland ECDIS for display generation and other navigational functions. The Inland SENC may also contain information from other sources.
- d) **Minimum Information Density (display base)** means the minimum amount of SENC information that is presented and which cannot be reduced by the operator, consisting of information that is required at all times in all geographic areas and under all circumstances.

- e) **Standard Information Density (standard display)** means the default amount of SENC information that shall be visible when the chart is first displayed on Inland ECDIS first.
- f) **All Information Density (all display)** means the maximum amount of SENC information. Here, in addition to the standard display, also all other objects are displayed, individually on demand.
- g) **User-defined settings** means the possibility to use and store a profile of display and operation controls-settings.
- h) **Integrated Display** means a head-up, relative-motion picture consisting of the SENC overlaid with the radar-image with matching scale, offset and orientation.
- i) **Navigation Mode** means the use of the Inland ECDIS for conning the vessel with overlaid radar image.
- j) **Information Mode** means the use of the Inland ECDIS for information purposes only without overlaid radar image.

2.2 References

- a) IHO Special Publication No. S-57 "IHO Transfer Standard for Digital Hydrographic Data", 3rd Edition, November 1996
- b) IHO Special Publication No. S-52 "Specifications for Chart Content and Display Aspects of ECDIS", 5th Edition, December 1996, including
 - S-52 Appendix 1 "Guidance on Updating the Electronic Chart", 3rd Edition, July 1997,
 - S-52 Appendix 2 "Provisional Colour and Symbol Specifications for ECDIS", 1st Edition, February 1991 and
 - S-52 Appendix 3 "Glossary of ECDIS-related Terms", 2nd Edition, September 1993
- c) IMO Resolution A.817(19) "Performance Standards for Electronic Chart Display and Information Systems (ECDIS)", November 1995
- d) IEC-Guideline 1174 "ECDIS -- Operational and performance requirements, methods of testing and required test results", December 1996
- e) ZKR-Beschlüsse 1989-II-33,- 34 und -35 (Vorschriften betreffend die Mindestanforderungen, die Prüfbedingungen, den Einbau und die Funktionsprüfung von Navigationsradaranlagen und Wendeanzeigern in der Rheinschifffahrt)

3 Contents, Provision and Updating of Chart Information

3.1 Contents and Provision of Inland ENCs

- a) The chart information to be used in Inland ECDIS shall be the latest edition of information.
- b) Provisions shall be made to prevent the user from altering the contents of original Inland ENC editions.
- c) If the chart is intended to be used for navigation mode (Ch. 5.2), at least the following objects shall be included in the ENC:

- bank of waterway (at mean water level)
 - shoreline construction (groyne, longitudinal control dam)
 - contours of locks and dams
 - boundaries of the fairway (if defined)
 - isolated dangers in the fairway under water
 - isolated dangers in the fairway above water level, such as bridges, overhead wires etc.
 - buoys, beacons, lights, notice marks
 - waterway axis with kilometres and hectometres
- d) If the chart is intended to be used for navigation mode (ch 5.2), the government-authorised authority decides for each waterway which of the above named objects are to be verified by the authority.

3.2 Updates

- a) Inland ECDIS shall be capable of accepting updates to the Inland ENC data provided in conformity with the agreed standards. These updates shall be applied to the SENC automatically. The implementation procedure shall not interfere with the display in use.
- b) Inland ECDIS shall allow display of updates, so that the skipper may review their contents and ascertain that they have been included in the SENC.
- c) Inland ECDIS shall be capable of revoking automatically applied updates of the Inland ENC data.
- d) Original Inland ENC editions and later updates shall never be merged.
- e) The Inland ENC and all updates to it shall be displayed without any degradation of their information content.
- f) The Inland ENC data and updates to it shall be clearly distinguishable from other information.
- g) Inland ECDIS shall ensure that the Inland ENC and all updates to it have been correctly loaded into the SENC.
- h) Inland ECDIS shall keep a record of updates, including the time of application to the SENC.
- i) The contents of the SENC to be used shall be adequate and up to date for the intended voyage.

4 Presentation of Information

4.1 Display Requirements

- a) The display method shall ensure that the displayed information is clearly visible to more than one observer in the typical conditions of light experienced in the wheelhouse of a vessel by day and night.
- b) The display size of the chart presentation shall be at least 270 mm by 270 mm for equipment designed and admitted for the Navigation Mode. In Information Mode ergonomic aspects shall determine the size.
- c) The display requirements shall be met whether in landscape or in portrait format.

4.2 Display Ranges (Scales)

- a) In Information Mode (ref. to Ch. 5.1), it is recommended to use the same ranges as specified in the Navigation Mode.
- b) In Navigation Mode (ref. to Ch. 5.2), only the successive switchable ranges (scales) specified in Section 4, ch.4.7 of this Standard are allowed.

4.3 Image Positioning and Orientation

- a) In Information Mode all kinds of chart orientation are allowed (see Ch. 5.1)
- b) In Navigation Mode the chart shall be automatically positioned and oriented in the relative motion, head-up orientation with the own ship's position in the screen centre or off-centred (see Ch. 5.2).

4.4 Display of SENC Information

- a) The display of SENC information shall be divided into the following three display categories:

- Display Base
- Standard Display
- All Information Display

The membership of the object classes in the display categories is given in detail in the Look-up Tables of IHO S-52, Appendix 2, Annex A (Presentation Library) and in Section 3, Appendix A (Presentation Library) of this Standard.

- b) The Display Base category has to contain at least the following objects:

- river bank (at mean water level)
- shoreline construction (groyne, longitudinal control dam)
- contours of locks and dams
- boundaries of the fairway (if defined)
- isolated dangers in the fairway under water
- isolated dangers in the fairway above water level, such as bridges, overhead wires etc.
- buoys, lights and beacons

- c) The Standard Display category has to contain at least the following objects:

- the objects of Display Base category
- prohibited and restricted areas
- piers for commercial vessels (cargo and passenger)
- kilometre and hectometre marks on the banks

- d) The All Information Display category has to display all objects that are contained in the Inland SENC, individually on demand.

- e) When invoking the Inland ECDIS, it shall come up with the Standard Information Density at an appropriate range available in the SENC for the displayed area

- f) Inland ECDIS shall be switchable to the Standard Information Density at any time by a single operator action.

- g) Inland ECDIS shall clearly indicate the information density currently in use at all times.
- h) Time variable depth information in the ENC has to be displayed independently of the above named three display categories.

4.5 Display of Radar Information

- a) In Navigation Mode the radar image shall have the highest display priority and it is only allowed to be presented in the relative motion, head-up mode.
- b) The underlaid SENC shall match in position, range and orientation. The radar image and the position from the position sensor shall both be adjustable for the antenna offset to the conning position.
- c) The overlaid radar image has to conform with the minimum requirements as specified in Section 4, ch. 4.14 of this Standard.
- d) The overlaid radar-image may contain additional navigational information.

4.6 Display of Other Navigational Information

- a) Inland ECDIS and additional navigational information shall use a common reference system.
- b) It shall be possible to display the skipper's own ship's position on the screen.
- c) It shall be possible for the skipper to select safety limits.
- d) Inland ECDIS shall emphasize the falling short of the safety limits.

4.7 Colours and Symbols

- a) The display of colours and symbols to represent SENC information shall comply with the regulations of Section 3 of this Standard.
- b) To present navigational elements and parameters as listed in the IMO Resolution A.817(19), Appendix 3 other colours and symbols than those mentioned in 4.7.a must be used.

4.8 Data and Display Accuracy

- a) The accuracy of the calculated data that are presented shall be independent of the display characteristics and shall be consistent with the SENC accuracy.
- b) The Inland ECDIS shall provide an indication whether the display uses a smaller display range than the accuracy of the Inland ENC data offers (over-scale indication).
- c) The accuracy of all calculations performed by Inland ECDIS shall be independent of the characteristics of the output device and shall be consistent with the SENC accuracy.
- d) Bearings and distances drawn on the display or those measured between features already drawn on the display shall have an accuracy no less than that afforded by the resolution of the display.

5 Operation

5.1 Information Mode

- a) Information Mode is intended to be used for information only and not for navigation.
- b) In Information Mode all kinds of chart orientation, rotation, zooming and panning are allowed. However, it is recommended to use the same fixed ranges as in the Navigation Mode and the chart orientation whether
 - to north, or
 - to the fairway axis at the actual position, or
 - to the actual ship's heading.
- c) It should be possible to scroll the chart manually on the screen with the fairway axis in line with the vertical screen axis.
- d) Inland ECDIS may be connected to a positioning sensor to scroll the chart picture automatically and to display the section of chart matching the actual surrounding, namely in the operator-selected range and with the own ship's position to the centre of the screen. The centre line of a river, channel or buoys route will be assumed as to be decisive for the orientation of the chart.
- e) The skipper's own ship's position should be marked with an appropriate generic symbol.

5.2 Navigation Mode

- a) In Navigation Mode, the Inland ECDIS display shall be integrated with the own ship's radar information. The radar information shall be clearly distinguishable from the SENC information.
- b) The integrated display must be in accordance with the requirements for radar on inland waterways as specified in Section 4, ch. 4.14 of this Standard.
- c) The chart and the radar image must match in size, position and orientation within the limits as specified in Section 4, ch. 3.4 and 8.3.2 of this Standard.
- d) The Integrated Display shall only be presented in the head-up orientation. Other orientations are not permitted.
- e) It shall be possible for the operator to adjust the displayed position of the vessel so that the radar image matches the SENC display.
- f) It shall be possible to remove either the ECDIS or the radar information by a single operator action temporarily.
- g) The vessel's position shall be derived from a continuous positioning system of which the accuracy is consistent with the requirements of safe navigation.
- h) Navigation Mode must provide an indication when the input from the position-fixing system is lost. Navigation Mode shall also repeat, but only as an indication, any alarm or indication passed to it from a position fixing system.
- i) The positioning system and the SENC shall be based on the same geodetic datum.
- j) In navigation mode, the data according to ch. 3.1.c of this standard shall always be visible and shall not be obscured by other objects.

5.3 Operation and Control Elements

- a) Inland ECDIS shall be designed following ergonomic principles for user-friendly operation.
- b) The Inland ECDIS equipment shall have a minimum of operation and control elements (see Section 4).
- c) Operation and control elements, and indicators for connected sensors, may be integrated in Inland ECDIS.
- d) Standard settings and user-defined settings shall be retrievable easily.

6 Connections with other Equipment

- a) Inland ECDIS shall not affect the performance of any connected equipment adversely. the connection of optional equipment shall degrade the performance of Inland ECDIS either.
- b) Inland ECDIS shall be capable of generating information to other systems, e.g. for the purpose of electronic reporting.
- c) The relevant requirements of controls and indicators to connected equipment shall be fulfilled.

7 Indications and Alarms

7.1 Built in Test Equipment (BITE)

Inland ECDIS shall be provided with means for carrying out on board tests of major functions either automatically or manually. In case of a failure, the module at fault shall be shown.

7.2 Malfunctions

Inland ECDIS shall provide a suitable alarm or indication of system malfunctions (ref. to Section 4, ch.9).

8 Fallback Arrangements

8.1 Insufficient accuracy of the SENC-positioning

In Navigation Mode the SENC shall be automatically switched off, if the SENC positioning does not match the radar picture within the limits of Section 4, ch. 5.1 and 5.2.

8.2 Defects

- a) If the Inland ECDIS system has an evident defect, it shall provide a suitable alarm (ref. to Section 4, ch. 4.16 and 9 of this Standard).
- b) Facilities enabling a safe take-over of the Inland ECDIS functions shall be provided in order to ensure that an Inland ECDIS failure does not result in a critical situation.

9 Power Supply in Navigation Mode

- a) The Inland ECDIS shall have its own separate fused power supply.
- b) Interruptions of the power supply for a period up to 5 minutes shall not have any influence on correct operation and shall not require restarting of the equipment manually.

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 2

Data Standard for Inland ECDIS

Contents

Data Standard

Appendix A Object Catalogue for Inland ECDIS
Annex A Codes for Producers and Waterways

Appendix B Product Specification for Inland ECDIS
Annex A Use of the Object Catalogue for Inland ENC

Data Standard

1 Scope

This "Data Standard for Inland ECDIS" describes the standard to be used

- for the exchange of digital hydrographic data between national inland waterway authorities and
- for its distribution to manufacturers, skippers and other users.

This Data Standard shall be used for the production of Inland ECDIS data. The transfer and distribution has to take place in such a way that none of the information is lost.

This Data Standard with its Appendices and Annexes is based on the "IHO Transfer Standard for Digital Hydrographic Data", Special Publication No. 57, Edition 3.0 of November 1996 with all Appendices and Annexes (see table in section 0 of this Inland ECDIS Standard), in brief "S-57".

This Data Standard describes the necessary additions and clarifications to S-57 and the application of S-57 for the purpose of use in Inland ECDIS applications.

2 Structure

Data Standard gives general regulations and describes the connection to the IHO-document S-57.

Appendix A is the "Object Catalogue for Inland ECDIS" which provides the officially approved data scheme to be used to describe entities in the real world. Its Annex A contains the codes producing agencies and waterways.

Appendix B contains the "Product Specification for Inland ECDIS". These are additional sets of rules applicable to Inland ECDIS data. Its Annex A contains the description "Use of the Object Catalogue for Inland ENC". Here rules for the encoding of the geometry and semantic descriptions are given.

3 Definitions

Definitions of terms may be found in

- S-57, part 1, clause 5
- the "Glossary of ECDIS Related Terms" in Appendix 3 to S-52
- the "Glossary of Terms" in Section 5 of this standard.

4 Conformity of data with the standard

No additions to S-57, part 1, clause 6.

5 Maintenance

Users of the standard, for example equipment manufacturers, must address their comments to the national inland waterways authority.

This standard will be updated by means of the following three documents:

Clarifications Document

This contains improvements to the wording of the standard. These are editorial amendments, which do not result in any substantive change to the standard.

Corrections Document

This contains changes to the standard to correct factual errors and to make necessary amendments to the standard.

Extensions Document

This contains extensions, or other significant changes to the standard, which will be included in the next edition of the standard. This is a working document which is produced and made available only on demand.

6 Theoretical Data Model

The description of the theoretical data model as contained in S-57 Part 2 applies to the theoretical data model of Inland ECDIS without any changes or amendments.

7 Data Structure

The description of the data structure as contained in S-57 Part 3 applies to the data structure of Inland ECDIS without any changes or amendments.

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 2

Data Standard for Inland ECDIS

Appendix A

Object Catalogue for Inland ECDIS

in addition to the

IHO-S-57 Object Catalogue

Contents

1	Introduction.....	18
1.1	The Object Catalogue.....	18
1.2	Extensions of the object classes and attributes.....	21
1.3	Conventions used in this document for types	21
2	Geo Object Classes (copied).....	22
	Anchor berth	22
	Anchorage area	23
	Berth	24
	Bridge	25
	Cable overhead	26
	Canal bank.....	27
	Depth area.....	28
	Distance mark.....	29
	Ferry route	30
	Harbour Area	31
	Harbour Facilities.....	32
	Lock Basin	33
	Radio calling-in point	34
	Restricted area	35
	River bank.....	36
	Signal station traffic	37
	Signal station warning.....	38
	Top Mark	39
3	Meta Object Classes (copied).....	40
	Navigational system of marks.....	40
4	Geo Object Classes (new)	41
	Beacon water-way	41
	Bridge area	42
	Bunker station.....	43
	Buoy water-way	44
	Communication Area	45
	Harbour Basin.....	46
	Lock area.....	47
	Lock basin part	48
	Notice mark	49
	Port Area.....	50
	Refuse dump	51
	Route planning point.....	52
	Terminal.....	53
	Turning basin.....	54
	Waterway axis	55
	Waterway profile	56
5	Object Attributes (copied).....	57
	Category of Anchorage area.....	57
	Category of bridge	58
	Category of distance mark.....	59

Category of ferry	60
Category of harbour facilities	61
Category of signal station traffic	62
Category of signal station warning.....	63
Marks navigational – System of.....	64
Restriction.....	65
Vertical datum.....	66
6 Object Attributes (new)	67
Additional mark	67
Bunker vessel, availability.....	68
Category of bank	69
Category of berth	70
Category of bunker station.....	71
Category of CEMT class.....	72
Category of communication.....	73
Category of harbour area.....	74
Category of notice mark	75
Category of refuse dump	78
Category of terminal	79
Category of waterway mark (buoy, beacon)	80
Class of dangerous cargo.....	81
Communication.....	82
Direction of impact.....	83
Distance from bank, first.....	84
Distance from bank, second.....	85
Distance of impact, upstream	86
Distance of impact, downstream	87
Elevation 1	88
Elevation 2	89
Function of notice mark	90
Horizontal clearance, length	91
Horizontal clearance, width.....	92
Transshipping goods	93
UN Location Code	94
Update message	95
National update message	96
Waterway distance	97
7 Overview of Inland ECDIS Object Classes and Attributes	98
8 List of additional used S-57 Object Attributes.....	100

1 Introduction

In the S-57 data model hydrographic information is represented as a defined combination of descriptive and spatial characteristics, called ‘feature objects’ and ‘spatial objects’. Details of further classification and relationships can be found in the respective publications of the IHO. In the S-57 standard, the IHO has laid down a data model, an object catalogue, a description of the exchange format and an ENC product specification.

In order to represent data necessary for inland waterway traffic in an application conforming to S-57, the S-57 object catalogue must be enhanced by the required object classes, attributes and values. Such enhancements in terms of ‘user defined objects’ are allowed in the S-57 standard and there are means to incorporate them.

1.1 The Object Catalogue

In the object catalogue, all official IHO object classes along with their allowed attributes and attribute values are defined. The Inland ECDIS object catalogue can be compared to the Chart 1 (INT 1) of the sea charts and additionally contains the special object classes and attributes for inland waterways.

The following types of feature objects exist:

- Geo: descriptive characteristics of the real world
- Meta: additional area related information, e.g. survey source
- Collection: information about relationships between objects

The following example from the object catalogue shows the definition of the S-57 feature object class 'Landmark'

Object class:	Landmark
Acronym:	LNDMRK
Code:	74
Set Attribute_A:	CATLMK; COLOUR; COLPAT; CONDTN; CONRAD; CONVIS; ELEVAT; FUNCTN; HEIGHT; NATCON; NOBJNM; OBJNAM; STATUS; VERACC; VERDAT; VERLEN;
Set Attribute_B:	INFORM; NINFOM; NTXTDS; PICREP; SCAMAX; SCAMIN; TXTDSC;
Set Attribute_C:	SORDAT; SORIND;
<u>Definition:</u>	A prominent object at a fixed location which can be used in determining a location or a direction. (adapted from IHO Dictionary S-32 5th Edition, 2643).
References:	INT 1: ID 5-6, 13; IE 10.1-20, 22-30.1, 30.3-4, 31; IL 11; IQ 100; M-4: 373.6; 374.1; 374.4; 374.5; 374.6; 374.7; 375.1-2; 375.4; 445.6; 456.2; 487.3;
Remarks:	
Distinction:	beacon, special purpose/general; building single; daymark; pylon/bridge support; topmark;

Example of S57-Object Catalogue (Object Classes)

Each object class is described by the following entries:

- Object Class: Object class name
- Acronym: 6-Character code of the object class
- Code: Integer code
- Set of attributes:
 - subset 'Attribute-A': individual characteristics of an object
 - subset 'Attribute-B': information about the use of an object
 - subset 'Attribute-C': administrative information on the origin of data
- Definition: Definition
- References:
 - INT 1: to the legend of paper charts
 - M-4: to the IHO-Publication M-4 (Chart Specifications of the IHO)
- Remarks: comments, relationships to other object classes

The following example from the object catalogue shows the definition of the S-57 attribute 'Category of landmark'

Attribute class: Category of landmark		
Acronym:	CATLMK	Code: 35
Attribute type:	L	
<u>Expected input (value):</u>		
ID	Meaning	INT 1 M-4
1 : cairn		IQ 100; 456.2;
... :;
20 : spire/minaret		IE 10.3, 17;
<u>Definitions:</u>		
cairn:	a mound of stones, usually conical or pyramidal, raised as a landmark or to designate a point of importance in surveying. (IHO Dictionary, S-32, 5th Edition, 601)	
..... :	
spire/minaret:	a tall conical or pyramid-shaped structure often built on the roof or tower of a building, especially a church or mosque. (adapted from The New Shorter Oxford English Dictionary, 1993)	
Remarks:	No remarks	

Example of S-57-Object Catalogue (Attributes)

Each attribute is described by the following entries:

- Attribute: attribute name
- Acronym: 6-character code of the attribute
- Code: Integer Code
- Attribute type: 1-character code for the data type
- enumerated ('E'): exactly one value selected from a list of pre-defined attribute values
- list ('L'): one or more values selected from a list of pre-defined attribute values
- float ('F'): floating point numeric value
- integer ('I'): integer numeric value
- coded string ('A'): string of ASCII characters in a predefined format
- free text ('S'): free-format alphanumeric string
- Expected input (value): expected input according to the above mentioned input types
- Definitions: Definition
- References:
 - INT 1: to the legend of paper charts
 - M-4: to the IHO-Publication M-4 (Chart Specifications of the IHO)
- Remarks: Comments, relations to other attributes

1.2 Extensions of the object classes and attributes

The extension of existing S-57 object classes with new attributes, and the extension of S-57 attributes with new values are not allowed. Therefore, the S-57 object classes and attributes, which are to be extended according to the requirements of Inland ECDIS, must be copied. Object classes are copied with their complete set of attributes, and attributes are copied with their complete list of attribute values. All new object classes and attributes have the same name as their source but the names are written in lower-case letters.

Reasons for copied object classes:

- Existing object class gets a new attribute, e.g. the object "canal bank" gets the new attribute "category of bank".
- Existing object class gets a copied attribute with new values, e.g. the attribute "category of anchorage area" of the object "anchorage area" gets the new values 10 – 12.
- Existing object class shall be symbolized in another way, e.g. top marks.

Reason for new object classes:

- Real world object can not be transferred into the S-57 world.

Reason for copied attributes:

- A new value is needed for an existing attribute.

Reason for new attributes:

- A new attribute with new values is needed.

Procedure with copied object classes and attributes:

The original object classes (i. e. RESARE) and attributes remain in the Presentation Library in order to enable the presentation of older charts. In the data production for Inland ECDIS only the copied object classes (i. e. resare) and attributes are used.

The Integer Codes for the copied and new object classes and attributes have to be registered at the "Open ECDIS Forum" at www.openecdis.org

1.3 Conventions used in this document for types

bold lower case

new and copied object classes and attributes,
new values to attributes.

UPPER CASE

old objects and attributes (already existing in S-57 Ed. 3.0 and used without any changes in Inland ECDIS)

lower case

old values to attributes

Object Classes

COPIED GEO OBJECT CLASS

Object class Anchor berth

ACRONYM **achbtrt** Code: **17000**

Set Attribute_A: **catach; clsdng; comctn; DATEND; DATSTA; NOBJNM; OBJNAM; PEREND; PERSTA; RADIUS; restrn; STATUS;**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A designated area of water where a single vessel, sea plane, etc... may anchor.

References:

INT 1: IN 11.1-2;

M-4: 431.2;

Remarks:

In general the anchor berth is defined by the centre point and a swinging circle.

Distinction: anchorage area; berth; mooring/warping facility;

Object Classes

COPIED GEO OBJECT CLASS

Object class Anchorage area

ACRONYM achare Code: 17001

Set Attribute_A: **catach; clsdng; comctn; DATEND; DATSTA; NOBJNM; OBJNAM; PEREND;**
PERSTA; restrn; STATUS;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

An area in which vessels anchor or may anchor. (IHO Dictionary, S-32, 5th Edition, 130)

References:

INT 1: IN 12.1-9;

M-4: 431.3;

Remarks:

Distinction: anchor berth; berth, mooring/warping facility;

Object Classes

COPIED GEO OBJECT CLASS

Object class Berth

ACRONYM **berths** Code: **17010**

Set Attribute_A: **catbrt; clsdng; comctn; DATEND; DATSTA; DRVAL1; NOBJNM; OBNAM; PEREND; PERSTA; QUASOU; SOUACC; STATUS; trshgd;** verdat

Set Attribute_B: INFORM; NINFOM; NTXTDSC; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A named or numbered place where a vessel is moored at a wharf. (IHO Dictionary, S-32, 5th Edition, 470)

References:

INT 1: IF 19;

M-4: 321.1;

Remarks:

Distinction: anchor berth; anchorage area, mooring/warping facility;

Object Classes

COPIED GEO OBJECT CLASS

Object class Bridge

ACRONYM **bridge** Code: **17011**

Set Attribute_A: **catbrg; comctn; COLOUR; COLPAT; CONDTN; CONRAD; CONVIS; DATEND; DATSTA; HORACC; HORCLR; NATCON; NOBJNM; OBJNAM; TIMEND; TIMSTA; VERACC; VERCCL; VERCLR; VERCOP; verdat**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A structure erected over a depression or an obstacle such as a body of water, railroad, etc. to provide a roadway for vehicles, pedestrians or to carry utility services. (IHO Dictionary, S-32, 5th Edition, 544)

References:

INT 1: ID 20, 21, 22, 23.1-6, 24;

M-4: 381.1-3;

Remarks:

A bridge may consist of portions which cover the land and the water. The bridge supports are encoded as pylon/bridge supports (PYLONS).

Distinction: bridge area, pylon/bridge support

Object Classes

COPIED GEO OBJECT CLASS

Object class	Cable overhead
--------------	----------------

ACRONYM **cblohd** Code: **17012**

Set Attribute_A: CATCBL; CONDTN; CONRAD; CONVIS; DATEND; DATSTA; ICEFAC;
NOBJNM; OBJNAM; STATUS; VERACC; VERCLR; VERCSA; **verdat**;

Set Attribute_B: INFORM; NINFOM; NTXTDS; SCAMIN; TXTDSC. **updmsg**;

Set Attribute_C: RECDAT; RECIND; SORDAT; SORIND;

Definition:

An overhead cable is an assembly of wires or fibres, or a wire rope or chain, which is supported by structures such as poles or pylons and passing over or nearby navigable waters. (Hydrographic Service, Royal Australian Navy).

References:

INT 1: ID 26, 27

M-4: 382; 382.1-2;

Remarks:

The cable supports are encoded as power transmission pylon/pole (PYLONS).

Distinction: cable area; cable, submarine; conveyor; pylon/bridge support;

Object Classes

COPIED GEO OBJECT CLASS

Object class Canal bank

ACRONYM canbnk Code: 17002

Set Attribute_A: **catbnk**; CONRAD; DATEND; DATSTA; NATSUR; NOBJNM; OBJNAM;

Set Attribute_B: INFORM; NINFOM; NTXTDSC; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute C: SORIND; SORDAT

Definition:

The limit line between the water area of a canal and the land area.

References:

INT 1; IF 40;

M-4: 361.6;

Remarks:

Distinction: canal; coastline; lake shore; river bank; shoreline construction;

Object Classes

COPIED GEO OBJECT CLASS

Object class Depth area

ACRONYM **depare** Code: 17003

Set Attribute_A: DRVAL1; DRVAL2; eleva1; eleva2; wtdis; QUASOU; SOUACC; verdat

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A depth area is a water area whose depth is within a defined range of values.

References:

Remarks:

Object Classes

COPIED GEO OBJECT CLASS

Object class Distance mark

ACRONYM **dismar** **Code:** **17004**

Set Attribute_A: **catdis**; DATEND; DATSTA; NOBJNM; OBJNAM;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute C: SORIND; SORDAT

Definition:

A distance mark indicates the distance measured from an origin and consists of either a solid visible structure or a distinct location without special installation. Usually found on canals and rivers.

References:

INT 1: IF 40;

M-4: 361.3; 307;

Remarks:

Distinction: beacon, special purpose;

Object Classes

COPIED GEO OBJECT CLASS

Object class Ferry route

ACRONYM **feryrt** Code: **17013**

Set Attribute_A: **catfry; comctn; DATEND; DATSTA; NOBJNM; OBJNAM; PEREND; PERSTA; STATUS; TIMEND; TIMSTA**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A route in a body of water where a ferry crosses from one shoreline to another. (Digital Geographic Information Working Group, Oct.87)

References:

INT 1: IM 50, 51;
M-4: 438.1, 438.2;

Remarks:

Object Classes

COPIED GEO OBJECT CLASS

Object class Harbour Area

Set Attribute_A: **cathbr; comctn; NOBJNM; OBJNAM; STATUS; unlocd**

Set Attribute_B: INFORM; NINFOM; NTXTDSC; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

The term "harbour" applies only to the area of water with the works necessary for its formation, protections and maintenance (International Maritime Dictionary, 2d. Edition).

A harbour area not only covers the area of water but also the area of land which supplies the harbour installations.

References:

Remarks:

Distinction: port area, harbour basin, terminal, berths

Object Classes

COPIED GEO OBJECT CLASS

Object class	Harbour Facilities
--------------	--------------------

ACRONYM **hrbfac** Code: **17015**

Set Attribute_A:
PEREND;
PERSTA; STATUS;

Set Attribute_B: INFORM; NINFOM; NTXTDS; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A harbour installation with a service or commercial operation of public interest.

References:

Remarks:

Distinction: small craft facilities

Object Classes

COPIED GEO OBJECT CLASS

Object class	Lock Basin
--------------	------------

ACRONYM **lokbsn** Code: **17016**

Set Attribute_A: HORACC; **horcll**; **horclw**; HORLEN; HORWID; NOBJNM; OBJNAM;
STATUS; TIMEND; TIMSTA

Set Attribute_B: INFORM; NINFOM; NTXTDS; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A lock basin is a wet dock in a waterway, permitting a ship to pass from one level to another
(adapted from IHO Dictionary, S-32, 5th Edition, 2881)

References:

Remarks:

Distinction: Lock area, lock basin part

Object Classes

COPIED GEO OBJECT CLASS

Object class	Radio calling-in point
--------------	------------------------

ACRONYM rdocal Code: 17017

Set Attribute_A: **catcom; comctn; COMCHA; DATEND; DATSTA; NOBJNM; OBJNAM; ORIENT; PEREND; PERSTA; STATUS; TRAFIC; dirimp**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

Also called radio reporting points, they have been established in certain busy waterways and port approaches to assist traffic control. On passing these points or crossing a defined line vessels are required to report on VHF to a Traffic Control Centre. (adapted from IHO Chart Specifications, M-4):

References:

INT 1: IM 40;

M-4: 488:

Remarks:

The attribute ‘orientation’ (ORIENT) encodes the orientation of the traffic flow at that point.

Distinction: radio station; pilot boarding place;

Object Classes

COPIED GEO OBJECT CLASS

Object class Restricted area

ACRONYM **resare** **Code:** **17005**

Set Attribute_A: CATREA; DATEND; DATSTA; NOBJNM; OBJNAM; PEREND; PERSTA;
restrn; STATUS;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A specified area designated by an appropriate authority within which navigation is restricted in accordance with certain specified conditions. (adapted from IHO Dictionary, S-32, 5th Edition, 4366)

References:

INT 1: IL 3; IN 2.1-2, 20-22, 25-26, 31, 34;
M-4: 431.4; 439.2-4; 441.8; 445.2; 448.1-2; 449.5;

Remarks:

Distinction: anchorage area; cable area; caution area; dumping ground; depth area; fair-way; dredged area; deep water route; military practice area; pipeline area; swept area;

Object Classes

COPIED GEO OBJECT CLASS

Object class River bank

ACRONYM rivbnk Code: 17006

Set Attribute_A: **catbnk**; CONRAD; NATSUR; NOBJNM; OBJNAM;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

The limit line between the water area of a river and the area of land.

References:

INT 1: IC 20, 21;

M-4: 353.1-4:

Remarks:

Distinction: canal bank; coastline; river; shoreline construction;

Object Classes

COPIED GEO OBJECT CLASS

Object class Signal station traffic

ACRONYM **sistat** **Code:** **17007**

Set Attribute_A: **catsit**; COMCHA; DATEND; DATSTA; **dirimp**; NOBJNM; OBJNAM;
PEREND; PERSTA; STATUS;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute C: SORIND; SORDAT

Definition:

A signal station is a place on shore from which signals are made to ships at sea. (IHO Dictionary, S-32, 5th Edition, 4742)

Traffic signal stations regulate the movement of traffic. (IHO Chart Specifications, M-4)

References:

INT 1: IT 21-25.2;

M-4: 495.1-5;

Remarks:

This object class is used to describe the function of the signal station rather than the structure on which the station is sited.

Distinction: signal station, warning;

Object Classes

COPIED GEO OBJECT CLASS

Object class Signal station warning

ACRONYM **sistaw** Code: **17008**

Set Attribute_A: **catsiw; COMCHA; DATEND; DATSTA; NOBJNM; OBJNAM; PEREND; PERSTA; STATUS;**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A signal station is a place on shore from which signals are made to ships at sea. (IHO Dictionary, S-32, 5th Edition, 4742)

References:

INT 1: IT 20, 26, 28-36;

M-4: 490.3; 494.1-2; 496.1-3; 497;

Remarks:

This object class is used to describe the function of the signal station rather than the structure on which the station is sited.

Distinction: signal station, traffic;

Object Classes

COPIED GEO OBJECT CLASS

Object class	Top Mark
--------------	----------

ACRONYM **topmar** Code: **17009**

Set Attribute_A: COLOUR; COLPAT; HEIGHT; **marsys**; STATUS; TOPSHP; VERACC;
verdat; VERLEN;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A characteristic shape secured at the top of a buoy or beacon to aid in its identification. (IHO Dictionary, S-32, 5th Edition, 5548)

References:

INT 1: IQ 9;

M-4: 463.1;

Remarks:

The body carrying the topmark is a separate object.

Distinction: beacon, waterway; buoy, waterway

Object Classes

COPIED META OBJECT CLASS

Object class	Navigational system of marks
--------------	------------------------------

ACRONYM **m_nsyst** Code: **17018**

Set Attribute_A: **marsys; ORIENT**

Set Attribute_B: INFORM; NINFOM; NTXTDS; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

An area within which a specific system of navigational marks applies and/or a common direction of buoyage.

References:

INT 1: IQ 130-130.6;

M-4: 461.1-4;

Remarks:

Object Classes

NEW GEO OBJECT CLASS

Object class	Beacon water-way
--------------	------------------

ACRONYM **bcnwtw** Code: **17060**

Set Attribute_A: BCNSHP; **catwwm**; COLOUR; COLPAT; CONDTN; CONRAD; CONVIS;
DATEND; DATSTA; **dirimp**; ELEVAT; HEIGHT; **marsys**; NATCON;
NOBJNM;
OBJNAM; PEREND; PERSTA; STATUS; VERACC; **verdat**; VERLEN;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A beacon is a prominent specially constructed object forming a conspicuous mark as a fixed aid to navigation or for use in hydrographic survey (IHO Dictionary, S-32, 5th Edition, 420).

A beacon water way signs a river or canal itself or any obstructions in or at the river or canal.

References:

Remarks:

Object Classes

NEW GEO OBJECT CLASS

Object class Bridge area

ACRONYM **brgare** Code: **17053**

Set Attribute A: comctn; NOBJNM; OBJNAM

Set Attribute B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsq**

Set Attribute_C: SORIND; SORDAT

Definition:

A bridge area covers the entire area, in which the bridge itself and any bridge traffic regulations are located.

References:

Remarks:

Distinction: bridge, notmrk, TSRLPT

Object Classes

NEW GEO OBJECT CLASS

Object class Bunker station

ACRONYM **bunsta** Code: **17054**

bunves, catbun, comctn; NOBJNM; OBJNAM, TIMEND, TIMSTA

Set Attribute B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsq**

Set Attribute C: SORIND; SORDAT

Definition:

A station, at which a ship is able to bunker fuel, water or ballast

References:

Remarks:

Object Classes

NEW GEO OBJECT CLASS

Object class	Buoy water-way
--------------	----------------

ACRONYM **boywtw** Code: **17061**

Set Attribute_A: BOYSHP; **catwwm**; COLOUR; COLPAT; CONDTN; CONRAD; CONVIS;
DATEND; DATSTA; **marsys**; NATCON; NOBJNM;
OBJNAM; PEREND; PERSTA; STATUS; VERLEN;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A buoy is a floating object moored to the bottom in a particular place, as an aid to navigation or for other specific purposes. (IHO Dictionary S-32 5th Edition, 565).

A buoy water way signs the fairway of a river or canal, any obstructions in the river or canal, turn offs, junctions, harbour entries or bridges.

References:

Remarks:

Object Classes

NEW GEO OBJECT CLASS

Object class	Communication Area
--------------	--------------------

ACRONYM **comare** Code: **17055**

Set Attribute_A: **catcom**; COMCHA; DATEND; DATSTA; NOBJNM; OBJNAM; STATUS;
 TIMEND

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

Indicates the coverage of an area, in which a vessel has to report or may request information.

References:

Remarks:

Distinction:

Object Classes

NEW GEO OBJECT CLASS

Object class	Harbour Basin
--------------	---------------

ACRONYM **hrbbsn** Code: **17056**

Set Attribute_A: HORACC; HORLEN; HORWID; NOBJNM; OBJNAM; STATUS;

Set Attribute_B: INFORM; NINFOM; NTXTDS; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

An enclosed area of water surrounded by quay walls constructed to provide means for the transfer of cargos from and to ships (International Maritime Dictionary, 2d. Edition).

References:

Remarks:

Distinction: port area, harbour area, terminal, berths

Object Classes

NEW GEO OBJECT CLASS

Object class Lock area

ACRONYM **lokare** Code: **17057**

Set Attribute_A: comctn; NOBJNM; OBJNAM; STATUS;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A lock area covers the entire area, in which the lock basins and any lock support are located.

References:

Remarks:

Distinction: Lock basin, lock basin part

Object Classes

NEW GEO OBJECT CLASS

Object class	Lock basin part
--------------	-----------------

ACRONYM **lkbspt** Code: **17058**

Set Attribute_A: HORACC; **horcll**; **horclw**; HORLEN; HORWID; NOBJNM; OBJNAM;
STATUS; TIMEND; TIMSTA

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A lock basin is divided into several lock basin parts, if this lock basin has one ground level but several gates.

References:

Remarks:

Distinction: Lock area, Lock basin

Object Classes

NEW GEO OBJECT CLASS

Object class Notice mark

ACRONYM **notmrk** **Code:** **17050**

Set Attribute_A: **catnmk; fnctnm; dirimp; disipd; disipu; disbk1; disbk2; addmrk; marsys;**
ORIENT; CONDTN; NOBJNM; OBJNAM; STATUS;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

to be amended

References:

Remarks:

Distinction:

Object Classes

NEW GEO OBJECT CLASS

Object class	Port Area
--------------	-----------

ACRONYM **prtare** Code: **17059**

Set Attribute_A: **comctn**; NOBJNM; OBJNAM; STATUS; **unlocd**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

Apart from harbours a port includes a city or borough with accommodation and facilities for landing passengers and goods and some amount of overseas trade. A port may possess a harbour but a harbour is not necessarily a port (International Maritime Dictionary, 2d. Edition).

References:

Remarks:

Distinction:

harbour area, harbour basin, terminal, berths

Object Classes

NEW GEO OBJECT CLASS

Object class Refuse dump

ACRONYM refdmp Code: 17062

Set Attribute_A: **catrfd; comctn; NOBJNM; OBJNAM; STATUS; TIMEND; TIMSTA;**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

At a refuse dump ships are able to unload their refuse like waste oil or black water.

References:

Remarks:

Object Classes

NEW GEO OBJECT CLASS

Object class	Route planning point
--------------	----------------------

ACRONYM **rtpipt** Code: **17063**

Set Attribute_A: NOBJNM; OBJNAM;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A route planning point describes the projection of a feature object onto the waterway axis.

References:

Remarks:

Object Classes

NEW GEO OBJECT CLASS

Object class	Terminal
--------------	----------

ACRONYM **termnl** Code: **17064**

Set Attribute_A: **cattml; comctn; NOBJNM; OBJNAM; TIMEND; TIMSTA; trshgd; STATUS; unlocd**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A terminal covers that area on shore which provides buildings and constructions for the transfer of cargos from and to ships.

References:

Remarks:

Distinction: port area, harbour area, harbour basin, berths

Object Classes

NEW GEO OBJECT CLASS

Object class	Turning basin
--------------	---------------

ACRONYM **trnbsn** Code: **17065**

Set Attribute_A: HORCLR; NOBJNM; STATUS; OBJNAM

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

An area of water or enlargement of a channel used for turning vessels (International Maritime Dictionary, 2d Edition)

References:

Remarks:

Object Classes

NEW GEO OBJECT CLASS

Object class	Waterway axis
--------------	---------------

ACRONYM **wtwaxs** Code: **17051**

Set Attribute_A: **catccl**; NOBJNM; OBJNAM;

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

The waterway axis can be defined by e.g:

- the middle line of a fairway,
(Definition of fairway: That part of a river, harbour; etc. where the main navigable channel for vessels of larger size lies. It is also the usual course followed by vessels entering or leaving harbours, called 'ship channel'. (International Maritime Dictionary, 2nd Ed.)
- the middle line of a water way
(Definition of waterway: The waterway covers the entire area of a river or canal)

References:

Remarks:

The object name indicates the specific name of a public waterway/or part of waterway.

Object Classes

NEW GEO OBJECT CLASS

Object class	Waterway profile
--------------	------------------

ACRONYM **wtwprf** Code: **17052**

Set Attribute_A: **wtwdis**; HEIGHT; **verdat**

Set Attribute_B: INFORM; NINFOM; NTXTDS; PICREP; SCAMIN; TXTDSC; **updmsg**

Set Attribute_C: SORIND; SORDAT

Definition:

A waterway profile is a physically non-existent line which is normally the connection of two opposite distance marks. Waterway profiles can be used to define a special water level.

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Category of Anchorage area
-----------	----------------------------

ACRONYM **catach** Code: **17000**

Attribute type: L

Expected input:

ID	Meaning	
1:	unrestricted anchorage	
2:	deep water anchorage	IN 12.4;431.3;
3:	tanker anchorage	IN 12.5;431.3;
4:	explosives anchorage	IN 12.7;431.3;
5:	quarantine anchorage	IN 12.8;431.3;
6:	sea-plane anchorage	IN 14; 449.6;
7:	small craft anchorage	
8:	small craft mooring area	IQ 44; 431.7;
9:	anchorage for periods up to 24 hours	IN 12.6;431.3;
10:	push tow anchorage	
11:	anchorage for other vessels than push tows	
12:	anchorage for other vessels than dangerous cargo vessels	

Definitions:

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Category of bridge
-----------	--------------------

ACRONYM **catbrg** Code: **17006**

Attribute type: L

Expected input:

ID	Meaning	
1:	fixed bridge	ID 22
2:	opening bridge	ID 23.1
3:	swing bridge	ID 23.2
4:	lifting bridge	ID 23.3
5:	bascule bridge	ID 23.4
6:	pontoon bridge	ID 23.5
7:	draw bridge	ID 23.6
8:	transporter bridge	ID 24
9:	footbridge	
10:	viaduct	
11:	aqueduct	
12:	suspension bridge	

Definitions:

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Category of distance mark
-----------	---------------------------

ACRONYM **catdis** Code: **17001**

Attribute type: E

Expected input:

ID	Meaning	
1:	distance mark not physically installed	IF 40;
2:	visible mark, pole	IF 40;
3:	visible mark, board	IF 40;
4:	visible mark, unknown shape	IF 40;
5:	kilometre mark, waterway bank	
6:	hectometre mark, waterway bank	
7:	kilometre mark, waterway axis	
8:	hectometre mark, waterway axis	

Definitions:

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Category of ferry
-----------	-------------------

ACRONYM **catfry** Code: **17007**

Attribute type: L

Expected input:

ID	Meaning	INT 1
1:	'free-moving' ferry	IM 50
2:	cable ferry	IM 51
3:	ice ferry	
4:	swinging wire ferry	

Definitions:

References:

Remarks:

The attribute `category of ferry` does not encode the various types of ferry vessel, but the manoeuvrability of the ferry. The value `cable ferry` indicates a ferry that follows a fixed route guided by a cable. A cable ferry may hinder the flow of other traffic.

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Category of harbour facilities
-----------	--------------------------------

ACRONYM **cathaf** Code: **17008**

Attribute type: L

Expected input:

ID	Meaning	
1-3:	deleted values (see new object class termnl)	
4-5	deleted values (see new object class hrbare)	
6	naval base	
7-8	deleted values (see new object class termnl)	
9:	ship yard	
10-11:	deleted values (see new object class termnl)	
12:	harbour master's office	IF60
13:	pilot office	
14:	water-police office	
15:	customs office	IF61
16:	service and repair	
17:	quarantine station	IF62.1

Definitions:

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute Category of signal station traffic

ACRONYM **catsit**

Attribute type: L

Expected input:

ID	Meaning	INT1
1:	port control	IT 23;
2:	port entry and departure	
3:	International Port Traffic	IT 21
4:	berthing	
5:	dock	
6:	lock	IT 24
7:	flood barrage	
8:	bridge passage	IT 25.1
9:	dredging	
10:	oncoming traffic indication	

Definitions:

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute Category of signal station warning

Code: 17003

Attribute type: L

Expected input:

ID	Meaning	INT1
1:	danger	IT 35
2:	maritime obstruction	
3:	cable	
4:	military practice	IT 36
5:	distress	IT 26
6:	weather	IT 29
7:	storm	IT 28
8:	ice	IT 30
9:	time	IT 31
10:	tide	IT 33
11:	tidal stream	IT 34
12:	tide gauge	IT 32.2
13:	tide scale	IT 32.1
14:	diving	
15:	high water mark	
16:	vertical clearance indication	
17:	over/under vertical clearance indication	
18:	depth indication	

Definitions:

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Marks navigational – System of
-----------	--------------------------------

ACRONYM **marsys** Code: **17009**

Attribute type: E

Expected input:

ID	Meaning	INT1
1:	IALA A	IQ 130
2:	IALA B	IQ130
9:	no system	
10:	other system	
11:	EU Inland waterway	

Definition:

to be amended

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Restriction
-----------	-------------

ACRONYM **restrn** **Code:** **17004**

Attribute type: L

Expected input:

ID	Meaning	
1:	anchoring prohibited	IN 20
2:	anchoring restricted	
3:	fishing prohibited	IN 21
4:	fishing restricted	
5:	trawling prohibited	
6:	trawling restricted	
7:	entry prohibited	IN 2.2
8:	entry restricted	
9:	dredging prohibited	
10:	dredging restricted	
11:	diving prohibited	
12:	diving restricted	
13:	no wake	
14:	area to be avoided	IM 29.1
15:	construction prohibited	
16:	overtaking prohibited	
17:	passing prohibited	
18:	standstill prohibited	
19:	standstill restricted	
20:	berthing prohibited	
21:	berthing restricted	
22:	turning prohibited	
23:	empty	
24:	speed limited	
25:	restricted fairway depth	
26:	restricted fairway width	

Definitions:

References:

Remarks:

Attributes

COPIED OBJECT ATTRIBUTES

Attribute	Vertical datum
-----------	----------------

ACRONYM **verdat** Code: **17005**

Attribute type: E

Expected input:

ID : Meaning

...

- 30. Equivalent height of water (German GIW)**
- 31. Highest Shipping Height of Water (German HSW)**
- 32. Amsterdam Ordinance Datum (NAP)**
- 33. current waterlevel**
- 34. RNW for the German Danube**
- 35. RNW for the Danube Commission**
- 36. HSW (Highest Shipping Height of Water) for the Danube**
- 37. Heigth above the Adriatic sea**

Definition:

to be amended

References:

to be amended

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Additional mark
-----------	-----------------

ACRONYM addmrk Code: 17050

Attribute type: L

Expected input:

ID:	Meaning
1:	top (board)
2:	bottom (board)
3:	right (triangle to the right)
4:	left (triangle to the left)

Definition:

The kind and location of an additional mark at a notice mark

References:

Remarks:

Distinction: notmrk

Attributes

NEW OBJECT ATTRIBUTES

Attribute Bunker vessel, availability

ACRONYM **bunves** **Code:** **17065**

Attribute type: E

Expected input:

ID: Meaning

- 1: bunker vessel available
2: no bunker vessel available

Definition:

The availability of a bunker vessel at a bunker station

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of bank
-----------	------------------

ACRONYM **catbnk** Code: **17051**

Attribute type: E

Expected input:

ID:	Meaning
1:	steep bank
2:	flat bank
3:	embankment, fastened
4:	embankment, unfastened

Definition:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of berth
-----------	-------------------

ACRONYM **catbrt** Code: **17066**

Attribute type: L

Expected input:

- | ID: | Meaning |
|-----|--|
| 1. | loading |
| 2. | unloading |
| 3. | overnight accommodation |
| 4. | push tow berths |
| 5. | berths for other vessels than push tows |
| 6. | berths for other vessels than dangerous cargo vessels |

Definition:

References:

Remarks:

Distinction: transshipment goods

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of bunker station
-----------	----------------------------

ACRONYM **catbun** Code: **17067**

Attribute type: L

Expected input:

ID	Meaning
1:	diesel oil
2:	water
3:	ballast

Definitions:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of CEMT class
-----------	------------------------

ACRONYM **catccl** Code: **17068**

Attribute type: L

Expected input:

ID	Meaning
1:	0 small vessels and pleasure craft
2:	I peniche
3:	II campine barge
4:	III Dortmund-Ems barge
5:	IV Rhine-Herne barge
6:	Va Large Rhine barge; 1-barge push-tow unit
7:	Vb 2-barge push-tow unit; long formation
8:	Vla 2-barge push-tow unit; wide formation
9:	Vlb 4-barge push-tow unit
10:	Vlc 6-barge push-tow unit
11:	No CEMT class

Definitions:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of communication
-----------	---------------------------

ACRONYM **catcom** Code: **17069**

Attribute type: L

Expected input:

ID	Meaning
1:	VTS centre
2:	VTS sector
3:	IVS point
4:	MID
5:	lock
6:	bridge
7:	custom
8:	harbour

Definitions:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute Category of harbour area

ACRONYM **cathbr** **Code:** **17070**

Attribute type: L

Expected input:

ID	Meaning
1:	custom harbour
2:	port of refuge
3:	yacht harbour/marina
4:	fishing harbour
5:	private harbour

Definitions:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of notice mark
-----------	-------------------------

Attribute type: E

Expected input:

ID	:	Meaning
1:		entry prohibited, (A.1)
2:		closed area, but small craft boats without engine permitted (A.1a, only RheinSchPV and Binnenvaartpolitiereglement)
3:		overtaking prohibited, (A.2)
4:		overtaking between push tows and towing units prohibited, (A.3)
5:		no passing and overtaking, (A.4)
6:		berthing prohibited, (A.5)
7:		berthing, with distance from the bank, (A.5.1)
8:		anchoring prohibited, (A.6)
9:		making fast to the bank prohibited, (A.7)
10:		turning prohibited, (A.8)
11:		avoid wave wash, (A.9)
12:		passing on left side prohibited, (A.10)
13:		passing on right side prohibited, (A.10)
14:		boats with engine prohibited, (A.12)
15:		sport and pleasure boats prohibited, (A.13)
16:		waterskiing prohibited, (A.14)
17:		sailing boats prohibited, (A.15)
18:		boats without engines or sails prohibited, (A.16)
19:		windsurfing prohibited, (A.17)
20:		waterscooters and jetskis prohibited, (A.20)
21:		highspeed motorboats prohibited (A.18)
22:		slipping of boats prohibited, (A.19)
23:		mandatory traffic direction, left, (B.1)
24:		mandatory traffic direction, right, (B.1)
25:		mandatory change of the fairwayside to port, (B.2a)
26:		mandatory change of the fairwayside to starboard, (B.2b)
27:		port fairwayside is mandatory traffic direction, (B.3a)
28:		starboard fairwayside is mandatory traffic direction, (B.3b)
29:		mandatory crossing of the fairwayside to port, (B.4a)
30:		mandatory crossing of the fairwayside to starboard, (B.4b)
31:		mandatory stop, (B.5)
32:		maximum speed limit, (B.6)
33:		mandatory sound signal, (B.7)
34:		special attention, (B.8)
35:		give way to other vessels when entering the main fairway, (B.9a)
36:		give way to other vessels when crossing the main fairway, (B.9b)
37:		mandatory radiophone, (B.11)

- 38: restricted fairway depth, (C.1)
39: restricted vertical clearance, (C.2)
40: restricted width of the fairway or passage, (C.3)
41: general restrictions (with additional sign), (C.4)
42: restricted width of the waterway at the left bank, (C.5)
43: restricted width of the waterway at the right bank, (C.5)
44: recommended passage for both directions, (D.1a)
45: recommended passage for only one direction, (D.1b)
46: recommended passage on right side, (D.2)
47: recommended passage on left side, (D.2)
48: recommended traffic direction, left; (D.3)
49: recommended traffic direction, right, (D.3)
50: entry permitted, (E.1)
51: overhead power line crossing, (E.2)
52: weir, (E.3)
53: cable ferry, (E.4)
54: ferry, (E.4b)
55: berthing permitted, (E.5)
56: berthing permitted, with distance, (E.5.1)
57: berthing permitted, between two distances, (E.5.2)
58: maximum number of vessels laying side by side, (E.5.3)
59: berthing facilities for push tows, (E.5.4)
60: berthing facilities for push tows with one blue cone, (E.5.5)
61: berthing facilities for push tows with two blue cones, (E.5.6)
62: berthing facilities for push tows with three blue cones, (E.5.7)
63: berthing facilities for other vessels than push tows, (E.8)
64: berthing facilities for other vessels than push tows with one blue cone, (E.5.9)
65: berthing facilities for other vessels than push tows with two blue cones, (E.5.10)
66: berthing facilities for other vessels than push tows with three blue cones, (E.5.11)
67: berthing facilities for all vessels (E.5.12)
68: berthing facilities for all vessels with one blue cone, (E.5.13)
69: berthing facilities for all vessels with two blue cones, (E.5.14)
70: berthing facilities for all vessels with three blue cones, (E.5.15)
71: anchoring permitted, (E.6)
72: making fast to the bank permitted, (E.7)
73: facilities for transfer of vehicles, (E.7.1.)
74: turning permitted, (E.8)
75: crossing with secondary waterway ahead, (E.9a)
76: secondary waterway ahead on the right, (E.9b)
77: secondary waterway ahead on the left, (E.9c)
78: secondary waterway ahead (main waterway right), (E.9d)
79: secondary waterway ahead (main waterway left), (E.9e)
80: secondary waterway left (main waterway right), (E.9f)
81: secondary waterway right (main waterway left) (E.9g)
82: secondary waterway ahead and left (main waterway right), (E.9h)
83: secondary waterway ahead and right (main waterway left), (E.9i)
84: crossing with main waterway ahead, (E.10a)
85: junction with main waterway ahead, (E.10b)
86: junction with main waterway ahead and right, (E.10.c)
87: junction with main waterway ahead and left, (E.10d)
88: junction with main waterway ahead and right (secondary waterway left), (E.10e)
89: junction with main waterway ahead and left (secondary waterway right), (E.10f)

- 90: **end of prohibition or regulation, (E.11)**
- 91: **drink water (E.13)**
- 92: **telephone (E.14)**
- 93: **boats with engine permitted (E.15)**
- 94: **sport and pleasure boats permitted, (E.16)**
- 95: **waterski area, (E.17)**
- 96: **sailing boats permitted, (E.18)**
- 97: **boats without engine or sails permitted, (E.19)**
- 98: **windsurfing permitted, (E.20)**
- 99: **nautical radio information, (E.23)**
- 100: **waterscooters, jetskis permitted, (E.24)**
- 101: **high speed motorboats permitted, (E.21)**
- 102: **slipping of boats permitted, (E.22)**

Definition:

References: All order numbers are referenced to CEVNI (European Code for Inland Waterways) revision 2, edited by the Economic Commission for Europe of the United Nations, 2001.

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of refuse dump
-----------	-------------------------

ACRONYM **catrfd** Code: **17071**

Attribute type: L

Expected input:

ID	Meaning
1:	cargo residue/slop
2:	waste oil
3:	gray/black water
4:	domestic refuse

Definitions:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Category of terminal
-----------	----------------------

ACRONYM **cattml** Code: **17072**

Attribute type: L

Expected input:

ID	Meaning	INT1
1:	Passenger terminal	
2:	Ferry terminal	IF10
3:	Tansshipment terminal	
4:	RoRo terminal	

Definitions:

A terminal provides facilities for handling particular forms of cargo (IHO Dictionary, S-32, 5th Edition, 5343).

References:

Remarks:

Distinction: transshipment goods

Attributes

NEW OBJECT ATTRIBUTES

Attribute Category of waterway mark (buoy, beacon)

ACRONYM catwwm

Code: 17112

Attribute type: E

Expected input:

ID	:	Meaning
1:		right side
2:		left side
3:		separation
4:		right fairway side
5:		left fairway side
6:		fairway separation
7:		fairway at the right side
8:		fairway at the left side
9:		fairway change to the right side
10:		fairway change to the left side
11:		obstruction at the right side
12:		obstruction at the left side
13:		turn off at the right side
14:		turn off at the left side
15:		junction at the right side
16:		junction at the left side
17:		harbour entry at the right side
18:		harbour entry at the left side
19:		bridge mark

Definition:

References:

This list is referenced to the German Rheinschiffahrts-Polizeiverordnung (RheinSchPV) and Wasserstraßen-Verkehrsordnung (WVO) of Republic of Austria.

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Class of dangerous cargo
-----------	--------------------------

ACRONYM **clsdng** Code: **17055**

Attribute type: E

Expected input:

ID	:	Meaning
1	:	one blue light/cone
2	:	two blue lights/cones
3	:	three blue lights/cones
4	:	no blue lights/cones

Definition:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Communication
-----------	---------------

ACRONYM **comctn** Code: **17073**

Attribute type: S

Expected input:

all kinds of communication, e.g. phone or fax number, email, address etc.

Definition:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Direction of impact
-----------	---------------------

ACRONYM **dirimp** Code: **17056**

Attribute type: L

Expected input:

ID	:	Meaning
1	:	upstream
2	:	downstream
3	:	to the left bank
4	:	to the right bank

Definition:

Direction of the impact of an area, which is signed by notice marks.

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Distance from bank, first
-----------	---------------------------

ACRONYM **disbk1** Code: **17057**

Attribute type: F

Definition:

Minimum distance of the impact of an area, which is signed by notice marks. The distance is measured from the notice mark rectangular to the bank.

References:

Minimum value: 0

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)

Resolution: 1 metre

Format:

xx

Example:

30

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Distance from bank, second
-----------	----------------------------

ACRONYM **disblk2** Code: **17058**

Attribute type: F

Definition:

Maximum distance of the impact of an area, which is signed by notice marks. The distance is measured from the notice mark rectangular to the bank.

References:

Minimum value: 0

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)
Resolution: 1 metre

Format:

XX

Example:

50

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Distance of impact, upstream
-----------	------------------------------

ACRONYM **disipu** Code: **17059**

Attribute type: F

Definition:

Upstream distance of the impact of an area, which is signed by notice marks. The distance is normally given on an additional mark left and/or right of the notice mark.

References:

Minimum value: **0**

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)

Resolution: 1 metre

Format:

xxx

Example:

100

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute Distance of impact, downstream

ACRONYM **disipd** Code: **17060**

Attribute type: F

Definition:

Downstream distance of the impact of an area, which is signed by notice marks. The distance is normally given on an additional mark left and/or right of the notice mark.

References:

Minimum value: 0

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)
Resolution: 1 metre

Format:

xxx

Example:

100

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Elevation 1
-----------	-------------

ACRONYM eleva1 Code: 17061

Attribute type: F

Definition:

Elevation 1 of a depth area

References:

Minimum value: **0.00**

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)
Resolution: 0.01 metre

Format:

xxx,xx

Example:

12.34

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Elevation 2
-----------	-------------

ACRONYM eleva2 Code: 17062

Attribute type: F

Definition:

Elevation 2 of a depth area

References:

Minimum value: **0.00**

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)
Resolution: 0.01 metre

Format:

xxx-xx

Example:

1234

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Function of notice mark
-----------	-------------------------

ACRONYM **fnctnm** Code: **17063**

Attribute type: E

Expected input:

ID	:	Meaning
1	:	prohibition mark
2	:	regulation mark
3	:	restriction mark
4	:	recommendation mark
5	:	information mark

Definition:

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute Horizontal clearance, length

ACRONYM **horcII**

Code: 17074

Attribute type: F

Definition:

The length of an object, such as a lock or basin, which is available for safe navigation. This may, or may not, be the same as the total physical length (HORLEN) of the object

References:

Minimum value: 0

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)
Resolution: 0.1 metres

Format:

xxx.x

Example:

125.1 for a width of 125.1 metres.

Remarks:

Distinction: HORLEN

Attributes

NEW OBJECT ATTRIBUTES

Attribute Horizontal clearance, width

ACRONYM **horclw** Code: **17075**

Attribute type: F

Definition:

The width of an object, such as a lock or basin, which is available for safe navigation. This may, or may not, be the same as the total physical width (HORWID) of the object.

References:

Minimum value: 0

Indication:

Unit: defined in the HUNI subfield of the DSPM record or in the HUNITS attribute of the M_UNIT meta object class, e.g. metre (m)
Resolution: 0.1 metres

Format:

xxx.x

Example:

125.1 for a width of 125.1 metres.

Remarks:

Distinction: HORWID

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Transshipping goods
-----------	---------------------

ACRONYM **trshgd** Code: **17076**

Attribute type: L

Expected input:

ID:	Meaning
1:	containers
2:	bulk goods
3:	oil
4:	fuel
5:	chemicals
6:	liquid goods
7:	explosive goods
8:	fish
9:	cars
10:	general cargo

Definition:

The kind of goods which are transferred from and to ships

References:

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	UN Location Code
-----------	------------------

ACRONYM **unlocd** **Code:** **17077**

Attribute type: S

Definition:

For locations the UN CEFACt Recommendation 16 (UN LOCODE - unique identification of locations and harbours) is proposed for use wherever possible for places and harbours.

For terminals 5 digits are added to identify the terminals within a harbour.

References:

The UN locodes can be obtained from the Internet (www.unece.org/locode).

The terminal codes are available at Bureau Telematica in the Netherlands

Indication:

Format:

UN LOCODE: Alphanumeric, 5 digits

Terminal code: Alphanumeric, 5 digits, always in combination with UNLOCODE

Example:

UN LOCODE of Bingen:

UN LOCODE and terminal code of ECT Duisburg: DEDUIECTDU

Remarks:

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Update message
-----------	----------------

ACRONYM **updmsg** Code: **40000**

Attribute type: S

Expected input:

Definitions:

Textual update information about an object

References:

Remarks:

The attribute `update message` can be used to inform the mariner about the reason for an update or special warnings referring to the object.

Attributes

OBJECT ATTRIBUTES

Attribute	National update message
-----------	-------------------------

ACRONYM **nupdms** Code: **40020**

Attribute type: S

Expected input:

Definitions:

Textual update information about an object in national language

References:

Remarks:

The attribute `update message` can be used to inform the mariner about the reason for an update or special warnings referring to the object.

Attributes

NEW OBJECT ATTRIBUTES

Attribute	Waterway distance
-----------	-------------------

ACRONYM **wtwdis** Code: **17064**

Attribute type: F

Definition:

The distance measured from an origin of a river or canal.

References:

Minimum value: 0

Indication:

Unit: kilometres
Resolution: 0.1

Format:

XXX.X

Example:

523.4 for a waterway distance of 523.4 km.

Remarks:

7 Overview of Inland ECDIS Object Classes and Attributes

Object class description	Acronym	Code	Page
Anchor berth	achbrt	17000	22
Anchorage area	achare	17001	23
Berth	berths	17010	24
Bridge	bridge	17011	25
Cable overhead	cblohd	17012	26
Canal bank	canbnk	17002	27
Depth area	depare	17003	28
Distance mark	dismar	17004	29
Ferry route	feryrt	17013	30
Harbour Area	hrbare	17014	31
Harbour Facilities	hrbfac	17015	32
Lock Basin	lokbsn	17016	33
Radio calling-in point	rdocal	17017	34
Restricted area	resare	17005	35
River bank	rivbnk	17006	36
Signal station traffic	sistat	17007	37
Signal station warning	sistaw	17008	38
Top Mark	topmar	17009	39
Navigational system of marks	m_nsyst	17018	40
Beacon water-way	bcnwtw	17060	41
Bridge area	brgare	17053	42
Bunker station	bunsta	17054	43
Buoy water-way	boywtw	17061	44
Communication Area	comare	17055	45
Harbour Basin	hrbbsn	17056	46
Lock area	lokare	17057	47
Lock basin part	lkbspt	17058	48
Notice mark	notmrk	17050	49
Port Area	prtare	17059	50
Refuse dump	refdmp	17062	51
Route planning point	rtplpt	17063	52
Terminal	termnl	17064	53
Turning basin	trnbsn	17065	54
Waterway axis	wtwaxs	17051	55
Waterway profile	wtwprf	17052	56
Attribute description			
Category of Anchorage area	catach	17000	57
Category of bridge	catbrg	17006	58
Category of distance mark	catdis	17001	59
Category of ferry	catfry	17007	60
Category of harbour facilities	cathaf	17008	61
Category of signal station traffic	catsit	17002	62
Category of signal station warning	catsiw	17003	63
Marks navigational – System of	marsys	17009	64
Restriction	restrn	17004	65
Vertical datum	verdat	17005	66

Additional mark	addmrk	17050	67
Bunker vessel	bunves	17065	68
Category of bank	catbnk	17051	69
Category of berth	catbrt	17066	70
Category of bunker	catbun	17067	71
Category of CEMT class	catccl	17068	72
Category of communication	catcom	17069	73
Category of harbour area	cathbr	17070	74
Category of notice mark	catnmk	17052	75
Category of refuse dump	catrfd	17071	78
Category of terminal	cattml	17072	79
Category of waterway mark	catwwm	17112	80
Class of dangerous cargo	clsdng	17055	81
Communication	comctn	17073	82
Direction of impact	dirimp	17056	83
Distance from bank	disbk1	17057	84
Distance from bank	disbk2	17058	85
Distance of impact, upstream	disipu	17059	86
Distance of impact, downstream	disipd	17060	87
Elevation 1	eleva1	17061	88
Elevation 2	eleva2	17062	89
Function of notice mark	fnctnm	17063	90
Horizontal clearance, length	horcll	17074	91
Horizontal clearance, width	horclw	17075	92
Transshipping goods	trshgd	17076	93
UN Location Code	unlocd	17077	94
Update message	updmsg	40000	95
National update message	nupdms	40020	96
Waterway distance	wtwdis	17064	97

8 List of additional used S-57 Object Attributes

-A-

-B-

-C-

COLOUR	Colour
COMCHA	Communication channel
CONDTN	Condition
CONRAD	Conspicuous, radar
CONVIS	Conspicuous, visually

-D-

DATEND	Date end
DATSTA	Date start

-E-

EXPSOU	Exposition of sounding
--------	------------------------

-F-

-G-

-H-

HORACC	Horizontal accuracy
HORCLR	Horizontal clearance
HORLEN	Horizontal length
HORWID	Horizontal width

-I-

INFORM	Information
--------	-------------

-J-

-K-

-L-

-M-

NATCON	Nature of construction
--------	------------------------

-O-

OBJNAM	Object name
ORIENT	Orientation

-P-

PEREND	Periodic date end
PERSTA	Periodic date start
PICREP	Pictorial representation

-Q-

QUASOU	Quality of sounding measurement
--------	---------------------------------

-R-

RECDAT	Recording date
RECIND	Recording indication

-S-
SCAMIN Scale minimum
SOUACC Sounding accuracy
SORDAT Source date
SORIND Source indication
STATUS Status

-T-
TXTDSC Textual description
TIMEND Time end
TIMSTA Time start
TRAFIC Traffic flow

-U-

-V-
VERACC Vertical accuracy
VERCLR Vertical clearance
VERCCL Vertical clearance, closed
VERCOP Vertical clearance, opened
VERCSA Vertical clearance, safe
VERLEN Vertical length

Additional National Language Attributes

NINFOM Information in national language
NOBJNM Object name in national language
NTXTDS Textual description in national language

Page 102 intentionally left free

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Waterways

Inland ECDIS

SECTION 2

Inland ECDIS Data Standard

Annex A of Appendix A Codes for Producers and Waterways

In addition to

IHO –S-57 IHO Codes

Codes for IHO Members (extract from IOH-S-57, Appendix A, Annex A)

Country Name	Country Code	Producer Name	Producer	Code
Belgium	BE	Antwerpse Zeediensten Hydrografie 1)	30	BE
Germany	DE	Bundesamt fuer Seeschiffahrt und Hydrographie 1)	180	DE
France	FR	Service Hydrographique et Océanographique de la Marine 1)	170	FR
Netherlands	NL	Dienst der Hydrografie Koninklijke Marine	310	NL

1) only for maritime purposes

Codes for Non-IHO Members

Country Name	Country Code	Producer Name	Producer	Code
Netherlands	NL	Rijkswaterstaat	7979	1R
Austria	A	Austrian Supreme Shipping Authority	12096	2W
Germany	DE	Wasser- und Schifffahrtsverwaltung des Bundes	7984	1W
Switzerland	CH	Bundesamt für Wasser und Geologie		

Codes for Waterways

Waterway Name	Waterway Code	Remark
Danube	D0	Km 0 – 1000 (with Sulina branch)
Danube	D1	Km 1000 – 2000
Danube	D2	Km 2000 -Source
Danube	D3	Chilia branch
Danube	D4	Cernavoda canal
Neckar	NE	
Main	MA	
Mosel	MO	
Elbe	EL	
Rhine	RH	
Nederrijn / Lek	RL	
Waal	WA	

If a private company decides to produce ENCs, it shall register a producer code with the “Open ECDIS Forum” at www.openecdis.org.

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 2

Data Standard for Inland ECDIS

Appendix B

Product Specification for Inland ECDIS

in addition to the

IHO-S-57 ENC Product Specification

Contents

1	General.....	107
2	Additions to the ENC Product Specification of IHO	107
to 2.1	Navigational purpose (usage)	107
to 2.2	Cells.....	107
to 3.3	Objects permitted for use in ENC and their geometric primitives.....	107
to 3.4	Meta objects	108
to 3.5.2	Mandatory attributes	108
to 3.7	Time varying objects.....	108
to 3.10	Depth area	108
to 4.1	Horizontal datum	108
to 5.6.3	Data set files.....	110
to 6.3.2.1	Data set identification field.....	110

1 General

This Product Specification for Inland ECDIS is a set of specifications intended to enable ENC manufacturers to produce consistent Inland ENC, and to use data efficiently in an ECDIS application that satisfies the Performance Standards for Inland ECDIS (Section 1 of this Standard for Inland ECDIS). An Inland ENC shall be produced in accordance with the regulations defined in these documents:

- this Product Specification for Inland ECDIS
- Annex A "Use of the Object Catalogue for Inland ECDIS"
- Appendix B.1 to the Standard IHO-S-57 ("ENC Product Specification")
- the documents, that are listed as references in Section 1 of this Standard for Inland ECDIS in clause 2.

2

Definitions of the used terms may be found in Section 5 ("Glossary of Terms") of this standard.

The numbering correlates to S-57 Appendix B.1.

2 Additions and Clarifications to the "ENC Product Specification" of the IHO

Further to 2.1 Navigational purpose (usage)

Nr.	Navigational purpose (usage)	Intended use
1 S57	Overview	For route planning and oceanic crossing.
2 S57	General	For navigating oceans, approaching coasts and route planning.
3 S57	Coastal	For navigating along the coastline, either inshore or offshore.
4 S57	Approach	Navigating the approaches to ports or major channels or through intricate or congested waters.
5 S57	Harbour	Navigating within ports, harbours, bays, rivers and canals, for anchorages.
6 S57	Berthing	Detailed data to aid berthing.
7 new	River	<i>Navigating the inland waterways (skin cell).</i>
8 new	River harbour	<i>Navigating within ports and harbours on inland waterways (skin cell).</i>
9 new	River berthing	<i>Detailed data to aid berthing manoeuvring in inland navigation (skin cell).</i>
L new	Overlay	<i>Overlay cell to be displayed in conjunction with skin cells</i>

The navigational purposes 1 to 8 and 9 may be used by authorities as well as private bodies. Navigational purpose 9 should be used by private bodies only.

It is allowed to assign a range of usages to overlay cells (see "to 5.6.3").

Further to 2.2 Cells

In Inland ENCs, skin-of-the-earth objects (group 1) within two overlapping cells with the same navigational purpose must not overlap. Objects of overlay cells (always group 2) are allowed to overlap other objects in other cells.

The minimum size of coverage at both sides of the waterway should be outside the radar coverage.

Further to 3.3 Objects permitted for use in ENC and their geometric primitives

The following object classes were copied for use in Inland ENC.

achare	P	A		
cblcoh		L		
feryrt		L	A	
m_nsys			A	
sistat	P			
achbtrt	P	A		
canbnk		L		
hrbare			A	
rdocal	P	L		
sistaw	P			
berths	P	L	A	
depare			A	
hrbfac	P		A	
resare			A	
topmar	P			
bridge	P	L	A	
dismar	P			
lokbsn			A	
rivbnk		L		

Table 3.1

P = point, L = line, A= area

The official object classes **CANBNK** and **RIVBNK** are existing in S-57 but their application is not permitted any more.

The copied object class **depare** may only be applied if it shall be updated to the current waterlevel.

The following object classes were added for use in Inland ENC.

bcnwtw	P			
comare			A	
notmrk	P			
termnl	P		A	
brgare			A	
hrbbsn			A	
prtare			A	
trnbsn	P		A	
boywtw	P			
locare			A	
refdmp	P			
wtwaxs		L		
bunsta	P			
lkbspt			A	
rtplpt	P			
wtwprf		L		

The application of the waterway axis object class **wtwaxs** (waterway axis) with the object **dismar** (distance mark) is mandatory.

Further to 3.4 Meta objects

The meta object **m_nsys** with the attribute **marsys** (to indicate the system of navigational marks) must provide an exhaustive non-overlapping coverage of the part of the cell containing data.

Further to 3.5.2 Mandatory attributes

The following attributes are mandatory for object classes, which were

- added for use in Inland ENC (new) or

- which already exist and have been extended for use in Inland ECDIS (copied):

Object class	Attribute					
bcnwtw	catwwm	BCNSPH	COLOUR			
bcnwtw	catwwm	BOYSHP	COLOUR			
bridge	if fixed if not fixed	VERCLR VERCCL	VERCOP			
cblohd	VERSCHA	or if this is unknown	VERCLR			
depare	DRVAL1	DRVAL2				
dismar	if located on axis	INFORM				
feryrt	catfry					
hrbfac	cathaf					
lkbspt	horcll	horclw				
lokbsn	horcll	horclw				
rdocal	dirimp					
sistat	catsit					
sistaw	catsiw					
notmrk	fnctnm	catnmk	dirimp		ORIENT ¹⁾	
topmar	marsys	TOPSHP				
wtwaxs	OBJNAM					

¹⁾ if fixed at a bridge

Further to 3.7 Time varying objects

The Inland ENC may contain time independent depth information as "minimum required depth" (Solltiefe in German) related to a reference waterlevel (on the Rhine river the "Equivalent Water Level" GIW).

Besides that Inland ECDIS may also contain time-variable depth information related to the actual water level at reference gauges. The rules for this will be formulated in an update of this standard when sufficient experience is gained.

To 3.10.1 Depth area

Depth area (depare) is part of group one (skin of the earth)

Further to 4.1 Horizontal datum


The horizontal datum of an Inland ENC shall be WGS-84. In the case that the data are transformed to WGS-84 from a local datum the responsible authority shall define the area where the local transformation parameters apply. Within this area, the difference between transformed coordinates and the surveyed WGS-84 coordinates may not exceed 0.5 m. For approval purposes, the responsible authority shall define appropriate reference points (surveyed WGS-84 coordinates) preferably exactly at the limit line of two adjacent areas. Reference points, transformation parameters and the algorithm shall be published and shall be the basis for Inland ENC production for that area.

To 5.6.3 Data set files

A valid data set file must be uniquely identified world wide by its name.

The data set files are named according to the specifications given below:

CCP_{RR}R_{DDD}.EEE



The main part forms an eight-character identifier where:

- The first two characters (CC) identify the producer. This list is given in Section 2, Appendix A, Annex A (Codes for Producers and Waterways).
- The third character (P) indicates the navigational purpose (see clause 2.1 of the IHO Product Specification). The letter "L" (in the position "usage") indicates, that the cell is displayed as overlay over other cells within a range of usages. Overlay cells may not contain skin-of-the-earth objects. The range of usages of overlay cells is indicated in the Data Set Identification Field of the header of the overlay cell (see S57, Part 3, Data Structure, ch. 7.3.1.1). The 8th bit of the intended usage subfield (INTU) has to be set if a range is used, and the other seven bits describe the range (e.g. 79 means a range from usage 7 to usage 9).
- The fourth and fifth characters (RR) identify the waterway. (This list is also given in Section 2, Appendix A, Annex A).
- The sixth to eighth characters (DDD) are used for the waterway distance, e.g. if the cell covers the stretch from km 640 to km 650 the string will be "640".

The primarily produced base cell file has the extension (EEE) 000.

The extension is used for updating. Update cell files have the same name as the original base cell file, with an extension number greater than or equal to 001. They cover the same geographical area as the base cell file to which they apply.

To 6.3.2.1 Data set identification field

Inland ENCs are considered as an independent product besides ENCs. To recognise a S-57 dataset as an Inland ENC the content of following two subfields has to be changed.

tag	subfield name	use	value	comment
PRSP	Product Specification	M	{10}	= European InlandENC, binary
PRED	Product Specification Edition Number	M	1.02	=ASCII

* This is the edition number of the Inland ECDIS Standard

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 2

Data Standard for Inland ECDIS

Annex A of Appendix B

Use of the Object Catalogue for Inland ENC

in addition to the

IHO-S-57 document
"Use of the Object Catalogue"

Contents

1	General	113
2	Additions and Clarifications to the IHO Document "Use of the Object Catalogue"	114
to:		
4.4.1	Distance marks.....	114
4.4.2	Waterway axis	114
4.4.3	Waterway profile	114
4.4.4	Route planning point.....	114
4.5.3	Banks.....	114
4.6.1	Harbour facilities	115
4.6.2	Berths	116
4.6.3	Harbour offices	116
4.6.6.4	Gates (lock gates flood control gates)	116
4.6.7.3	Pontoons.....	116
4.6.12	Bunker stations	116
4.6.13	Refuse dumps	117
4.7.6	Rivers.....	117
4.8.1	Canals.....	117
4.8.10	Bridges.....	117
4.8.21	Signs and notice boards/marks	118
4.8.22	Locks	120
9.1.1	Administrative harbour areas.....	122
9.1.2	Harbour basin	122
10.2.6	Two-way routes	123
10.3	Ferries.....	124
11.1	Restricted areas in general.....	124
11.5.2	Overhead cables.....	124
11.6.3	Overhead pipelines.....	125
11.15.1	Achorage area (more ships)	125
11.15.2	Anchor berth (1 ship)	125
11.16	Turning basin.....	125
12.2	Buoyage system and direction of buoyage	126
12.3.1	Beacons.....	126
12.4.1	Buoys	126
12.6	Topmarks.....	126
12.12.	Radar conspicuous objects	126
12.13	Radio reporting (calling in) points	126
12.14	Communication area	127
13.4	Signal stations	127
3	Index of Object Classes:.....	128

1 General

This part of the Standard for Inland ECDIS specifies the conventions that are to be used to encode the geometry and semantic descriptions of each object in an Inland ENC.

The contents of an Inland ENC are at the discretion of the producing manufacturer provided that the regulations of the Standard for Inland ECDIS and by it of this document "Use of the Object Catalogue" are followed.

Chapter 2 of this document contains the additions and clarifications further to the IHO publication 'Use of the Object Catalogue for ENC' (S-57 Appendix B.1, Annex A) for Inland ECDIS (see References in Section 1, clause 2.2. of this standard for Inland ECDIS). The numbering and the layout correlate to S-57 Appendix B.1, Annex A.

The following printing conventions are used:

- Copied object classes and Attributes from IHO-S-57 upper case **ACRONYM**
- New object classes and Attributes lower case **acronym**
- Object class: bold **ACRONYM**
- Attribute thin **ACRONYM**
 Acronym
- Set_Attributes A: For each object class, the whole list of Attributes of set A is given with the specific values for this feature object.
- Set_Attributes B, Set_Attributes C: Except for attributes INFORM, NINFOM, and more rarely SORDAT, the attributes from sets B and C are not mentioned in the following lists; however, this does not mean that their use is prohibited.

2 Additions and Clarifications further to the IHO Document "Use of the Object Catalogue" for Inland ECDIS

New 4.4.1 Distance marks

There are two different kinds of distance marks, distance marks located at the bank and distance marks located on the waterway axis. Distance marks on the waterway axis have to be geometrically connected with the waterway axis. That means that the spatial object of the distance mark has to be a connected node, which also defines the beginning or end of an edge, which is linked with the waterway axis.

Geo object: distance mark (**dismar**)

Attributes:	catdis	DATEND	DATSTA	NOBJNM	OBJNAM
	INFORM	the value of the distance (for kilometre points without '.0' and for hectometre points only the hectometre number)			

New 4.4.2 Waterway axis

Geo object: waterway axis (**wtwaxs**)

Attributes:	NOBJNM	OBJNAM	INFORM	NINFOM
-------------	--------	--------	--------	--------

New 4.4.3 Waterway profile

Geo object: waterway profile (**wtwprf**)

Attributes:	wtwdis	HEIGHT	VERDAT	NOBJNM	OBJNAM
		INFORM	NINFOM		

New 4.4.4 Route planning point

Geo object: route planning point (**rtpcpt**)

Attributes:	NOBJNM	OBJNAM	INFORM	NINFOM
-------------	--------	--------	--------	--------

A route planning object is the projection of one or more of the following feature objects onto the **wtwaxs** (waterway axis):

achbrt	achare	berths	bridge	BUAARE	bunsta
cblhd	hrbare	hrbsn	lokbsn	lkbspt	prtare
refdmp	termnl	trnbsn			

These feature objects have to be related with their respective **rtpcpt** by creation of a C_ASSO object.

New 4.5.3 Banks

In banks there is no distinction between natural or artificial banks. The nature of the bank, e.g. sand or stones, is encoded with the attribute NATSUR and the kind of bank, e.g. flat coast or embankment is encoded with the attribute catbnk.

New 4.5.3.1 River bank

Geo object: river bank (**rivbnk**)

Attributes:	catbnk	CONRAD	NATSUR	NOBJNM	OBJNAM
		INFORM	NINFOM	SCAMIN	

New 4.5.3.2 Canal banks

Geo object: canal bank (**canbnk**)

Attributes:	catbnk	CONRAD	NATSUR	NOBJNM	OBJNAM
		INFORM	NINFOM	SCAMIN	SORDAT
		SORIND			




Figure 1 – Harbour and transshipping installations

To 4.6.1 Harbour facilities

All kind of terminals are no longer encoded as **hrbfac** but as **termnl** (see 4.6.1.1).

Geo object: harbour facilities (**hrbfac**)

Attributes:	cathaf	CONDTN	DATEND	DATSTA	NATCON
	NOBJNM	OBJNAM	PEREND	PERSTA	STATUS
	INFORM	NINFOM			

New 4.6.1.1 Terminals

Geo object: terminals (**termnl**)

Attributes:	cattml	comctn	CONDTN	DATEND	DATSTA
	NATCON	NOBJNM	OBJNAM	PEREND	PERSTA
	STATUS	INFORM	NINFOM		

A terminal covers the landside area in which all the transshipping facilities and warehouses are located.

To 4.6.2 Berths

Geo object: berth (**berths**)

Attributes:	catbrt	comctn	DATEND	DATSTA	DRVAL1
	NOBJNM	OBJNAM	PEREND	PERSTA	QUASOU
	SOUACC	STATUS	VERDAT	INFORM	NINFOM

Berths may also be located at the river side (see Figure 10).

To 4.6.3 Harbour offices

Harbour offices are no longer encoded as **BUISGL** but as **hrbfac**.

To 4.6.6.4 Gates (lock gates flood control gates)

A gate must be covered by a **DRGARE**.

To 4.6.7.3 Pontoons

Pontoons whose size is not sufficient to create an area object must be encoded as point **SLCONS** with CATSLC=4 (pier/jetty).

New 4.6.11 Ship yards




Figure 2 – ship yards

The production area on shore is always encoded as **hrbfac** with cathaf = 9. The slipways are encoded as **SLCONS** with CATSLC = 13 and the respective WATLEV attribute. The limit line between water and land is encoded as **rivbnk**, **canbnk** or **SLCONS**.

New 4.6.12 Bunker stations

Geo object: bunker station (**bunsta**)

Attributes:	bunves	catbun	comctn	TIMEND	TIMSTA
	NOBJNM	OBJNAM	INFORM	NINFOM	

4.6.13 Refuse dumps

Geo object: berth (**refdmp**)

Attributes:	catdmp	comctn	TIMEND	TIMSTA	NOBJNM
	OBJNAM	INFORM	NINFOM		

To 4.7.6 Rivers

For Inland ECDIS data rivers are mostly navigable at compilation scale. They must be encoded as **DE-PARE** or **DRGARE** and the river banks must be encoded as **rivbnk**. The object class **RIVERS** may only be used for rivers which are not navigable at compilation scale.

To 4.8.1 Canals

For Inland ECDIS data canals are mostly navigable at compilation scale. They must be encoded as **DE-PARE** or **DRGARE** and the canal banks must be encoded as **canbnk**. The object class **CANALS** may only be used for canals which are not navigable at compilation scale.

To 4.8.10 Bridges




Figure 3 - Bridges

New 4.8.10.1 Bridge area

A bridge area covers the entire area, in which the bridge itself, the bridge supports and any bridge traffic regulations are located.

Geo object: bridge area (**brgare**)

Attributes:	comctn	NOBJNM	OBJNAM	INFORM	NINFOM
-------------	--------	--------	--------	--------	--------

New 4.8.10.2 Bridge

Each part of a bridge with different properties, e.g. categories or vertical clearances, has to be encoded as a single bridge object.

Geo object: bridge (**bridge**)

Attributes:	catbrg	comctn	COLOUR	COLPAT	CONDTN
	CONRAD	CONVIS	DATEND	DATSTA	HORACC
	HORCLR	NATCON	NOBJNM	OBJNAM	TIMEND
	TIMSTA	VERACC	VERCCL	VERCLR	VERCOP
	verdat				

notmrk (notice mark) and **TWRPT** (two way route part) shall be used for the indication of traffic direction in navigable waters under bridges. The opening times can be encoded with the attributes **TIMSTA** and **TIMEND**.

New 4.8.10.3 Pylons and bridge supports

Geo object: Pylon / bridge support (**PYLONS**)

Attributes:	CATPYL	COLOUR	COLPAT	CONDTN	CONRAD	CONVIS	DATEND
	DATSTA	HEIGHT	NATCON	NOBJNM	OBJNAM	VERLEN	WATLEV
	INFORM	NINFOM					

Area **PYLONS** must be covered by an area **LNDARE**

New 4.8.21 Signs and notice boards/marks

Notice boards which are used only for inland water navigation have to be encoded as notice marks.

Geo object: notice mark (**notmrk**)

Attributes:	catnmk	fncnmk	dirimp	disipd	disipu
	disbk1	disbk2	addmrk	ORIENT	CONDTN
	NOBJNM	OBJNAM	STATUS	INFORM	NINFOM

Normally a pair of notice marks describes an area. To define this area the direction of impact and the distances are used, which are normally given by additional marks. For notice marks on bridges the attribute **ORIENT** has to be used as well, to rotate the symbol according the orientation of the bridge. The value of **ORIENT** at bridges should correspond to the prescribed heading of the vessels.

Table 1 - Notice marks and their related areas:

code number	Point / Area	Area of impact	Area Feature object	Area Feature attributes	remarks
A1	P				at bridges or locks
A1	A		resare	restrn = 1	
A2-A4	A	bank to bank	resare	restrn = 16,17	
A5-A7	A	bank to fairway	resare	restrn = 1,18	
A8-A9	A	bank to bank	resare	restrn = 20,13	
A10	P				only at bridges (ORIENT)
A13-A18	P				
B1-B5	P				
B6	A	bank to bank	resare	restrn = 21	
B7-B11	P				
C1-C3	A		resare	restrn = 22,23	
C4	P,A				depending on add. inform.
C5	A	bank to distance	resare	restrn = 7	distance given on notmrk
D1-D2	P				only at bridges (ORIENT)
D3	P				
E1	P				only at bridges (ORIENT)
E2-E4	P				
E.5	A		berths, achare	clsndg, catach, clsndg	berthing area; symbolization by an „anchor“ or „circle with the number of the berthing area“
E.6	A		achare	catach, clsndg	anchoring
E.7	A		berths	catbrt,clsndg	making fast to the bank
E.8	A		trnbsn		
E.9-E.14	P				
E.15-E.22	A	bank to fairway	CTNARE	INFORM	

Table 2 - Notice marks at bridges (see Figure 3):

no	fnctnm	catnmk	addmrk	dirimp	disipu	disipd	disbk1	disbk2	ORIENT
1	recom. = 2	D1b = 45	-	-	-	-	-	-	90
2	proh. = 1	A1 = 1	-	-	-	-	-	-	90

Table 3 - Notice marks at restricted areas (see Figure 10):

no	fnctnm	catnmk	addmrk	dirimp	disipu	disipd	disbk1	disbk2	INFORM
1	regul. = 2	B11 = 37	4	downstr.	-	-	-	-	VHF 11
2	restr. = 3	C5 = 42,43	4	downstr.	-	120	-	40	-
3	proh. = 1	A6 = 8	-	-	-	-	-	-	-
4	inform. = 5	E11 = 90	-	-	-	-	-	-	-
5	proh. = 1	A2 = 4	-	downstr.	-	-	-	-	-
6	regul. = 2	B6 = 32	3	downstr.	-	-	-	-	6 km/h
7	inform. = 5	E17 = 95	4	upstr.	-	-	-	-	-
8	inform. = 5	C4 = 41	3	downstr.	-	-	-	-	-

Table 4 - Notice marks at anchorages and berths (see Figure 11):

no	fnctnm	catnmk	addmrk	dirimp	disipu	disipd	disbk1	disbk2	INFORM
1	inform. = 5	C4 = 41	2,3	upstr.	-	-	-	-	Reede
2	inform. = 5	E5.4 = 59	3	upstr.	200	-	-	-	-
3	inform. = 5	E5.4 = 59	4	downstr.	-	200	-	-	-
4	inform. = 5	E5.9 = 64	2,3	upstr.	-	-	30	80	-
5	inform. = 5	E5.9 = 64	2,4	downstr.	-	-	40	90	-
6	inform. = 5	C4 = 41	2,4	downstr.	-	-	-	-	Reede

New 4.8.22 Locks




Figure 4 - locks

New 4.8.22.1 Lock area

The lock area covers the entire area in which all lock buildings are located.

Geo object: lock area (**lokare**)

Attributes:	comctn	NOBJNM	OBJNAM	STATUS	INFORM
	NINFOM				

New 4.8.22.2 Lock basin

Geo object: lock basin (**lokbsn**)

Attributes:	HORACC	horcll	horclw	HORLEN	HORWID
	NOBJNM	OBJNAM	STATUS	INFORM	NINFOM

The lock basin must be covered by a depth area (DEPARE) with depth = waterway fairway depth. The horizontal length and width (HORLEN and HORWID) are the physical distances given by the building itself. The usable horizontal clearance of length and width (horcll and horclw) are distances which are provided by the competent authority for safe navigation. The opening times can be encoded with the attributes **TIM-STA** and **TIMEND**.

New 4.8.22.3 Lock basin part

If a lock basin has more than two gates and the ground level is the same, than different lock basin parts must be created.

Geo object: lock basin part (**lkbspt**)

Attributes:	HORACC	horcll	horclw	HORLEN	HORWID
	NOBJNM	OBJNAM	STATUS	INFORM	NINFOM

The lock basin part must be covered by a DEPARE.

To 5 Depths

As long as depths shall not be updated to the current water level the object class DEPARE must be used to encode depths. The object class **depare** is only to be used when time variable depths below actual water levels are needed. The object class **depare** is a part of Group 1.

Geo object: Depth area (**depare**)

Attributes:	DRVAL1	DRVAL2	eleva1	eleva2	verdat
	wtwdis	QUASOU	INFORM		NINFOM

The attributes eleva1 and eleva2 are used to define the elevation of the bottom of a river or canal. The attribute **verdat** only applies to the attributes **eleva1** and **eleva2**. The attribute **wtwdis** is used for the application of any water level models.




Figure 5 – port area




Figure 6 – harbour area

To 9.1.1 Administrative harbour areas

New 9.1.1.1 Port Area

Geo object: port area (**prtare**)

Attributes:	comctn	NOBJNM	OBJNAM	STATUS	INFORM
	NINFOM				

New 9.1.1.2 Harbour Area

Geo object: harbour area (**hrbare**)

Attributes:	cathbr	comctn	NOBJNM	OBJNAM	STATUS
	INFORM	NINFOM			

The port area covers the entire area of a city's harbour areas, harbour basins, terminals and harbour facilities. Normally it applies only to big international ports.

New 9.1.2 Harbour basin

Geo object: harbour basin (**hrbbsn**)

Attributes:	HORACC	HORLEN	HORWID	NOBJNM	OBJNAM
	STATUS	INFORM	NINFOM		

A harbour basin is bordered by shoreline constructions and the entrance to the basin.

To 10.2.6 Two-way routes

A two-way route in inland waterways regulates the flow of traffic at bridges or fairway separations.




Figure 7 - Two-way route part at bridges




Figure 8 - Two-way route part at bridges




Figure 9 – Two-way route parts at a fairway separation

Geo object: Two-way route part (**TWRTPT**)

Attributes: CATTRK DATEND DATSTA DRVAL1 ORIENT QUASOU
SOUACC STATUS TECSOU TRAFIC INFORM NINFOM

A two-way route part in front of or behind a bridge should be at least as long as the fairway is wide.

To 10.3 Ferries

Geo object: Ferry route (**ferryrt**)

Attributes:	catfry	comctn	DATEND	DATSTA	NOBJNM	OBJNAM
	PEREND	PERSTA	STATUS	INFORM	NINFOM	




Figure 10 – Restricted Areas in general

To 11.1 Restricted areas in general

If the restriction is a special inland waterway restriction the object class **resare** has to be used.

Geo object: restricted area (**resare**)

Attributes:	CATREA	DATEND	DATSTA	NOBJNM	OBJNAM
	PEREND	PERSTA	restrn	STATUS	INFORM
				NINFOM	

To 11.5.2 Overhead cables

If the cables have a special inland water vertical datum the object class **cblohd** has to be used.

Geo object: Cable overhead (**cblohd**)

Attributes:	CATCBL	CONDTN	CONRAD	CONVIS	DATEND	DATSTA	ICEFAC
	NOBJNM	OBJNAM	STATUS	VERACC	VERCLR	VERCSA	verdat
	INFORM						

To 11.6.3 Overhead pipelines

If the cables have a special inland water vertical datum the object class PIPOHD has to be used.

Geo object: Pipeline overhead (PIPOHD)

Attributes:	CATPIP	CONDTN	CONRAD	CONVIS	DATEND	DATSTA	NOBJNM
	OBJNAM	PRODCT	STATUS	VERACC	VERCLR	verdat	INFORM
	NINFORM						

New 11.15 Berthing areas




Figure 11 –berthing areas

New 11.15.1 Anchorage area (more ships)

Geo object: Anchorage area (**achare**)

Attributes:	catach	clsndg	DATEND	DATSTA	NOBJNM
	OBJNAM	PEREND	PERSTA	RESTRN	STATUS
	INFORM	NINFOM			

New 11.15.2 Anchor berth (1 ship)

Geo object: Anchor berth (**achbrt**)

Attributes:	catbrt	clsndg	DATEND	DATSTA	NOBJNM
	OBJNAM	PEREND	PERSTA	RESTRN	STATUS
	INFORM	NINFOM			

New 11.16 Turning basin

Geo object: Turning basin (**trnbsn**)

Attributes: HORCLR NOBJNM OBJNAM INFORM NINFOM

To 12.2 Buoyage system and direction of buoyage

The buoyage system and, where necessary, the direction of buoyage are encoded with the meta object **m_nsys**.

Meta object: Navigational system of marks (**m_nsys**)

Attributes: marsys ORIENT INFORM NINFOM

To 12.3.1 Beacons

Inland waterway beacons are encoded as **bcnwtw**.

Geo objects: Beacon waterway (**bcawtw**)

Attributes:	BCNSHP	catwwm	COLOUR	COLPAT	CONDTN
	CONRAD	CONVIS	DATEND	DATSTA	ELEVAT
	HEIGHT	marsys -	NATCON	NOBJNM	OBJNAM
	PEREND	PERSTA	STATUS	VERLEN	INFORM
					NINFOM

The attribute marsys may only be defined if it is different to the value encoded in **m_nsys**.

To 12.4.1 Buoys

Inland waterway buoys are encoded as **boywtw**.

Geo objects: Buoy waterway (**boywtw**)

Attributes:	BOYSHP	catwwm	COLOUR	COLPAT	CONRAD
	DATEND	DATSTA	marsys -	NATCON	NOBJNM
	OBJNAM	PEREND	PERSTA	STATUS	INFORM
					NINFOM

The attribute marsys may only be defined if it is different to the value encoded in **m_nsys**.

12.6 Topmarks

Geo object: Topmark (**topmar**)

Attributes: COLOUR COLPAT marsys STATUS TOPSHP INFORM NINFOM

To 12.12 Radar conspicuous objects

For the use of radar matching systems the following object classes have to be defined as radar conspicuous:

bcnwtw	bridge	boywtw	cblohd	canbnk	FLODOC
PYLONS	rivbnk	SLCONS			

To 12.13 Radio reporting (calling in) points

Geo object: Radio calling-in point (**rdocal**)

Attributes: catcom COMCHA DATEND DATSTA NOBJNM OBJNAM ORIENT
PEREND PERSTA STATUS TRAFIC INFORM NINFOM

To 12.14 Communication area

Geo object: Communication area (**comare**)

Attributes: catcom COMCHA DATEND DATSTA NOBJNM OBJNAM
STATUS TRAFIC INFORM

To 13.4 Signal stations

Signal stations which control the traffic are encoded as **sistat**, e. g. lock signals or wahrschau signals.

Geo object: signal station, traffic (**sistat**)

Attributes: catsit
COMCHA DATEND DATSTA NOBJNM OBJNAM PEREND PERSTA
STATUS INFORM NINFOM

Signal stations where the skipper gets information on the conditions which influence his voyage, e.g. water levels, weather in general, are encoded as signal stations, warning **sistaw**.

Geo object: signal station, warning (**sistaw**)

Attributes: catsiw
COMCHA DATEND DATSTA NOBJNM OBJNAM PEREND PERSTA
STATUS INFORM NINFOM

The building housing the service is encoded as a **BUISGL** or **LNDMRK**.

3 Index of Object Classes:

A

achare..... 114, 119, 125
achbrt..... 114, 125

B

bcnwtw..... 126, 127
berths..... 114, 116
boywtw..... 126, 127
brgare..... 118
bridge..... 114, 118, 127
BUAARE..... 114
BUISGL..... 116, 127
bunsta..... 114, 117

C

canbnk..... 115, 116, 117, 127
cblcoh..... 114, 124, 125, 127
comare..... 127

D

depare..... 121
DEPARE..... 117, 127
dismar..... 114
DRGARE..... 116, 117, 121

F

feryrt..... 123
FLODOC..... 127

H

hrbare..... 114, 122
hrbsn..... 114, 122
hrbfac..... 115, 116

L

lkbspt..... 114, 121
LNDARE..... 118
LNDMRK..... 127
lokare..... 120
lokbsn..... 114, 121

M

m_nsys..... 126

N

notmrk..... 118

P

pipohd..... 125
prtare..... 114, 122
PYLONS..... 118, 127

R

rdocal..... 127
refdmp..... 114, 117
resare..... 119, 125
rivbnk..... 115, 116, 117, 127
RIVERS..... 117
rtplpt..... 114

S

sistat..... 127
sistaw..... 127
SLCONS..... 116, 122, 127

T

termnl..... 114, 115
topmar..... 126
trnbsn..... 114, 119, 126
TWRPT..... 118, 123

W

wtwaxs..... 114
wtwprf..... 114

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 3

Presentation Standard for Inland ECDIS

Contents

Presentation Standard

Appendix A Presentation Library for Inland ECDIS

Presentation Standard

1. This "Presentation Standard for Inland ECDIS" describes the standard to be used for the presentation of Inland ECDIS data. The presentation has to take place in such a way that none of the information is lost.
2. This Presentation Standard is based on the document "S-52, Specification for Chart Content and Display Aspects of ECDIS" of the IHO, Edition 5.0 of December 1996, with all Appendices and Annexes (see table "Comparison of the structures of the standards for (Maritime) ECDIS and Inland ECDIS" in Section 0 of this Standard for Inland ECDIS).
3. This Presentation Standard describes the necessary additions and clarifications to S-52 and the application of S-52 for the purpose of use in Inland ECDIS applications.
4. This Presentation Standard is organized as follows:
 - this section 2 of the Inland ECDIS Standard,
 - Appendix A "Presentation Library for Inland ECDIS" with additions and clarifications to be applied to S-52, Appendix 2, Annex A.
5. Definitions of terms may be found in
 - IHO-S-57, Part 1, clause 5,
 - the "Glossary of ECDIS-Related Terms" in Appendix 3 to S-52,
 - the "Glossary for Inland ECDIS" in Section 5 of this Inland ECDIS Standard.
6. Section 2 (Data Standard), ch. 5 of this Inland ECDIS Standard shall be applied also for the maintenance of this Presentation Standard.

Page 132 intentionally left empty

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 3

Presentation Standard for Inland ECDIS

Appendix A

Presentation Library for Inland ECDIS

In addition to the

IHO-S-52 Presentation Library

Contents

1	Introduction	135
2	Presentation Library (Preslib)	135
2.1	Look-up tables	136
2.2	Symbols	136
2.3	Conditional symbology procedures (CS)	136
2.4	Colours	136
3	Extensions to the Look-up Tables of IHO-S-52	137
3.1	New entries for Inland ECDIS object classes	137
3.1.1	Points	137
3.1.2	Lines	139
3.1.3	Areas	140
3.2	Extended entries for S-57 object classes	141
3.2.1	Areas	141
4	Extensions of conditional symbology procedures (CS)	141
4.1	Top marks	141
4.2	Restricted areas	141
4.3	Lights	141
4.4	Notice marks	141
5	Extensions to the Symbol Library	142
5.1	New symbols to be shown on the chart display (simplified point symbols)	142
5.1.1	Raster symbols	142
5.1.2	Vector symbols (must be rotated, the numbers refer to CEVNI)	143
5.2	New symbols to be shown in the "information window on notice marks"	143
6	Presentation of notice marks	145
7	Presentation of objects for radar map matching	146
8	Inland ECDIS symbols	147
8.1	Raster symbols	147
8.1.1	Symbols in general	147
8.1.2	Navigational aids	148
8.1.3	Harbour facilities, terminals	149
8.2	Symbols for the "information window on notice marks"	150
8.3	Vector symbols	155

1 Introduction

S-57 data sets do not contain any information about how it is going to be presented. The chart is generated online in the ECDIS application. For that purpose, the ECDIS application uses machine readable symbolization instructions for each object which are drawn on the screen and form the chart image. The S-52 standard contains all rules which are necessary for the symbolization and presentation of S-57 data on the screen. The symbolization depends on a number of parameters the user may change during runtime. That requires that not only colour and symbol definitions are available but also procedures which allow a dynamic change of presentation.

The ECDIS symbolization also must allow five different levels of brightness in order to cope with different light conditions on the bridge of the ship.

2 Presentation Library (Preslib)

The major components of the presentation library are:

- A library of symbols, line styles and fill styles
- A colour coding scheme which includes the IHO colour tables for day and night time
- A set of symbology command words from which machine readable instructions can be assembled. The result is a symbology instruction which is processed to symbolise S-57 objects in turn.
- A set of conditional symbology procedures to decide the appropriate symbolisation in cases determined by the mariner's selection (e.g. safety contour) or for complex symbols (e. g. topmarks on buoys and beacons)
- A set of look-up tables that link object descriptions from the SENC database to the appropriate symbology instructions depending on whether:
 - a) the link is straight forward, i.e. a direct relationship between an object's description and its presentation such as a buoy or a land area. In this case, the look-up table provides the symbology instruction to show a symbol, an area fill, or a line style.
 - b) the link is conditional, i.e. depending on circumstances, for example a depth area, whose colour fill depends on the choice of the safety contour. In this case the look-up table refers the decision to a conditional symbology procedure that selects the appropriate symbology instructions later.

2.1 Look-up tables

For each geometry type (point, line, area) and its respective symbolization type (for points: traditional and simplified) there is a separate look-up table. Each entry in a look-up table consists of the following fields:

1. 6-character code of the object class (acronym)
2. Attribute combination
3. Symbolization instructions
4. Display priority, 0-9 (comparable with drawing layers)
5. Radar code
6. Display category (Display base, standard, all other)
7. "Viewing group", more refined grouping of objects than the display categories

"LNDMRK","CATLMK17|","SY(TOWERS01)","7","O","OTHER","32250"

Figure 1 - Example entry of a look-up table

In this case the object LNDMRK is shown by the symbol TOWERS01 with priority 7, if the attribute CATLMK equals 17. The object lies over the radar.

In Inland ECDIS, the simplified type of symbolization of points is used only.

The presentation of objects in a specific area, that are contained in different cells of the same usage, follows the entries in the look-up tables.

2.2 Symbols

Symbols can be defined in vector format or in raster format. Symbols which will be rotated must be defined in vector format. The size of vector symbols is adapted automatically to the resolution and size of the screen. In case of raster symbols, different symbol sets must be designed to meet the requirements of a readable display.

2.3 Conditional symbology procedures (CS)

CS are generated for objects of which the symbolization

- depends on application settings, e.g. safety contour,
- depends on other objects, e.g. top marks and their structure,
- is too complex to be defined in a direct look-up table entry.

2.4 Colours

Colours used in an ECDIS are defined in an absolute, monitor independent way (CIE coordinates). This ensures that ECDIS charts look similar on monitors of different suppliers. By means of a colour calibration software which must be used by the manufacturer, CIE values are converted into RGB values. Because of

the different light conditions on the bridge of a ship, it is necessary to offer presentations with different brightness. For each level a separate colour table exists.

3 Extensions to the Look-up Tables of IHO-S-52

3.1 New entries for Inland ECDIS object classes

Points:

"achare","","","SY(ACHARE02)","60","O","STANDARD","26220"
"achbtr","","","SY(ACHBRT07);TX(OBJNAM,3,1,2,'14106',1,0,CHBLK,29)","50","O","STANDARD","26220"
"bcnwtw","","","SY(BCNLAT50);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17020"
"berths","","","SY(BRTHNO01);TX(OBJNAM,1,2,3,'14108',0,0,CHMGD,29)","60","O","STANDARD","22440"
"boywtw","","","SY(BOYDEF03);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","","catwwm4|COLOUR3|","SY(BOYLAT50);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm5|COLOUR4|","SY(BOYLAT51);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm6|COLOUR3,4|","SY(BOYLAT54);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm6|COLOUR4,3|","SY(BOYLAT54);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm7|COLOUR1,3|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm7|COLOUR3,1|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm7|COLOUR3,4,3|","SY(BOYLAT52);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm8|COLOUR1,4|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm8|COLOUR4,1|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm8|COLOUR4,3,4|","SY(BOYLAT53);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm9|COLOUR1,3|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm9|COLOUR3,1|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm9|COLOUR3,4,3|","SY(BOYLAT52);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm10|COLOUR1,4|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm10|COLOUR4,1|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm10|COLOUR4,1,4|","SY(BOYLAT53);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm11|COLOUR1,3|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm11|COLOUR3,1|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm12|COLOUR1,4,1|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm12|COLOUR4,1,4|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm13|COLOUR1,3|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm13|COLOUR3,1|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm13|COLOUR3,4,3|","SY(BOYLAT52);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm14|COLOUR1,4|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm14|COLOUR4,1|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm14|COLOUR4,3,4|","SY(BOYLAT53);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm15|COLOUR1,3|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm15|COLOUR3,1|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm15|COLOUR3,4,3|","SY(BOYLAT52);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm16|COLOUR1,4|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm16|COLOUR4,1|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm16|COLOUR4,3,4|","SY(BOYLAT53);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm17|COLOUR1,3|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm17|COLOUR3,1|","SY(BOYLAT55);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm17|COLOUR3,4,3|","SY(BOYLAT52);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm18|COLOUR1,4|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm18|COLOUR4,1|","SY(BOYLAT56);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm18|COLOUR4,3,4|","SY(BOYLAT53);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","catwwm19|COLOUR6|","SY(boyspp50);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"boywtw","COLOUR6|","SY(boyspp50);TX(OBJNAM,2,1,2,'14106',-1,-1,CHBLK,21)","80","O","DISPLAYBASE","17010"
"bridge","","","SY(BRIDGE01)","80","O","DISPLAYBASE","12210"
"bunsta","","","SY(CHINFO07)","80","O","STANDARD","22410"
"bunsta","catbun1|","SY(BUNSTA01)","80","O","STANDARD","22410"
"bunsta","catbun2|","SY(BUNSTA02)","80","O","STANDARD","22410"

"bunsta","catbun3|","SY(BUNSTA03)","80","O","STANDARD","22410"
"dismar","catdis5|","SY(HECMTR02);TX(INFORM,3,1,2,'14106',1,0,CHMDG,21)","60","O","STANDARD","22430"
"dismar","catdis6|","SY(HECMTR01);TX(INFORM,3,1,2,'14106',1,0,CHMDG,21)","60","O","STANDARD","22430"
"dismar","catdis7|","SY(DISMAR06);TX(INFORM,3,1,2,'14106',1,-1,CHBLK,21)","60","O","OTHER","31050"
"dismar","catdis8|","SY(DISMAR05)","60","O","OTHER","31050"
"hrbfac","","SY(HRBFFAC10)","70","O","STANDARD","22410"
"hrbfac","cathaf6|","SY(HRBFFAC11)","70","O","STANDARD","22410"
"hrbfac","cathaf9|","SY(HRBFFAC12)","70","O","STANDARD","22410"
"hrbfac","cathaf12|","SY(HRBFFAC13)","70","O","STANDARD","22410"
"hrbfac","cathaf13|","SY(HRBFFAC14)","70","O","STANDARD","22410"
"hrbfac","cathaf14|","SY(HRBFFAC15)","70","O","STANDARD","22410"
"hrbfac","cathaf15|","SY(HRBFFAC16)","70","O","STANDARD","22410"
"hrbfac","cathaf16|","SY(HRBFFAC17)","70","O","STANDARD","22410"
"hrbfac","cathaf17|","SY(HRBFFAC18)","70","O","STANDARD","22410"
"notmrk","","SY(NOTMRK02)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk1|","SY(NMKPRH02,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk12|","SY(NMKPRH12,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk13|","SY(NMKPRH13,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk44|","SY(NMKRCD01,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk45|","SY(NMKRCD02,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk46|","SY(NMKRCD03,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk47|","SY(NMKRCD04,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","catnmk50|","SY(NMKINFO1,ORIENT)","80","O","DISPLAYBASE","17030"
"notmrk","fnctnm1|","SY(NOTMRK01)","80","O","DISPLAYBASE","17030"
"notmrk","fnctnm4|","SY(NOTMRK03)","80","O","DISPLAYBASE","17030"
"notmrk","fnctnm5|","SY(NOTMRK03)","80","O","DISPLAYBASE","17030"
"rdocal","","SY(RCLDEF01)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG1|","SY(rdocal02,ORIENT);TX(COMCHA,1,2,2,'14106',0,0,CHMDG,11);TX(OBJNAM,3,2,2,'14106',2,-
2,CHBLK,11)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG2|","SY(rdocal02,ORIENT);TX(COMCHA,1,2,2,'14106',0,0,CHMDG,11);TX(OBJNAM,3,2,2,'14106',2,-
2,CHBLK,11)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG3|","SY(rdocal02,ORIENT);TX(COMCHA,1,2,2,'14106',0,0,CHMDG,11);TX(OBJNAM,3,2,2,'14106',2,-
2,CHBLK,11)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG4|","SY(rdocal03,ORIENT);TX(COMCHA,1,2,2,'14106',0,0,CHMDG,11);TX(OBJNAM,3,2,2,'14106',2,-
2,CHBLK,11)","60","O","DISPLAYBASE","15060"
"refdmp","","SY(REFDMP01)","80","O","STANDARD","22410"
"rtplpt","","","","","","",""
"sistat","","SY(SISTAT02)","70","O","STANDARD","28020"
"sistat","catsit2|","SY(SSENTR01)","70","O","STANDARD","28020"
"sistat","catsit6|","SY(SSLOCK01)","70","O","STANDARD","28020"
"sistat","catsit10|","SY(SSWARS01)","70","O","STANDARD","28020"
"sistaw","","SY(SISTAT02)","70","O","STANDARD","28020"
"sistaw","catsiw12|","SY(WTLVGG02)","70","O","STANDARD","28020"
"sistaw","catsiw13|","SY(WTLVGG01)","70","O","STANDARD","28020"
"sistaw","catsiw15|","SY(HGWWTMK01)","70","O","STANDARD","28020"
"sistaw","catsiw16|","SY(VTCLMK01)","70","O","STANDARD","28020"
"sistaw","catsiw17|","SY(VTCLMK01);SY(WTLVGG02)","70","O","STANDARD","28020"
"termnl","","SY(TERMNL12)","80","O","STANDARD","22420"
"termnl","cattml1|","SY(TERMNL01)","80","O","STANDARD","22420"
"termnl","cattml1|","SY(TERMNL03)","80","O","STANDARD","22420"
"termnl","cattml3|","SY(TERMNL12)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd1|","SY(TERMNL03)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd2|","SY(TERMNL04)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd3|","SY(TERMNL05)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd4|","SY(TERMNL06)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd5|","SY(TERMNL07)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd6|","SY(TERMNL08)","80","O","STANDARD","22420"

"termnl","cattml3|trshgd7|","SY(TERMNL09)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd8|","SY(TERMNL10)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd9|","SY(TERMNL11)","80","O","STANDARD","22420"
"termnl","cattml3|trshgd10|","SY(TERMNL12)","80","O","STANDARD","22420"
"topmar","",","CS(TOPMARI1)","80","O","DISPLAYBASE","17010"
"trnbsn","",","SY(TRNBSN01)","60","O","STANDARD","26020"

Lines

"berths","",","LS(SOLD,3,CHGRD);SY(BRTHNO01);TX(OBJNAM,1,2,3,'14108',1,0,CHMDG,29)","50","O","OTHER","32440"
"bridge","",","LS(SOLD,4,CHGRD);TX(OBJNAM,3,1,2,'24207',1,0,CHBLK,21);TE('clr
%4.1lf','VERCLR',3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","12210"
"bridge","CATBRG2|","LS(SOLD,4,CHGRD);SY(bridge01);TE('clr cl %4.1lf','VERCCL',3,1,2,'24207',1,0,CHBLK,52);TE('clr op
%4.1lf','VERCOP',3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","12210"
"bridge","CATBRG3|","LS(SOLD,4,CHGRD);SY(bridge01);TE('clr cl %4.1lf','VERCCL',3,1,2,'24207',1,0,CHBLK,52);TE('clr op
%4.1lf','VERCOP',3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","12210"
"bridge","CATBRG4|","LS(SOLD,4,CHGRD);SY(bridge01);TE('clr cl %4.1lf','VERCCL',3,1,2,'24207',1,0,CHBLK,52);TE('clr op
%4.1lf','VERCOP',3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","12210"
"bridge","CATBRG5|","LS(SOLD,4,CHGRD);SY(bridge01);TE('clr cl %4.1lf','VERCCL',3,1,2,'24207',1,0,CHBLK,52);TE('clr op
%4.1lf','VERCOP',3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","12210"
"bridge","CATBRG7| ","LS(SOLD,4,CHGRD);SY(bridge01);TE('clr cl
%4.1lf','VERCCL',3,1,2,'24207',1,0,CHBLK,52);TE('clr op
%4.1lf','VERCOP',3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","12210"
"bridge","CATBRG8|","LS(SOLD,4,CHGRD);SY(bridge01);TE('clr cl %4.1lf','VERCCL',3,1,2,'24207',1,0,CHBLK,52);TE('clr op
%4.1lf','VERCOP',3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","12210"
"canbnk","",","LS(SOLD,1,CSTLN)","50","O","DISPLAYBASE","12410"
"cblohd","",","LS(DASH,2,CHGRD)","60","O","DISPLAYBASE","12210"
"cblohd","CONRAD1|VERCSA|","LS(DASH,2,CHGRD);SY(RACNSP01);TE('sf clr
%4.1lf','VERCSA',3,1,2,'24207',1,0,CHBLK,52)","60","O","DISPLAYBASE","12210"
"cblohd","CONRAD3|VERCSA|","LS(DASH,2,CHGRD);SY(RACNSP01);TE('sf clr
%4.1lf','VERCSA',3,1,2,'24207',1,0,CHBLK,52)","60","O","DISPLAYBASE","12210"
"cblohd","CONRAD1|VERCLR|","LS(DASH,2,CHGRD);SY(RACNSP01);TE('clr
%4.1lf','VERCLR',3,1,2,'24207',1,0,CHBLK,52)","60","O","DISPLAYBASE","12210"
"cblohd","CONRAD3|VERCLR|","LS(DASH,2,CHGRD);SY(RACNSP01);TE('clr
%4.1lf','VERCLR',3,1,2,'24207',1,0,CHBLK,52)","60","O","DISPLAYBASE","12210"
"cblohd","CONRAD1|","LS(DASH,2,CHGRD);SY(RACNSP01)","60","O","DISPLAYBASE","12210"
"cblohd","CONRAD3|","LS(DASH,2,CHGRD);SY(RACNSP01)","60","O","DISPLAYBASE","12210"
"cblohd","VERCSA|","LS(DASH,2,CHGRD);TE('sf clr %4.1lf','VERCSA',3,1,2,'24207',1,0,CHBLK,52)","60","O","DISPLAYBASE","12210"
"cblohd","VERCLR|","LS(DASH,2,CHGRD);TE('sf clr %4.1lf','VERCLR',3,1,2,'24207',1,0,CHBLK,52)","60","O","DISPLAYBASE","12210"
"feryt","",","LC(FERYRT02)","40","O","STANDARD","25030"
"feryt","CATFRY1|","LC(FERYRT01)","40","O","STANDARD","25030"
"feryt","CATFRY2|","LC(FERYRT02)","40","O","STANDARD","25030"
"rdocal","",","LS(DASH,1,TRFCDF);SY(RCLDEF01);TX(OBJNAM,3,2,2,'24207',1,-1,CHBLK,21)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG1|ORIENT|","LS(DASH,1,TRFCDF);SY(rdocal02,ORIENT);TX(OBJNAM,3,1,2,'24207',1,-
1,CHBLK,21);TX(COMCHA,3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG2|ORIENT|","LS(DASH,1,TRFCDF);SY(rdocal02,ORIENT);TX(OBJNAM,3,1,2,'24207',1,-
1,CHBLK,21);TX(COMCHA,3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG3|ORIENT|","LS(DASH,1,TRFCDF);SY(rdocal02,ORIENT);TX(OBJNAM,3,1,2,'24207',1,-
1,CHBLK,21);TX(COMCHA,3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","15060"
"rdocal","TRAFIG4|ORIENT|","LS(DASH,1,TRFCDF);SY(rdocal03,ORIENT);TX(OBJNAM,3,1,2,'24207',1,-
1,CHBLK,21);TX(COMCHA,3,1,2,'24207',1,1,CHBLK,52)","60","O","DISPLAYBASE","15060"
"rivbnk","",","LS(SOLD,1,CSTLN)","50","O","DISPLAYBASE","12410"
"rivbnk","catbnk3|","LS(SOLD,2,CSTLN)","50","O","DISPLAYBASE","12410"
"rivbnk","NATSUR6|","LS(DOTT,2,CSTLN)","50","O","DISPLAYBASE","12410"
"rivbnk","NATSUR9|","LS(DOTT,2,CSTLN)","50","O","DISPLAYBASE","12410"
"wtwaxs","",","LS(DOTT,1,CHGRD)","30","S","OTHER","31010"
"wtwprf","",","LS(DOTT,1,CHGRD)","30","S","OTHER","31010"

Areas

"achare","","SY(ACHARE51);LS(DASH,2,CHMGF);CS(RESTRN01)","20","S","STANDARD","26220"
"achbtr","","SY(ACHBRT07);TX(OBJNAM,3,1,2,'14106',1,0,CHBLK,29);LS(DASH,2,CHMGF)","20","S","STANDARD","26220"
"berths","","SY(BRTHNO01);TX(OBJNAM,1,2,3,'14108',0,0,CHMDG,29);LS(DASH,2,CHMGF)","30","S","STANDARD","22440"
"bridge","","AC(CHBRN,1);TE('clr cl %4.1lf','VERCCL',3,1,2,'14108',1,0,CHBLK,11);TE('clr op
%4.1lf','VERCOP',3,1,2,'14108',1,1,CHBLK,11);LS(SOLD,2,CHGRD)","50","O","DISPLAYBASE","12210"
"brgare","","","
"comare","","","
"departe","","CS(DEPARE01)","10","S","DISPLAYBASE","13030"
"feryrt","","SY(FRYARE51);LC(NAVARE51)","40","S","STANDARD","26040"
"feryrt","CATFRY2|","SY(FRYARE52);LC(NAVARE51)","40","S","STANDARD","26040"
"hrbare","","TX(OBJNAM,1,2,3,'15106',0,0,CHBLK,28);LS(DASH,1,CHGRD)","20","S","OTHER","36020"
"hrbare","cathbr3|","SY(SMCFAC02);TX(OBJNAM,1,2,3,'15106',0,3,CHBLK,28);LS(DASH,1,CHGRD)","20","S","OTHER","36020"
"hrbbsn","","LS(DASH,1,CHGRF)","20","S","DISPLAYBASE","12420"
"hrbfac","","AC(CHBRN,3);SY(HRBFAC10)","40","O","STANDARD","22410"
"hrbfac","cathaf6|","AC(CHBRN,3);SY(HRBFAC11)","40","O","STANDARD","22410"
"hrbfac","cathaf9|","AC(CHBRN,3);SY(HRBFAC12)","40","O","STANDARD","22410"
"hrbfac","cathaf12|","AC(CHBRN,3);SY(HRBFAC13)","40","O","STANDARD","22410"
"hrbfac","cathaf13|","AC(CHBRN,3);SY(HRBFAC14)","40","O","STANDARD","22410"
"hrbfac","cathaf14|","AC(CHBRN,3);SY(HRBFAC15)","40","O","STANDARD","22410"
"hrbfac","cathaf15|","AC(CHBRN,3);SY(HRBFAC16)","40","O","STANDARD","22410"
"hrbfac","cathaf16|","AC(CHBRN,3);SY(HRBFAC17)","40","O","STANDARD","22410"
"hrbfac","cathaf17|","AC(CHBRN,3);SY(HRBFAC18)","40","O","STANDARD","22410"
"lokare","","","
"lokbsn","","LS(DASH,2,CHGRF)","20","S","DISPLAYBASE","12420"
"lkbspt","","LS(DASH,2,CHGRF)","20","S","DISPLAYBASE","12420"
"m_nsys","","","
"prtare","","","
"resare","","LS(DASH,2,CHMGD);CS(RESARE11)","30","S","STANDARD","26010"
"termnl","","AC(CHGRF,3);SY(TERMNL12)","40","O","STANDARD","22420"
"termnl","cattml1|","AC(CHGRF,3);SY(TERMNL01)","40","O","STANDARD","22420"
"termnl","cattml2|","AC(CHGRF,3);SY(TERMNL02)","40","O","STANDARD","22420"
"termnl","cattml3|","AC(CHGRF,3);SY(TERMNL12)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd1|","AC(CHGRF,3);SY(TERMNL03)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd2|","AC(CHGRF,3);SY(TERMNL04)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd3|","AC(CHGRF,3);SY(TERMNL05)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd4|","AC(CHGRF,3);SY(TERMNL06)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd5|","AC(CHGRF,3);SY(TERMNL07)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd6|","AC(CHGRF,3);SY(TERMNL08)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd7|","AC(CHGRF,3);SY(TERMNL09)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd8|","AC(CHGRF,3);SY(TERMNL10)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd9|","AC(CHGRF,3);SY(TERMNL11)","40","O","STANDARD","22420"
"termnl","cattml3|trshgd10|","AC(CHGRF,3);SY(TERMNL12)","40","O","STANDARD","22420"
"trnbsn","","SY(TRNBSN01);LS(DASH,2,CHMGD)","30","O","STANDARD","26020"

3.2 Extended entries for S-57 object classes

3.2.1 Areas

"BUAARE","CATBUA5|","AC(CHBRN);TX(OBJNAM,1,2,3,'15106',0,0,CHBLK,26);LS(SOLD,1,LANDF)","30","S","STANDARD","22240"
"SLCONS","CATSLC4|","SY(PIER0001)","60","O","DISPLAYBASE","12410"

4 Extensions of conditional symbology procedures (CS)

4.1 Top marks

The symbolization of top marks depends on whether the top mark is located on a floating object (buoy) or on a fixed object (beacon). This is checked by the CS (TOPMAR01). In inland water navigation, the colour and top mark shape of beacons are more important than for maritime navigation. Therefore, top marks of beacons shall be symbolized in their real shape and colour, and a new CS (TOPMAR|1) for top marks must be applied by copying and extending the existing CS (see annex to this presentation library).

4.2 Restricted areas

The CS (RESARE02) for the RESARE object class is affected because in this CS the values of the attribute RESTRN are checked. In Inland ECDIS, the object class RESARE and the attribute RESTRN are copied. Therefore, the CS (RESARE02) has also to be copied as CS (RESAR|1) and extended by "resare" and "restrn".

4.3 Lights

The CS for the LIGHTS object class is affected because in this CS there is a check whether a light is located on a floating object or on a fixed object. The list of floating platforms must be extended by the new object class "boywtw". To avoid a copy of this CS which would lead to a copy of the official object class LIGHTS, the Inland ECDIS manufacturers have to extend the official CS for LIGHTS as described above.

4.4 Notice marks

For the symbolization of the notice marks in the "information window on notice marks" (see 6), the main notice mark must be combined with the auxiliary panel. Therefore, a new CS for notice marks has to be applied.

5 Extensions to the Symbol Library

New symbols are designed as bitmap (BMP) files with a pixel program. The BMP files are converted into the specific S-57 raster format. Vector symbols are designed with a special symbol editor.

5.1 New symbols to be shown on the chart display (simplified point symbols)

5.1.1 Raster symbols

a. Symbols in general

bunsta01:	bunker station, diesel oil station
bunsta02:	bunker station, water
bunsta03:	bunker station, ballast
dismar05:	distance mark 100m on river axis
dismar06:	distance mark 1km on river axis
hecmtr01:	hectometre point, 100m
hecmtr02:	hectometre point, 1km
hwtmpk01:	high water mark
notmrk01:	notice mark, prohibition
notmrk02:	notice mark, regulation, restriction
notmrk03:	notice mark, information, recommendation
radhl01:	radar highlight (CONRAD=1)
refdmp01:	refuse dump
ssentr01:	port entry
sslock01:	signal station, lock
sswars01:	signal station, wahrschau
trnbsn01:	turning basin
vtclmk01:	vertical clearance mark at bridges
wtlvgg01:	gauge, height of water
wtlvgg02:	recording gauge, height of water

b. Navigational aids

bcnlat50:	beacon stake - pole
boylat50:	river buoy fairway, red, right side
boylat51:	river buoy fairway, green, left side
boylat52:	river buoy fairway junction, turn off, red-green-red, right side
boylat53:	river buoy fairway junction, turn off, green-red-green, left side
boylat54:	river buoy fairway splitting, red-green....
boylat55:	river buoy obstruction red-white, right side
boylat56:	river buoy obstruction green-white, left side
boyspp50:	buoy special purpose
topma100:	beacon top mark, red cone, point down
topma101:	beacon top mark, red boarded cone, point down
topma102:	beacon top mark, green cone, point up
topma103:	beacon top mark, green boarded cone, point up
topma104:	beacon top mark, red boarded cone, point down, green boarded cone, point up, simplified
topma105:	beacon top mark, red boarded cone, point down, green boarded cone, point up, simplified
topma106:	beacon top mark, white-red square board, vertical
topma107:	beacon top mark, red boarded square board, vertical
topma108:	beacon top mark, white-green square board, diagonal
topma109:	beacon top mark, green boarded square board, diagonal
topma110:	beacon top mark, yellow-black square board, vertical
topma111:	beacon top mark, yellow St.Georg cross
topma112:	beacon top mark, yellow-black square board, diagonal
topma113:	beacon top mark, yellow Andreacross
topma114:	buoy top mark, red cylinder
topma115:	buoy top mark, green cone, point up
topma116:	buoy top mark, red-white-red board, entry prohibited

c. Harbour facilities and terminals

hrbfac10:	default harbour facility
hrbfac11:	harbour facility naval base
hrbfac12:	harbour facility ship yard
hrbfac13:	harbour facility harbour-master's office
hrbfac14:	harbour facility pilot
hrbfac15:	harbour facility water police
hrbfac16:	harbour facility customs office
hrbfac17:	harbour facility service and repair
hrbfac18:	harbour facility quarantine station
termnl01:	terminal, passenger terminal
termnl02:	terminal, ferry terminal
termnl03:	terminal, Container transshipment
termnl04:	terminal, Bulk transshipment
termnl05:	terminal, Oil transshipment
termnl06:	terminal, Fuel transshipment
termnl07:	terminal, Chemical transshipment
termnl08:	terminal, Liquid Goods transshipment
termnl09:	terminal, Explosive goods transshipment
termnl10:	terminal, Fish transshipment
termnl11:	terminal, Car transshipment
termnl12:	terminal, General Cargo transshipment
termnl13:	terminal, RoRo Terminal

5.1.2 Vector symbols (must be rotated, the numbers refer to CEVNI)

- nmkprh02: entry prohibited (A.1)
- nmkprh12: passing on the left side prohibited (A.10)
- nmkprh13: passing on the right side prohibited (A.10)
- nmkrhd01: recommended passage for both directions (D.1a)
- nmkrhd02: recommended passage for only one direction (D.1b)
- nmkrhd03: recommended passage on the right side (D.2)
- nmkrhd04: recommended passage on the left side (D.2)
- nmkinf01: entry permitted (E.1)

5.2 New symbols to be shown in the "information window on notice marks"

a. notice marks (the numbers refer to CEVNI)

- nmkprh01: entry prohibited (A.1)
- nmkprh03: closed area, but small craft boats without engine permitted (A.1.a, only RheinSchPV and Binnenvaartpolitiereglement)
- nmkprh04: overtaking prohibited (A.2)
- nmkprh05: overtaking between push tows and towing units prohibited (A.3)
- nmkprh06: no passing and overtaking (A.4)
- nmkprh07: berthing prohibited (A.5)
- nmkprh08: anchoring prohibited (A.6)
- nmkprh09: making fast to the bank prohibited (A.7)
- nmkprh10: turning prohibited (A.8)
- nmkprh11: avoid wave wash (A.9)
- nmkprh14: boats with engine prohibited (A.12)
- nmkprh15: sport and pleasure boats prohibited (A.13)
- nmkprh16: waterskiing prohibited (A.14)
- nmkprh17: sailing boats prohibited (A.15)
- nmkprh18: boats without engines or sails prohibited (A.16)
- nmkprh19: windsurfing prohibited (A.17)
- nmkprh20: waterscooters and jetskis prohibited (A.18)
- nmkprh21: high speed boats prohibited (A.18)

- nmkprh22: slipping of boats prohibited (A.19)
- nmkreg01: general restrictions (with additional sign) (C.4)
- nmkreg02: mandatory traffic direction, left (B.1)
- nmkreg03: mandatory traffic direction, right (B.1)
- nmkreg04: mandatory change of the fairway side to port (B.2a)
- nmkreg05: mandatory change of the fairway side to starboard (B.2b)
- nmkreg06: port fairwayside is mandatory traffic direction (B.3a)
- nmkreg07: starboard fairwayside is mandatory traffic direction (B.3b)
- nmkreg08: mandatory crossing of the fairway side to port (B.4a)
- nmkreg09: mandatory crossing of the fairway side to starboard (B.4b)
- nmkreg10: mandatory stop (B.5)
- nmkreg11: mandatory sound signal (B.7)
- nmkreg12: special attention (B.8)
- nmkreg13: give way other vessels when entering the main fairway (B.9a)
- nmkreg14: give way other vessels when crossing the main fairway (B.9b)
- nmkreg15: mandatory radiophone (B.11)
- nmkreg16: restricted fairway depth (C.1)
- nmkreg17: restricted vertical clearance (C.2)
- nmkreg18: restricted width of the fairway (C.3)
- nmkreg19: restricted width of the waterway at the left bank (C.5)
- nmkreg20: restricted width of the waterway at the right bank (C.5)
- nmkrccd05: recommended traffic direction, left (D.3)
- nmkrccd06: recommended traffic direction, right (D.3)
- nmkinf02: overhead power line crossing (E.2)
- nmkinf03: weir (E.3)
- nmkinf04: cable ferry (E.4)
- nmkinf05: ferry (E.4b)
- nmkinf06: berthing permitted (E.5)
- nmkinf07: berthing facilities for push tows (E.5.4)
- nmkinf08: berthing facilities for push with one blue cone (E.5.5)
- nmkinf09: berthing facilities for push tows with two blue cones (E.5.6)
- nmkinf10: berthing facilities for push tows with three blue cones (E.5.7)
- nmkinf11: berthing facilities for other than push tows (E.5.8)
- nmkinf12: berthing facilities for other than push tows one blue cone (E.5.9)
- nmkinf13: berthing facilities for other than push tows with two blue cones (E.5.10)
- nmkinf14: berthing facilities for other vessels than push tows three blue cones (E.5.11)
- nmkinf15: berthing facilities for all vessels (E.5.12)
- nmkinf16: berthing facilities for all vessels with one blue cone (E.5.13)
- nmkinf17: berthing facilities for all vessels with two blue cones (E.5.14)
- nmkinf18: berthing facilities for all vessels with three blue cones (E.5.15)
- nmkinf19: anchoring permitted (E.6)
- nmkinf20: making fast to the bank permitted (E.7)
- nmkinf21: facilities for making fast to the bankof vehicles (E.7.1)
- nmkinf22: turning permitted (E.8)
- nmkinf23: crossing with secondary waterway ahead (E.9a)
- nmkinf24: secondary fairway ahead on the right (E.9.b)
- nmkinf25: secondary fairway ahead on the left (E.9.c)
- nmkinf26: secondary fairway ahead (main fairway right)
- nmkinf27: secondary fairway ahead (main fairway left)
- nmkinf28: secondary fairway left (main fairway right)
- nmkinf29: secondary fairway right (main fairway left)
- nmkinf30: secondary fairway ahead and left (main fairway right)
- nmkinf31: secondary fairway ahead and right (main fairway left)
- nmkinf32: crossing with main fairway ahead (E.10.a)
- nmkinf33: junction with main fairway ahead (E.10.b)
- nmkinf34: junction with main fairway ahead and right
- nmkinf35: junction with main fairway ahead and left
- nmkinf36: junction with main fairway ahead and right (secondary fairway left)
- nmkinf37: junction with main fairway ahead and left (secondary fairway right)
- nmkinf38: end of prohibition or regulation (E.11)

- nmkinf39: drink water (E.13)
- nmkinf40: telephone (E.14)
- nmkinf41: boats with engine permitted (E.15)
- nmkinf42: sport and pleasure boats permitted (E.16)
- nmkinf43: waterski (E.17)
- nmkinf44: sailing boats (E.18)
- nmkinf45: boats without engine or sails (E.19)
- nmkinf46: windsurfing (E.20)
- nmkinf47: nautical radio information (E.21)
- nmkinf48: waterscooters, jetskis (E.22)
- nmkinf49: high speed boats permitted (E.21)
- nmkinf50: facilities for berthing of vehicles (E.22)
- nmkinf51-55: maximum number of vessels mooring side by side (E.5.3)

b. Auxiliary panels (CEVNI Annex 7, Section II)

- addmrk01: top (board)
- addmrk02: bottom (board)
- addmrk03: right (triangle to the right)
- addmrk04: left (triangle to the left)
- addmrk05: top (board, square main board)
- addmrk06: bottom (board, square main board)
- addmrk07: right (triangle to the right, landscape main board)
- addmrk08: left (triangle to the left, landscape main board)

6 Presentation of notice marks

Notice marks which are located at the river bank are presented twice:

1. In the chart presentation notice marks are displayed by generic symbols (notmrk01, notmrk02 and notmrk03). This does not apply to the notice marks on bridges.
2. To display the detailed symbol of a notice mark which is similar to the real world indication the user must pick on the generic symbol in the chart. Then, the special "information window on notice" marks pop up showing the detailed notice mark symbol and offering the full set of object information. This does not apply to the notice marks on bridges.

Notice marks which are located at bridges (see no 5.1.2 and 8.2 vector symbols), shall be symbolized according to the orientation of the bridge.

Notice marks which specify distances or a velocity will not be symbolized with the number itself, but only with that symbol which gives the general regulation or information.

7 **Presentation of objects for radar map matching**

The presentation of objects necessary for radar map matching is handled by the application. This is not done by means of look-up tables. A kernel function is available which extracts those objects and presents them in the required way. The object classes for radar map matching are listed in section 2, appendix B, annex A (Use of the Object Catalogue for Inland ECDIS), ch. 12.12. For the symbolization of the point objects for radar map matching see ch. 5.1.1.g and ch. 8.1, picture RADHLT01 of this presentation library.

8 Inland ECDIS symbols

8.1 Raster symbols

8.1.1 Symbols in general

NOD TA		
CURSR		
CHBLK		
CHGRD		
CHGRF		
CHRED		
CHGRN		
CHYLW		
CHMGD		
CHMCF		
CHBRN		
CHWHT		
SCLER		
CHCOR		
LITRD		
LITGN		
LITYW		
ISDNG		
DNGHIL		
TRFCDF		
TRFCF		
LANDA		
LANDF		
CSTLN		
SNDG1		
SNDG2		
DEPSC		
DEPCN		
DEPDW		
DEPMR		
DEPMR		
DEPV		
DEPIT		
RADHI		
RADLO		
ARPAT		
NINFO		
RESBL		
ADINF		
RESGR		
SHIPS		
PSTRK		
SYTRK		
PLRTE		
PLRTE		
UIBCK		
UIBDR		
UIAFD		
UIAFF		
UINFD		
UINFF		
UINFR		
UINFO		
UINFB		
UINFM		
OUTLW		
OUTLL		
RESO1		
RESO2		
RESO3		
RESO4		
RESO5		

8.1.2 Navigational aids

NOD TA		
CURSR		
CHBLK		
CHGRD		
CHGRF		
CHRED		
CHGRN		
CHYLW		
CHMGD		
CHMGF		
CHBRN		
CHWHT		
SCLBR		
CHCOR		
LITRD		
LITGN		
LITYW		
TSDNG		
DNGHL		
TRFCDF		
TRFCF		
LANDA		
LANDF		
CSTLN		
SNDG1		
SNDG2		
DEPSC		
DEPCN		
DEPDW		
DEPMDD		
DEPMIS		
DEPVIS		
DEPIT		
RADHI		
RADLO		
ARPAT		
NINFO		
RESBL		
ADINFF		
RESGR		
SHIPS		
PSTRK		
SYTRK		
PLRTE		
APIRT		
UIBCK		
UIBDR		
UIAFD		
UIAFF		
UINFID		
UINFF		
UINFR		
UINFG		
UINFO		
UINFB		
UINFM		
OUTLW		
OUTLL		
RESO1		
RESO2		
RESO3		
RESO4		
RESO5		

8.1.3 Harbour facilities, terminals

NODTA		
CURSR		
CHBLK		
CHGRD		
CHGRF	HRBFAC10	HRBFAC11
CHRED		
CHGRN		
CHYLW		
CHMGD		
CHMGF	HRBFAC12	HRBFAC13
CHBRN		
CHWHT		
SCLBR		
CHCOR		
LITRD	HRBFAC14	HRBFAC15
LITGN		
LITYW		
TSDNG		
DNGHL		
TRFCDF	HRBFAC16	HRBFAC17
TRFCF		
LANDA		
LANDF		
CSTLN		
SNDG1	HRBFAC18	TERMNL01
SNDG2		
DEPSC		
DEPCN		
DEPDW		
DEPMR		
DEPMS	TERMNL02	TERMNL03
DEPVIS		
DEPIT		
RADHI		
RADLO		
ARPAT	TERMNL04	TERMNL05
NINFO		
RESBL		
ADINIF		
RESGR		
SHIPS	TERMNL06	TERMNL07
PSTRK		
SYTRK		
PLRTE		
APIRT		
UIBCK	TERMNL08	TERMNL09
UIBDR		
UIAFD		
UIAFF		
UINFID		
UIMFF	TERMNL10	TERMNL11
UINFR		
UINFG		
UINFO		
UINFB		
UINFM		
OUTLW	TERMNL12	TERMNL13
OUTLL		
RESO1		
RESO2		
RESO3		
RESO4		
RESO5		


8.2 Symbols for the "information window on notice marks"

NODTA			
CURSTARK			
CHBLK			
CHGRDF			
CHGRF			
CHRED			
CHGRN			
CHYLW			
CHMGD			
CHMGF			
CHBRN			
CHWHT			
SCLB.R			
CHCOP			
LITRD			
LITGN			
LITYW			
ISDNG			
DNGHL			
TRFCDD			
TRFCFD			
LANDFA			
LANDFN			
CSTLN			
SNDG1			
SNDG2			
DEPSCN			
DEPDGU			
DEPMDD			
DEPMSS			
DEPVST			
DEPITT			
RADHTI			
RADLO			
ARPAT			
NINFOI			
RESBLE			
ADINFE			
RESGFSR			
SHIPSK			
PSTRK			
SYTRK			
PLRTE			
APIRT			
UIBCK			
UIBDR			
UIAFFF			
UIINFD			
UIINFF			
UINFG			
UINFOB			
UINFBN			
OUTLG			
OUTLL			
RESO1			
RESO3			
RESO4			
RESO5			

NOD TA			
CURSR			
CHBLK			
CHGRD			
CHGRF			
CHRED			
CHGRN			
CHYLW			
CHMGD			
CHMGF			
CHBRN			
CHWHT			
SCLB R			
CHCOR			
LITRD			
LITGN			
LITYW			
ISDNG			
DNGHL			
TRFC D			
TRFC F			
LAND A			
LAND F			
CSTLN			
SNDG1			
SNDG2			
DEPSC			
DEPCN			
DEPDW			
DEPM D			
DEPM S			
DEPV S			
DEPIT			
RADHI			
RADLO			
APPAT			
NINFO			
RESBL			
ADINF			
RESGR			
SHIPS			
PSTRK			
SYTRK			
PLRTE			
APLRT			
UIBCK			
UIBDR			
UIAFD			
UIAFF			
UINF D			
UINFF			
UINFG			
UINFO			
UINFB			
OUTLW			
OUTLL			
RESO 1			
RESO 2			
RESO 3			
RESO 4			
RESO 5			
NMKREG01			
NMKREG02			
NMKREG03			
NMKREG04			
NMKREG05			
NMKREG06			
NMKREG07			
NMKREG08			
NMKREG09			
NMKREG10			
NMKREG11			
NMKREG12			
NMKREG13			
NMKREG14			
NMKREG15			
NMKREG16			
NMKREG17			
NMKREG18			
NMKREG19			
NMKREG20			

NODTA						
CURSR						
CHBLK						
CHGRD						
CHGRF						
CHRED						
CHGRN						
CHYLW						
CHMGD						
CHMGF						
CHBRN						
CHWHT						
SCLBR						
CHCOR						
LITRD						
LITGN						
LITYW						
ISDNG						
DNGHL						
TRFCD						
TRFCF						
LANDA						
LANDF						
CSTLN						
SNDG1						
SNDG2						
DEPSC						
DEPCN						
DEPDW						
DEPMR						
DEPMG						
DEPVG						
DEPIT						
RADHI						
RADLO						
ARPAT						
NINFO						
RESBL						
ADINF						
RESGR						
SHIPS						
PSTRK						
SYTRK						
PILRT						
A PLRT						
UIBCK						
UIBDR						
UIAFD						
UIAFF						
UINFD						
UINFF						
UINFR						
UINFG						
UINFO						
UINFB						
UINFM						
OUTLW						
OUTLL						
RESO1						
RESO2						
RESO3						
RESO4						
RESO5						

NOD TA		
CURSR		
CHBLK		
CHGRD		
CHGRF		
CHRED		
CHGRN		
CHYLW		
CHMGD		
CHMGF		
CHERN		
CHWHT		
SCLBR		
CHCOR		
LITRD		
LITGN		
LITYW		
ISDNG		
DNGHL		
TRFCDF		
TRFCF		
LANDA		
LANDF		
CSTLN		
SNDG1		
SNDG2		
DEPSC		
DEPCN		
DEPDW		
DEPMR		
DEPMR		
DEPVUS		
DEPIT		
RADHI		
RADLO		
ARPAT		
NINFO		
RESBL		
ADINF		
RESGR		
SHIPS		
PSTRK		
SYTRK		
PLRTE		
APLRT		
UIECK		
UIBDR		
UIAFD		
UIAFF		
UINFD		
UINFF		
UINFR		
UINFO		
UINFB		
UINFM		
OUTLW		
OUTLL		
RESO1		
RESO2		
RESO3		
RESO4		
RESO5		




8.3 Vector symbols

NODTA	
CURSR	
CHBLK	
CHGRD	
CHGRF	
CHRED	
CHGRN	
CHYLW	
CHMGD	
CHMGF	
CHBRN	
CHWHT	
SCLBR	
CHCOR	
LITRD	
LITGN	
LITYW	
ISDNG	
DNGHL	
TRFCD	
TRFCF	
LANDA	
LANDF	
CSTLN	
SNDG1	
SNDG2	
DEPSC	
DEPCN	
DEPDW	
DEPMR	
DEPMS	
DEPVW	
DEPIT	
RADHI	
RADLO	
ARPAT	
NINFO	
RESBL	
ADINF	
RESGR	
SHIPS	
PSTRK	
SYTRK	
PLRTE	
APLRT	
UIECK	
UIBDR	
UIAFD	
UIAFF	
UINFD	
UINFF	
UINFR	
UINFG	
UINFO	
UINFB	
UIMFM	
OUTLW	
OUTLL	
RESOI	
RESOZ	
RESO3	
RESO4	
RESO5	

TOPMARI1

Conditional symbology procedure for symbolization of objects of the class topmar (Top Mark)



Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 4

Operational and performance requirements, methods of testing and required test results

Appendices:

- A Software Quality Assurance**
- B System Configurations (Figures)**

Contents

1	Introduction.....	161
1.1	Scope of this document	161
1.2	Normative references	161
2	Operating modes and system configuration.....	161
2.1	Operating modes	161
2.2	System configurations	162
3	Performance requirements.....	162
3.1	Hardware performance	162
3.2	Software performance	162
3.3	Performance of operation controls	163
3.4	Display performance.....	163
4	Operational functions	164
4.1	Operating mode	164
4.2	Equipment pre-sets (store/recall)	164
4.3	Presentation of SENC information	164
4.4	Chart orientation, positioning and shifting	165
4.5	Position and bearing of the own ship	165
4.6	Information density	165
4.7	Ranges / Range rings.....	165
4.8	Picture Brilliance.....	166
4.9	Picture colours.....	166
4.10	Pick report.....	166
4.11	Measuring features.....	166
4.12	Input functions	9
4.13	Loading and updating of SENC's	166
4.14	Radar picture presentation and overlay	167
4.15	Functions with immediate access.....	167
4.16	Permanent visible function parameters	167
5	Service functions.....	167
5.1	Static correction of the chart position	167
5.2	Static correction of the chart orientation.....	168
5.3	Configuration of interfaces.....	168

6	Hardware test and required certificates.....	168
6.1	Compatibility with the environmental requirements.....	168
6.2	Equipment documentation.....	168
6.3	Interfaces	169
6.4	Characteristic of operation controls	169
6.5	Characteristic of the display	169
7	Test of the chart presentation, operation and functionality	169
7.1	Preparation of the Equipment Under Test (EUT)	169
7.2	Test of the operation modes.....	169
7.3	Test of the displayed objects	169
7.4	Test of the scale dependent information density (SCAMIN)	169
7.5	Test of the brilliance variation.....	170
7.6	Test of the colours	170
7.7	Test of the measurement functions	170
7.8	Test of the chart update function	170
7.9	Test of displayed objects in more than one cell of the same usage for the same area ..	170
8	Test of the radar picture presentation and -operation	170
8.1	Preparations	170
8.2	Test of the radar picture without underlaid chart.....	171
8.3	Test of the radar picture and the underlaid chart	171
9	Test of alarms and indications.....	172
10	Test of fall back arrangements	172

1 Introduction

1.1 Scope of this document

This section 4 of the Inland ECDIS Standard specifies the minimum requirements contained in section 1 and describes the test procedures and the required results concerning the hardware, the software, the functions, the operation, the display and the interfaces to other equipment on board of ships.

1.2 Normative references

References to the following normative documents are made in this document in addition to the references in section 2, ch. 2.2 of this standard:

EN 60945 (1997)	Marine navigational equipment; General requirements - Methods of testing and required test results
IEC 1174:	ECDIS - Operational and performance requirements, methods of testing and required test results
ISO 9000 (1987)	Quality management and quality assurance standard
CCNR Decision 1989-II-33:	Standard on the minimum requirements and on the required test results for navigational radar equipment in the Rhine navigation
CCNR Decision 1989-II-34:	Standard on the minimum requirements and on the required test results for rate-of-turn indicators in the Rhine navigation
CCNR Decision 1989-II-35:	Standard on the installation and on functional tests of navigational radar equipment and of rate-of-turn indicators in the Rhine navigation
EU-Directive 1999/5/EC:	Radio Equipment and Telecommunications Terminal Equipment and the Mutual Recognition of their Conformity

2 Operating modes and system configuration

2.1 Operating modes

- a) The Inland ECDIS Standard distinguishes two operating modes: **navigation mode** and **information mode**.
- b) Inland ECDIS equipment designed for operating in **navigation mode** has to fulfil the requirements of this standard and the standards on navigational radar equipment and rate-of-turn indicators to be proven by conformity tests.
- c) For Inland ECDIS equipment designed for **information mode** only, the requirements of this section 4 are to be understood as a recommendation.

2.2 System configurations

2.2.1 Inland ECDIS equipment, stand-alone-system without connection to radar

In this configuration only operation in **information mode** is possible (see Appendix B, Fig. 1).

2.2.2 Inland ECDIS equipment, parallel installation and connection to radar

This configuration allows operation in **information mode** as well as in **navigation mode** (see Appendix B, Fig. 2).

2.2.3 Inland ECDIS equipment, monitor shared with connected radar equipment

In special cases, it is possible to share one display for the Inland ECDIS equipment and for the radar equipment. The prerequisite for this is a monitor with matching graphic parameters for both video signals, and a video switch, which allows a fast switchover of the video sources, and – if needed - a mechanical rotation of the display to the required orientation (see Appendix B, Fig. 3).

2.2.4 Radar equipment with integrated Inland ECDIS functionality

This is a radar installation with integrated Inland ECDIS functionality that can be operated in **information mode** as well as in **navigation mode** (see Appendix B, Fig. 4).

3 Performance requirements

3.1 Hardware performance

- a) Inland ECDIS equipment shall be designed and manufactured to withstand typical environmental conditions prevailing on board of a vessel without any degradation in quality and reliability. Furthermore, it shall not disturb other communication and navigation equipment.
- b) In the configuration as described in paragraph 2.2.4 all components of inland ECDIS equipment, installed inside the wheelhouse, shall fulfil the requirements of the class b) "protected from weather" equipment as specified in the standard EN 60945 with the exception that the test temperature range is limited to 0 °C to +40 °C (whereas the test temperature range in EN 60945 is specified from – 15 °C to + 55 °C) unless specified differently in this document. For the configurations described in paragraph 2.2.2 and 2.2.3 CE conformity is sufficient.

3.2 Software performance

Operation, visualisation, and functionality of Inland ECDIS equipment are usually realised by software. Taking this into account, the software shall be designed, developed, implemented, and tested according to the generally accepted state of the art. Therefore, the manufacturer shall fulfil the software requirements described in Appendix A to this document.

3.3 Performance of operation controls

- a) The operation of the system shall be simple, appropriate and conform to common human interface standards.
- b) The number of operational controls shall be as low as possible and restricted to the required number.
- c) Wireless remote controls are not admitted.
- d) The ON/OFF switch is to perform and to be arranged in such a way that inadvertent operation is not possible.
- e) The symbols of the operating controls need a minimum character height of 4 mm and shall be readable under all conditions that may exist in a wheelhouse.
- f) The brilliance and the illumination of the operating controls should be adjustable to the required value.

3.4 Display performance

3.4.1 Display dimensions

In **navigation mode** the minimum chart and radar display area is 270 mm x 270 mm.

3.4.2 Display orientation

- a) A rectangular display may be mounted in landscape or in portrait orientation under the prerequisite that the above mentioned minimum dimensions are fulfilled.
- b) Because of the limited space available in the typical wheelhouse of an inland vessel and the fact that a vessel usually follows the fairway-axis, the display shall be installed preferably in the portrait orientation.

3.4.3 Display resolution

A display resolution of 5 m in the 1,200 m range is required. This leads to a maximum pixel dimension of 2.5 m x 2.5 m, i.e. about 1,000 pixels at the short edge of the display.

3.4.4 Display colours

The system shall be able to display ergonomically proven colour combinations for day and night.

3.4.5 Display brilliance

The brilliance of the display shall be adjustable to every operational required value. This is especially valid for the lowest value during operation at night.

3.4.6 Picture renewal

- a) The picture renewal rate shall not be shorter than that of the radar picture (≥ 24 pictures per minute).
- b) Between two consecutive renewals no fluctuations of brilliance may occur.
- c) On raster scan displays, the frame repetition rate may not be lower than 60 Hz.

3.4.7 Display technology

Preferably such display systems shall be used that are insensitive to the magnetic fields that may occur in the wheelhouse of an inland vessel.

4 Operational functions

4.1 Operating mode

- a) If the equipment is able to work in both operation modes it shall provide the possibility to switch between **navigation mode** and **information mode**.
- b) The operation mode in use shall be displayed.
- c) Suitable measures are required to prevent inadvertent switching off of the **navigation mode**.

4.2 Equipment pre-sets (store/recall)

- a) After invoking, the Inland ECDIS equipment shall come up with a moderate brilliance pre-set which neither blinds in a dark environment nor makes the picture invisible in a bright environment.
- b) Other parameters may come up with their values at the time before switching off or from stored settings.

4.3 Presentation of Inland SENC information

Inland SENC = Inland System Electronic Navigational Chart

- a) The radar picture shall be clearly distinguishable from the chart independently of the chosen colour table.
- b) Only a monochrome presentation of the actual radar picture is permitted.
- c) The presentation of chart information shall not mask or degrade important parts of the radar picture. This has to be ensured by appropriate entries into the look-up tables (ref. to section 3 of this standard, appendix A, ch. 2.1, field "radar code").
- d) In **navigation mode**, chart and radar picture presentation shall have the same scale.
- e) The heading line must be always visible.
- f) Additionally, the mariner's own ship's contour and the safety contours may be inserted.

4.4 Chart orientation, positioning and shifting

- a) In **navigation mode**, only the chart orientation "relative motion, head up" and the "centred" or "off centred" presentations, as required for the radar picture, are permitted.
- b) In **information mode**, at least the chart orientations north and parallel to the waterway axis as well as positioning are recommended. By connection of a positioning sensor, the displayed part of the chart can automatically follow the mariner's own ship's position.

4.5 Position and bearing of the own ship

- a) In **navigation mode**, the own ships position shall always be visible in the display area, whether centred or off centred as specified in the CCNR radar requirements.
- b) The heading line, which runs from the display centre to the top and which always shall be visible, shall represent the heading of the mariner's own ship.

4.6 Information density

The information density shall be at least adjustable to the three switchsteps: "Minimum", "Standard" and "All Information". The latter displays all other objects in addition to the "Standard" display, individually on demand. All corresponding visible objects are defined in the "Performance Standard" and the "Presentation Standard (Presentation Library)" (Sections 1 and 3 of the Inland ECDIS Standard).

4.7 Ranges/Range rings

- a) In **navigation mode** the following fixed ranges and range rings are prescribed according to the radar regulations:

Range	Range rings
500 m	100 m
800 m	200 m
1.200 m	200 m
1.600 m	400 m
2.000 m	400 m

- b) Both, smaller as well as larger ranges with a minimum of four and a maximum of six range rings are permitted.
- c) Inland ECDIS equipment in **navigation mode** shall have fixed range rings with the above mentioned intervals and at least one variable range marker (VRM).
- d) Switching on/off of fixed and variable range markers shall be independent of each other and their display shall be clearly distinguishable.
- e) The position of the VRM and the corresponding displayed distance shall use the same incrementation and resolution.
- f) The functions of the VRM and the electronic bearing line (EBL) may additionally be realised by a cursor and by a corresponding numerical display, showing range and bearing of the cursor position.
- g) For **information mode** the same ranges are recommended.

4.8 Picture Brilliance

- a) The brightness of the display shall be adjustable to the operationally necessary value. This applies in particular to operation in darkness.
- b) Chart and radar picture require separate brightness controls.
- c) Because of the strongly different environment brightness of bright day and dark night, another control for the basic brightness of the display shall be available additionally to the colour tables in the menu.

4.9 Picture colours

At least the colour combinations included in the IHO-S-52 Presentation Library, ch. 4 and 13 (*colour tables*) for bright day, white-back day, black-back day, dusk and night shall be supported.

4.10 Pick report

- a) In **navigation** mode, it shall be possible to get all information concerning the objects that are displayed in the chart. By moving the cursor to the desired point in the chart and clicking it with the mouse, the addressed point shall be marked by a symbol. At the same time, a window (pick report) shall be opened with textual and/or graphical information about all objects existing at that point.
- b) The pick report window may only be shown in the designated areas outside of the screen section that is preserved for the navigational chart.

4.11 Measuring features

- a) Measuring features for distances and bearings are required.
- b) Resolution and accuracy shall at least be the same as those of the display, but may not suggest better values than those of the chart data.

4.12 Input and editing of skippers' own chart entries

- a) Inland ECDIS equipment shall allow input, storing, modifying, and deletion of additional chart information by the skipper (*skippers' own objects*).
- b) These own chart entries shall be distinguishable from the SENC data, and may not overlay or degrade the radar picture.

4.13 Loading and updating of SENC's

- a) All **manual** activities concerning loading or updating of charts shall be possible only outside the navigation mode.
- b) **Automatic** updating shall not downgrade the performance of the navigation display.
- c) A **roll-back function** has to be implemented to allow restoring to the last working combination.

4.14 Radar picture presentation and overlay

- a) The radar image representation is mandatory for operation in the navigation mode.
- b) The dimensions, resolution and attributes of the radar presentation shall fulfil the relevant radar requirements.
- c) The radar picture must not be degraded by other contents of the picture (see 4.3.c)
- d) Provided the functional requirements are fulfilled, overlaying of different picture layers is permitted.
- e) It shall be possible to switch off the chart and to display only the radar picture.
- f) If the quality and plausibility monitors of the Inland ECDIS equipment detect that the chart cannot be oriented and/or positioned with the accuracy required by this document, an alarm shall be presented on the display and the chart shall be switched off automatically.

4.15 Inland ECDIS functions with immediate access

- a) The following operational functions require direct access:
 - RANGE
 - BRILLIANCE
 - COLOURS
 - INFORMATION DENSITY
- b) These functions need either own control elements or own menu areas, which are arranged in the highest menu level and are permanently visible.

4.16 Permanent visible function parameters

The following function parameter shall be always visible:

- actual RANGE
- sensor STATUS (radar tuning, position quality, alarms)
- selected WATER LEVEL (if available)
- selected SAFETY DEPTH (if available)
- selected INFORMATION DENSITY

5 Service functions

Service functions shall be protected by a password or other suitable measures against unauthorised access and shall not be selectable in navigation mode.

5.1 Static correction of the chart position

- a) The position of the mariner's own ship shall be presented centred or off centred on the display in accordance with the radar requirements. The chart position shall match the radar image. Assuming an absolute position's input the permissible static difference between actual radar position and displayed radar centre shall not exceed 1 m.

- b) It shall be possible to correct an offset error (distance between the positions of the position sensor and the radar sensor).

5.2 Static correction of the chart orientation

- a) The difference between the heading line orientation and the ship's axis shall not be greater than ± 1.0 deg.
- b) Chart and radar image shall have the same orientation. The static directional error between heading line and chart orientation shall be less than ± 0.5 deg.

5.3 Configuration of interfaces

- a) It shall be possible to configure interfaces for connected sensors, actors and signals (*An actor transforms an electrical quantity into another physical quantity (e.g. optical). An actor is the opposite of a sensor*).
- b) Interfaces shall comply with existing interface specifications like the NMEA 01/83 standard and the interface specifications for rate of turn indicators (20 mV/deg/min).

6 Hardware test and required certificates

- a) The test consists of a comparison between the equipment under test (EUT) and the requirements of this document.
- b) Proved equivalent tests, and proved and documented test results will be accepted without renewed tests.

6.1 Compatibility with the environmental requirements

- a) Inland ECDIS equipment, as described in paragraph 2.2.4, shall fulfil the requirements of the Standard EN 60 945 concerning the environmental conditions (humidity, vibration and temperature) (the latter reduced according to chapter 3.1 of this document) and concerning electromagnetic compatibility.
- b) The provider or his representative is obliged to submit a relevant conformity declaration of an accredited laboratory.

6.2 Equipment documentation

The technical documentation will be checked to be complete, appropriate, and understandable, and to be sufficient for unproblematic installation, configuration and operation of the equipment.

6.3 Interfaces

- a) All interfaces shall be documented correctly and completely.
- b) Electronic Circuits need to be designed failsafe, mechanically as well as electronically, and may not have degrading repercussions on connected equipment.

6.4 Characteristic of operation controls

All operation controls will be checked regarding the ergonomic and functional mode of operation and shall fulfil the requirements of this document.

6.5 Characteristic of the display

The display shall fulfil all requirements of this document concerning dimension, displayable colours, resolution, and variation of brilliance.

7 Test of the chart presentation, operation and functionality

7.1 Preparation of the “Equipment under test” (EUT)

The EUT will be installed, assembled and connected according to the installation manual. After switching on the test SENC will be loaded.

7.2 Test of the operation modes

All operating modes as described in the operating manual will be successively invoked and tested. The requirements of chapter 4 shall be fulfilled.

7.3 Test of the displayed objects

It will be tested if all objects included in the test SENC are visible and correctly displayed. For this test, the information density will be switched to “all objects”.

7.4 Test of the scale dependent information density (SCAMIN)

- a) Whether the SCAMIN functionality (*the minimum scale at which the object may be used for ECDIS presentation*) is installed correctly will be tested.
- b) For this test, the range will be used at which the object shall be visible according to its SCAMIN attribute value (ref. to the IHO-S-57 Attribute Catalogue and the IHO-S-52 Users Manual to the Presentation Library, ch. 8.4).

7.5 Test of brilliance variation

The Inland ECDIS equipment will be operated in a dark room and the brilliance will be brought to its lowest level. The brilliance of the objects shall not exceed a value of 15 cd/m², and the background a value of 0,5 cd/m².

7.6 Test of the colours

All user selectable S-52 colour tables will be sequentially tested to conform to this document.

7.7 Test of the measurement functions

- a) All numeric displayed values of the electronic bearing line (EBL) and the variable range marker (VRM) shall exactly match with the analogue positions of the EBL and the VRM (or correspond with the cursor co-ordinates).
- b) The resolution and incrementation of the numerical display shall be identical with the analogue values of EBL and VRM.

7.8 Test of the chart update function

- a) Before and after every test step the version numbers of the loaded SENCs and updates will be recalled as described in the operation manual and showed on the display.
 - Step 1: Loading of the test SENC,
 - Step 2: Update of the test SENC,
 - Step 3: Test of the roll-back function,
 - Step 4: Loading of a new SENC.

After an update it should be possible to recall and display all objects concerned.

7.9 Test of displayed objects in more than one cell of the same usage for the same area

It will be tested whether all objects included in the test SENC and in the additional overlay test SENC are visible and correctly displayed. For this test the information density will be switched to "all objects". It will be tested whether it is possible to select one or more specific cells for presentation if there are several cells from different producers for the same area with the same usage.

8 Test of radar picture presentation and operation

8.1 Preparations

- a) For the test purposes, the manufacturer or provider has to provide a serial interface at the system to be approved (*Equipment under test - EUT*) which delivers the same actual values (as NMEA 01/83 strings) of position and heading that are used to position and orient the chart.
- b) During the test, a reference system will be used of which position and heading values are compared with those of the EUT.

- c) The EUT will be connected to any type approved radar equipment (to the choice of the provider).
- d) The radar picture will be adjusted in range and bearing with reference to the heading line.

8.2 Test of the radar picture without underlaid chart

- a) If the Inland ECDIS equipment displays the radar picture but the radar operation control remains at the radar equipment (App. B, figures 2 and 3), the radar picture of the inland ECDIS equipment will be considered as the "daughter display" of an item of radar equipment. In that case, the radar picture has to fulfil the display and picture-relevant requirements of the requirements for radar and rate-of-turn indicators.
- b) If the EUT is a radar installation with integrated Inland ECDIS functionality (Appendix B, figure 4), all requirements of the standards for radar equipment and rate-of-turn indicators have to be fulfilled.

8.3 Test of the radar picture and the underlaid chart

The Inland ECDIS equipment will be installed in a reference environment. This can be real (on a ship) or simulated.

8.3.1 Test of the picture overlay

- a) The radar image shall not be degraded by the chart picture (ref. to ch. 4.3.c).
- b) The chart picture shall be renewed not later than the radar picture.

8.3.2 Test of the chart positioning and orientation

- a) The static offset of the chart position shall be less than ± 5 m in all ranges up to 2,000 m.
- b) The static azimuth orientation offset error between radar and chart image shall be less than $\pm 0,5$ deg.
- c) The correction of these parameters shall be demonstrated in the service mode.
- d) The dynamic deviation of the chart orientation at rates of turn less than ± 60 deg./min shall be less than ± 3 deg.
- e) These tests will be performed visually or by evaluation of measured data.

8.3.3 Test of scale conformity

The chart's information will be compared with well-known reference points contained in the radar picture in order to test whether the chart scale sufficiently conforms to the radar scale.

9 Test of alarms and indications

- a) The alarms generated from Inland ECDIS equipment itself as well as the passed alarms delivered by the connected sensors to the ECDIS will be tested.
- b) The test procedure comprises the following situations:
 - any error in the Inland ECDIS equipment (built-in test equipment - BITE),
 - missing positioning signal,
 - missing radar signal,
 - missing rate of turn signal,
 - missing heading signal,
 - radar map matching not possible,

10 Test of fall back arrangements

- a) This test shall demonstrate the reaction of the Inland ECDIS equipment to a failure of any internal or external component and the possible and required actions by the operator.
- b) In addition, the operating manual will be checked to determine whether the measures required by the operator are described adequately and appropriately.

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

Inland ECDIS

SECTION 4

Operational and Performance Requirements, Methods of Testing and required Test Results

Appendix A

Measures to Ensure Software Quality

Contents

1 General requirements	175
1.1 Software design requirements	175
1.2 Implementation requirements	175
1.3 Test requirements	175
1.4 Third party components requirements	176
1.5 Requirements to additional services in navigation mode	176
1.6 Language	176
1.7 Documentation requirements for users.....	176
2 Methods of testing and required results.....	176
2.1 Navigation mode operation test	176
2.2 General software tests	178
3 Changes on certified systems	179
3.1 General requirements	179
3.2 Hardware and software changes	179

1 General requirements

Software used in navigation mode is assumed to be a safety-relevant part of a navigation system. Providers of navigation systems have to make sure that all software components used in navigation mode allow secure navigation in every situation.

1.1 Software design requirements

Software components have to be clearly designed by means of established software design methods. The design specification must indicate how safety requirements are addressed in the software design. A software style guide has to be provided that specifies code writing style, documentation style, modularization, conflict analyses and testing of software components. For every software component documents describing specification and design are required.

1.2 Implementation requirements

Implementation of software modules has to be done by qualified developers, fully understanding the design and safety requirements.

If more than one developer is working on the navigation system software, a version control system has to be used that guarantees conflict-free development.

The implementation has to be according to the design specification and has to reflect the software style guide. Moreover, well known implementation problems (depending on the language used) have to be addressed in the implementation. This includes but is not restricted to:

- null pointer handling,
- uninitialised variables,
- range checking,
- array size verification,
- memory allocation and de-allocation,
- exception handling.

If parallel processing is used (e.g. multiple threads, tasks or processes) problems of conflict-free processing have to be addressed in the implementation. This includes but is not restricted to:

- race conditions,
- re-entrance problems,
- priority inversion,
- deadlocks.

1.3 Test requirements

In accordance with the design specification, software modules have to be tested. The test results have to be compared with the design guidelines and documented in test reports.

Tests have to incorporate module as well as system tests. Providers of a navigation system have to use extensive simulator-based tests to ensure stability of their system. The simulator must allow the simulation of a complete navigation environment including all required external sensors.

1.4 Third party components requirements

Third party components (OEM products, OEM means original equipment manufacturer) include software not developed by the navigation system provider. This includes but is not restricted to

- static or dynamic linked libraries,
- computer aided design and engineering tools producing source or object code,
- operating systems.

Third party software components have to be chosen according to the general safety requirements. The navigation system provider has to prove that third party components meet the high standards necessary for safe navigation either by providing acceptable quality certificates or by extensive and provable testing of the components

1.5 Requirements for additional services in navigation mode

Navigation systems may support additional services in navigation mode if they are useful. These services must not interfere with navigation mode.

The navigation system provider is responsible for additional test equipment, necessary to verify interface specification, protocol specification and compliance tests with the Inland ECDIS standard.

1.6 Language

Additional national versions of a type-approved Inland ECDIS shall reapply for type approval to be checked for the translation of the user interface.

1.7 Documentation requirements for users

The documentation (manuals) has to contain comprehensive information on installation, operation and service of the navigation system. The presentation of user-relevant information shall be made clear, understandable and without unnecessary technical terms. The user manual shall be available in the official CCNR languages. The technical documentation may be made available in English only.

2 Methods of testing and required results

2.1 Navigation mode operation test

2.1.1 Performance requirements

Navigation systems must make reliable estimations of position and heading. Moreover, the estimation of position and heading has to be checked by the system for conformity with the required accuracy.

Position and heading information has to be calculated and displayed for the same reference position. This should normally be the centre of the radar antenna. A new position estimate must at least be available with every revolution of the radar antenna.

2.1.1.1 Position

The navigation system has to estimate and display the position of the ship. The following minimal requirements have to be fulfilled under normal operation conditions:

- a) The average position estimation shall not deviate more than 5 meters from the true position and shall cover all systematic errors.
- b) The standard deviation σ has to be less than 5 meters and shall be based on random errors only.
- c) The system shall be capable to detect deviations of more than 3σ within 30 seconds.

These results have to be verified by a realistic test of at least 60 min.

2.1.1.2 Heading

The navigation system has to estimate and display the heading of the ship.

The following minimal requirements have to be fulfilled:

- a) The average heading angle estimation shall not deviate more than 1 degree from the radar heading direction and shall cover all systematic errors. The offset between ship heading direction and radar heading shall be less than 1 degree.
- b) The standard deviation σ has to be less than 2 degrees and shall be only based on random errors.

These results have to be verified by a realistic test of at least 60 min.

2.1.2 Sensor failure

Navigation systems have to check proper operation of the position and heading estimation online. Problems have to be detected within 30 seconds. In case of malfunction, the navigation system has to inform the user about the problem and its consequence for navigation.

If reliable navigation is not possible the navigation chart should not be displayed.

2.1.3 Performance test interface

A navigation system provider has to equip navigation systems during the compliance test with a standard NMEA interface sending the position and heading information used by the navigation system. This information has to be encoded by NMEA sentences known as GGA and PAT.

Example: GGA - Global Position System Fix Data

\$GPGGA,123519,4807.038,N,01131.324,E,1,08,0.9,545.4,M,46.9,M,,*42<CR><LF>

123519 Fix taken at 12:35:19 UTC. (This field has to provide the time of the position estimation.)

4807.038,N	Latitude 48 deg 07.38' N (This field has to provide the latitude of the fix.)
01131.324,E	Longitude 11 deg 31.324' E (This field has to provide the longitude of the fix.)
1	Fix quality (0 = invalid, 1 = GPS fix, 2 = DGPS fix (This field can have any valid value.)
08	Number of satellites being tracked. (This field can have any valid value.)
0.9	Horizontal dilution of position (This field can have any valid value.)
545.4,M	Altitude, Metres, above mean sea level. (This field is can have any valid value.)
46.9,M	Height of geoid (mean sea level) above WGS 84 ellipsoid. (This field can have any valid value.)
(empty field)	Time in seconds since last DGPS update. (This field can have any valid value.)
(empty field)	DGPS station ID number. (This field can have any valid value.)

**Example: PAT - Position and altitude message
(Ashtech proprietary position and altitude message.)**

\$GPPAT,223924.0,3922.2871,N,12159.4503,W,+/-00253.2,121.673,+/-002.59, +/-004.61,.....
...0.0031, 0.0205, 0<CR><LF>

223924.0	UTC of position. (This field has to provide the time of the position estimation.)
3922.2871,N	Latitude 39 deg 22.2871' N (This field has to provide the Latitude of the fix.)
12159.4503,W	Longitude 121 deg 59.4503' W (This field has to provide the Longitude of the fix.)
+/-00253.2	Altitude in meters. (This field can have any valid value.)
121.673	Heading in degrees. (This field has to provide the heading angle use by the navigation system.)
+/-002.59	Pitch in degrees. (This field can have any valid value.)
+/-004.61	Roll in degrees. (This field can have any valid value.)
0.0031	Attitude phase measurement error MRMS (meters). (This field can have any valid value.)
0.0205	Attitude baseline length rms error, BRMS (meters). (This field can have any valid value.)
0	Attitude reset flag ((0: good attitude, 1: rough estimate or bad attitude). (This field can have any valid value.)

Both strings have to be sent over the same NMEA interface at least every second. The position and heading have to be according to the definitions in section 2.1.1.1 and section 2.1.1.2 of this Appendix.

2.2 General software tests

2.2.1 Equipment documentation

The following documents have to be provided for admittance and have to be shipped with every navigation system:

- Users manual,
- Installation manual,
- Service manual.

The following documents and files have to be provided during the admittance procedure and are not required for end users:

- design specification,
- software style guide,
- certificates of third party software components or test and simulation protocols.

The documents and files provided must allow a complete verification of compliance with the Inland ECDIS standard.

2.2.2 Endurance test

The navigation system must pass an endurance test of 48 hours of uninterrupted operation under normal operation conditions. The system has to provide standard interfaces for performance and resource monitoring during operation. Monitoring the system must show no indication of system instability, memory leaking or any kind of performance loss over time. Navigation systems supporting additional services while running in navigation mode provide the necessary test equipment including all documents mentioned in chapter 1.7 of this Appendix.

3 Changes to certified systems

3.1 General requirements

Navigation systems installed on board must be functionally equivalent to a system certified by authorities. For every system the navigation system provider must ship a statement of compliance with the Inland ECDIS standard and its functional equivalence to the certified system.

The competent authority is entitled to check Inland ECDIS compliance of installed systems at any time.

3.2 Hardware and software changes

The navigation system provider can change software or hardware as long as Inland ECDIS compliance is maintained. Changes have to be fully documented and submitted to the competent authority together with an explanation of how the navigation system is affected by these changes. The competent authority can require a partial or complete renewal of certification if considered necessary. The aforementioned also applies to the use of an approved Inland ECDIS with another national version of the operating system.

The following changes do not affect certification of the system and require only a notice to the competent authority:

- minor changes on third party components (e.g. operation system or library updates),
- use of equivalent or better hardware components (e.g. faster microprocessor, newer)
- chip revisions, equivalent graphic card etc.),
- minor changes in source code or documentation

Page 180 intentionally left empty

Edition 1.02
16.10.2003

**Standard
Electronic Chart Display and Information System
for Inland Navigation**

Inland ECDIS

SECTION 4

**Operational and Performance Requirements,
Methods of Testing and Required Test Results**

Appendix B

**System Configurations
Figures**




Fig. 1: Inland ECDIS equipment, self-sufficient system without connection to radar




Fig. 2: Inland ECDIS equipment, self-sufficient system with connection to radar




Fig. 3: Inland ECDIS equipment with connection to radar and shared monitor




Fig. 4: Navigational radar equipment with integrated Inland ECDIS functionality

Page 184 intentionally left empty

Edition 1.02
16.10.2003

Standard

Electronic Chart Display and Information System for Inland Navigation

*Electronic Chart Display and Information System
for Inland ECDIS*

Inland ECDIS

SECTION 5

Glossary of Terms

Sources

- 1 IMO A.817(19)
- 2 IHO S-52
 - 2.1 IHO S-52, Appendix 3, Glossary
- 3 IHO S-57
- 4 Inland ECDIS Standard, Edition 1.0
 - 4.1 Section 1: Performance
 - 4.2 Section 2: Data
 - 4.2.1 Object Catalogue
 - 4.3 Section 3: Presentation
 - 4.4 Section 4: Operational Requirements and Tests
- 5 CCNR / ZKR: Radar Regulations
- 6 IEC 1174

Remarks:

Definitions of the object classes and attributes are given in the tables of IHO S-57, Appendix A, Object Catalogue and on the Object Catalogue for Inland ECDIS (Section 2, Appendix A of this Standard)

Acronyms (e. g. ECDIS) are used in all language versions in the English form.

Pages 187 – 1990 are empty

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Acronym	6-character-code of the object class/of the attribute 6-Zeichen-Code der Objektklasse/des Attributs Code en 6 caractères de la classe d'objets/de l'attribut 6 karakter code van de objectenklasse/van de attributen	4.2.1
All information density	All information density (all display) means the maximum amount of SENC information. Here, in addition to the standard display, also all other objects are displayed, individually on demand. Höchstinformationsdichte (alles) (<i>All information Display</i>) bedeutet den gesamten Informationsumfang der SENC. Hier wird zusätzlich zur Standardinformationsdichte auch der Rest der Objekte - bei Bedarf abgestuft - dargestellt. Densité maximale d'information (maximum) (<i>All information display</i>) désigne la densité maximale des informations du SENC. Outre la densité d'information standard, cette configuration permet d'afficher les autres objets, en plusieurs niveaux si nécessaire. "Maximale informatie (alles) betekent de complete hoeveelheid aan SENC informatie. Hier wordt, aanvullend aan de standaardinformatie, ook de rest van de objecten getoond, naar keuze instelbaar".	4.1
Attribute	A defined characteristic of an entity (e.g. the category of a light, the sector limits, the light characteristics etc.) Attribut; definierte Charakteristik einer Einheit (z.B. Kategorie eines Lichtzeichens, Sektorgrenzen, Helligkeitsstufen usw.) Attribut; la caractéristique définie d'une unité (par ex. la catégorie d'un feu de signalisation, les limites d'un secteur, les caractéristiques de luminosité etc.)" Een gedefinieerde karakteristiek van een eenheid (bijv. Categorie van een licht, de sector grenzen, de licht karakteristieken etc.).	2.1
Attribute copied	S-57 attributes (with their complete list of attribute values) which were extended according to the requirements of Inland ECDIS. All new attributes have the same name like their source, but written in small case letters. Kopiertes Attribut; S-57-Attribut (mit der kompletten Liste ihrer Attributwerte) das gemäß der Anforderungen von Inland ECDIS erweitert wurde. Alle neuen Attribute haben den gleichen Namen wie das ursprüngliche Attribut, allerdings in Kleinbuchstaben geschrieben. Attribut copié; attribut S-57 (avec la liste complète des valeurs d'attributs) étendu conformément aux exigences du système ECDIS intérieur. Tous les nouveaux attributs portent le nom de l'attribut d'origine, mais écrit en minuscules. S-57 attributen (met de complete lijst van attribuut waarden) die zijn uitgebreid overeenkomstig de eisen van Inland ECDIS. Alle nieuwe attributen hebben dezelfde naam als het oorspronkelijke attribuut, maar worden in kleine letters geschreven.	4.2.1
Attribute value	A specific quality or quantity assigned to an attribute (e.g. "leading light", the limiting angles, the code specifying the light's colour - see attribute). Attributwert; zu einem Attribut gehörende spezielle Qualität oder Quantität (z.B. "Leitfeuer", Grenzwinkel, Code zur Festlegung der Farbe von Lichtzeichen - siehe Attribut) Valeur de l'attribut; la qualité ou quantité associée à un attribut (par ex. "feu de direction", angle limite, code de spécification de la couleur d'un signal lumineux – Cf. attribut) Bij een attribuut behorende speciale kwaliteit of hoeveelheid (bijv. geleide licht, de grens hoeken, de code die de kelur van het licht specificeert – zie attribuut)	2.1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Cartographic object	<p>Graphical object needed to satisfy certain presentation requirements mostly associated with a real world object. The attributes of a cartographic object (if any) provide additional drawing instructions. Examples: anchorage symbol associated with an anchorage area; textual annotations.</p> <p>Kartografisches Objekt; grafisches Objekt, das zur Erfüllung der Darstellungsanforderungen benötigt wird; meist in Verbindung mit einem real existierenden Objekt. Die Attribute eines kartografischen Objektes liefern zusätzliche Zeicheninstruktionen. Bsp. Ankersymbol in Verbindung mit Ankergebiet; textliche Anmerkungen.</p> <p>Objet cartographique; objet graphique nécessaire pour satisfaire aux exigences de la représentation, généralement en liaison avec un objet existant dans la réalité. Les attributs d'un objet cartographique fournissent des indications supplémentaires relatives à sa présentation, par ex. symbole d'une ancre en liaison avec une zone de mouillage; annotations textuelles.</p> <p>Grafisch object dat nodig is om aan bepaalde weergave eisen te kunnen voldoen, meestal in relatie tot het ware object. De attributen van een cartografisch object leveren aanvullende teken instructies. Bijv. anker symbol in samenhang met een ankergebied; tekstuele opmerkingen.</p>	2.1
CIE colour calibration	<p>Procedure to confirm that the colour specified in IHO S-52 appendix 2 is correctly reproduced on the ECDIS display.</p> <p>CIE-Farbenkalibrierung; Verfahren zur Gewährleistung, dass die in IHO S-52 Anhang 2 festgeschriebenen Farben korrekt auf dem ECDIS-Bildschirm wiedergegeben werden.</p> <p>Calibrage des couleurs CEI; procédure destinée à confirmer que les couleurs spécifiées dans le document OHI-S-52, appendice 2, sont correctement reproduites à l'écran ECDIS.</p> <p>Procedure om vastteleggen dat de in IHO S-52 vastgelegde kleuren correct op het ECDIS-beeldscherm worden weergegeven.</p>	6
Cell (chart cell)	<p>Predefined, scale dependant geographic area.</p> <p>Zelle (Kartenausschnitt); vorgegeben; maßstabsabhängige geografische Fläche.</p> <p>Cellule (partie de la carte); prédefinie, aire géographique dépendant de l'échelle.</p> <p>Voor gedefinieerde schaal afhankelijk geografisch gebied</p>	2.1
Collection object	<p>Type of feature object containing information about the relationships between other objects.</p> <p>Typ eines Merkmals-Objektes, das Informationen über Beziehungen von Objekten untereinander enthält.</p> <p>Type d'un objet caractéristique contenant des informations relatives aux liens entre d'autres objets.</p> <p>Type van een karakteristiek object, dat informatie over relatie tussen andere objecten bevat.</p>	4.2.1
Compilation scale	<p>The scale with which the chart information meets the IHO requirements for chart accuracy. It is established by the producing Hydrographic office and encoded in the ENC.</p> <p>Kompilations (zusammengetragener, zusammengestellter -) maßstab; der Maßstab, bei dem die Karteninformation exakt die IHO-Anforderungen hinsichtlich der Kartengenauigkeit erfüllt; wird vom Hersteller (hydrografische Behörde) festgelegt und in ENCs verschlüsselt.</p> <p>Echelle de compilation; l'échelle à laquelle l'information cartographique est parfaitement conforme aux exigences de l'IHO relatives à la précision de la carte. Elle est établie par le fabricant (administration hydrographique) et incorporée sous forme de code dans les ENC.</p> <p>De schaal waarmee de kaart informatie overeenkomt met de IHO eisen voor kaart nauwkeurigheid. Het wordt vastgesteld door de producerende hydrografische autoriteit en in de ENC geïncorporeerd.</p>	6

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Datum	<p>A set of parameters specifying the reference surface or the reference coordinate system used for geodetic control in the calculation of coordinates of points on the earth. Commonly datums are defined as horizontal and vertical datums separately. For the practical use of the datum it is necessary to have one or more well monumented points with coordinates given in that datum.</p> <p>Datensatz, der die Bezugsebene oder das Bezugskoordinatensystem festlegt, die/das für die geodätische Überprüfung bei der Berechnung der Koordinaten von Punkten auf der Erde verwendet wird. Gewöhnlich sind Datensätze jeweils als horizontale und vertikale Datensätze definiert. Für die praktische Anwendung der Datensätze ist/sind ein oder mehrere markante (Referenz-) Punkt(e) mit Koordinaten in diesem Datensatz erforderlich.</p> <p>Série de paramètres spécifiant l'aire de référence ou le système des coordonnées de référence utilisés pour le contrôle géodésique lors du calcul des coordonnées de points sur la terre. Les séries de paramètres sont généralement définies en tant que séries horizontales et verticales de paramètres. L'application pratique des séries de paramètres nécessite un ou plusieurs points de référence marquants assortis des coordonnées de cette série de paramètres.</p> <p>Een set van parameters die het referentie vlak of het referentie coördinatie systeem gebruikt voor de geodetische controle bij de berekening van coördinaten van punten op de aarde specificeren. Gewoonlijk zijn gegevens gescheiden gedefinieerd als horizontale en verticale gegevens. Voor de praktische</p>	2.1
Datum, horizontal	<p>A set of parameters specifying the reference for horizontal geodetic control, commonly the dimensions and the location of a reference ellipsoid.</p> <p>Datensatz, der den Bezug für die geodätische Überprüfung der horizontalen Koordinaten festlegt, gewöhnlich die Abmessungen und die Lage eines Referenzellipsoids.</p> <p>Une série de paramètres spécifiant la référence pour le contrôle géodésique horizontal, généralement les dimensions et la position d'un ellipsoïde de référence.</p> <p>Een set van parameters die de referentie voor de horizontale geodetie specificeert, gewoonlijk de dimensies en de plaats van een referentie ellipsiode</p>	2.1
Datum, vertical	<p>A surface to which elevations and/or depths (soundings and tide heights) are referred. For elevations commonly a level (equipotential) surface, approximately the mean sea level is used, for depths in many cases low water.</p> <p>Eine Ebene auf die sich Höhen bzw. Tiefen (Peilungen und Tidehöhen) beziehen; für Erhebungen (im Sinne von Höhen) gewöhnlich eine (einheitliche) Oberfläche, meist die Meeresebene (m über Normal Null), für Tiefen meist Niedrigwasser.</p> <p>Une surface à laquelle font référence les élévations et/ou les profondeurs (relèvements et hauteurs des marées); pour les élévations il s'agit le plus souvent d'une surface (équipotentielle), généralement le niveau de la mer (m > NN) et les basses eaux pour la profondeur.</p> <p>Een vlak waarop zich de hoogte en de diepte (peilingen en getijde hoogte) zich betrekken. Voor verhogingen (in de zin van hoogtes) gewoonlijk een oppervlak, meestal de zeespiegel (m boven NAP), voor diepte meestal laag water.</p>	2.1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Differential GPS (DGPS)	<p>A form of GPS in which the reliability and accuracy are enhanced by broadcasting a time-varying correction message from a GPS monitoring receiver (differential mode) at a known position on shore. The corrections are fed automatically into the GPS receiver onboard and used to compute an improved position.</p> <p>Eine Form von GPS, bei dem die Zuverlässigkeit und Genauigkeit beeinflusst werden von der Funkübertragung eines zeitverschobenen Korrektursignals von einem GPS-Empfänger (Differenzanteil, Unterschiedlichkeitsprinzip) in bekannter Position auf der Oberfläche. Die Korrekturen werden automatisch in den GPS-Empfänger an Bord eingespeist und zur Berechnung einer verbesserten Position verwendet.</p> <p>Une forme de GPS avec laquelle la fiabilité et la précision peuvent être améliorées par la transmission radioélectrique d'un signal temporisé de correction d'un récepteur GPS (mode différentiel) pour une position connue par rapport à la surface. Les corrections sont intégrées automatiquement par le récepteur GPS à bord et sont utilisées pour le calcul de la correction de la position.</p> <p>Een vorm van GPS, waarbij de betrouwbaarheid en de nauwkeurheid beïnvloed wordt door de uitzending van een in tijd varierend correctiesignaal van een GPS ontvanger (differentieel modus) op een bekende positie aan land. De correcties worden automatisch in de GPS ontvanger aan boord geïntegreerd en voor de berekening van een verbeterde positie gebruikt.</p>	2.1
Display base	<p>Minimum information density; means the minimum amount of SENC information that is presented and which cannot be reduced by the operator, consisting of information that is required at all times in all geographic areas and under all circumstances.</p> <p>Basisanzeige, Mindestinformationsdichte; Mindestumfang an SENC-Information, der dargestellt wird und der durch den Betreiber nicht reduziert werden kann; enthält die Informationen, die jederzeit in sämtlichen geografischen Bereichen und unter allen Umständen erforderlich sind.</p> <p>Base de la visualisation, densité minimale d'information; désigne la quantité minimale d'information SCEN visualisable qui ne peut être réduite par l'utilisateur et contient les informations requises en permanence dans tous les secteurs géographiques et en toutes circonstances.</p> <p>Minimum informatie dichtheid, betekent de minimum hoeveelheid van SENC informatie dat wordt gepresenteerd en dat niet kan worden gereduceerd door de gebruiker; bevat de informatie dat onder alle omstandigheden wordt vereist in alle geografische gebieden.</p>	1
Display scale	<p>The ratio between a distance on the display and a distance on the ground, normalised and expressed as a ratio, e.g. 1:10 000.</p> <p>Anzeigemaßstab; das Verhältnis zwischen der Entfernung auf der Anzeige und der Entfernung auf der Erde, genormt und ausgedrückt als Maßstab, z.B. 1:10 000.</p> <p>Echelle d'affichage; le rapport entre la distance affichée et la distance réelle, normalisé et exprimé par une échelle, par exemple : 1:10 000.</p> <p>De verhouding tussen een afstand op de weergave en een afstand op de grond, genormaliseerd en uitgedrukt als verhouding, bijv. 1 : 10.000.</p>	6
EBL	<p>Electronic Bearing Line</p> <p>Elektronische Peillinie</p> <p>Relèvement électronique</p> <p>Elektrische peilingslijn</p>	5

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
ECDIS	<p>Electronic Chart Display and Information System; A navigation information system which can be accepted as complying with the up-to-date chart required by regulation V/20 of the 1974 SOLAS Convention, by displaying selected information from a system electronic navigational chart (SENC) with positional information from navigation sensors to assist the mariner in route planning and route monitoring, and if required display additional navigation-related information. The performance requirements for ECDIS are defined in the Performance Standard for ECDIS developed by IMO.</p> <p>Elektronisches Kartenanzeige- und Informationssystem; Navigations-Informations-System, das mit den aktuellen Karten gemäß der Anforderung V/20 des SOLAS-Vertrages von 1974 übereinstimmt; Anzeige einer herstellerspezifischen (systemspezifischen) elektronischen Navigationskarte (SENC) mit Positions-Informationen von Navigationssensoren zur Unterstützung des Schiffsführers bei der Reiseplanung und Reiseüberwachung und auf Wunsch Anzeige von navigationsbezogenen Informationen. Die Leistungsanforderungen für ECDIS sind im Leistungsstandard für ECDIS definiert, der von der IMO erarbeitet wurde.</p> <p>Système de visualisation des cartes électroniques et d'informations; Système de renseignements sur la navigation correspondant aux cartes actualisées conformément aux exigences de la réglementation V/20 de la Convention SOLAS de 1974; et qui, en affichant des renseignements sélectionnés d'une carte électronique de navigation fonctionnelle (SENC) propre au fabricant (et au système) comportant des indications relatives à la position fournies par des capteurs et destinée à assister le conducteur lors de la planification et la surveillance du voyage par la mise à disposition d'informations relatives à la navigation affichables sur demande. Les exigences relatives aux performances du système ECDIS sont définis dans le standard de performance pour le système ECDIS élaboré par IMO.</p> <p>Elektronische kaart weergave en informatie systeem; een navigatie informatie systeem dat met de actuele kaart overeenkomstige de eisen V/20 van het SOLAS verdrag van 1974 overeenkomt, door weergave van geselecteerde informatie van een systeem electronische navigatie kaart (SENC) met positie-informatie van navigatie-sensoren ter ondersteuning van de schipper bij de reisplanning en reis monitoring en op verzoek weergave van aanvullende navigatie gerelateerde informatie. De prestatie eisen voor ECDIS zijn in de prestatiestandaard voor ECDIS gedefinieerd, die door de IMO ontwikkeld werd.</p>	1
Edge	<p>A one-dimensional spatial object, located by two or more coordinate pairs (or two connected nodes) and optional interpolation parameters.</p> <p>Schneide, scharfe Kante, Rand, Saum; Eindimensionales räumliches Objekt, festgelegt durch zwei oder mehr Koordinatenpaare (oder zwei verbundene Knoten) und wahlweise Interpolationsparametern.</p> <p>Limite, arête, bord, lisière; objet spatial unidimensionnel représenté sur la base de deux (ou plus) paires de coordonnées (ou par deux points noudaux) et des paramètres optionnels d'interpolation.</p> <p>Rand; een eendimensionaal ruimtelijk object, vastgelegd door twee of meer coördinaten paren (of twee verbonden knooppunten) en optioneel interpolatie parameters.</p>	1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
ENC	<p>Electronic Navigational Chart; The data base, standardized as to content, structure and format, issued for use with ECDIS on the authority of government authorized hydrographic offices. The ENC contains all the chart information necessary for safe navigation and may contain supplementary information in addition to that contained in the paper chart (eg sailing directions) which may be considered necessary for safe navigation.</p> <p>Elektronische Navigationskarte; Datengrundlage standardisiert nach Inhalt, Aufbau und Form und durch staatliche hydrografische Behörden zur Verwendung von ECDIS herausgegeben; enthält alle für eine sichere Navigation notwendigen Karteninformationen und darf zusätzliche Informationen zu denen, die in der Papierkarte vorhanden sind (z.B. Fahrtrichtungen) enthalten, die als für die sichere Navigation wichtig angesehen werden.</p> <p>Carte Electronique de Navigation; base de données normalisée quant au contenu, à la structure et au format, qui est destinée à être utilisée avec le système ECDIS intérieur et est diffusée avec l'approbation des services hydrographiques agréés par les pouvoirs publics. La ENC contient tous les renseignements cartographiques nécessaires à la sécurité de la navigation et peut contenir d'autres renseignements que ceux fournis par la carte papier (des instructions nautiques, par exemple), qui sont jugés nécessaires à la sécurité de la navigation.</p> <p>Electronische navigatie kaart; de database gestandardiseerd naar inhoud, opbouw en vorm en door de bevoegde autoriteiten van het hydrografisch bureau uitgegeven voor gebruik met ECDIS.</p>	1
ENC cell	<p>The geographic division of ENC data for distributing purposes.</p> <p>ENC-Zelle (-Kartenabschnitt, d.A.); der geografische Kartenabschnitt der ENC für einen bestimmten Zweck.</p> <p>Cellule ENC; secteur géographique de la carte ENC réservé à une usage donné.</p> <p>ENC cel; het geografische gedeelte van de ENC voor een bepaald doel.</p>	6
Electronic chart	<p>Very broad term to describe the data, the software, and the electronic system, capable of displaying chart information. An electronic chart may or may not be equivalent to the paper chart required by SOLAS.</p> <p>Elektronische Karte; breitgefächterter Begriff zur Beschreibung der Daten, der Software und des elektronischen Systems für die Fähigkeit, Karteninformationen anzuzueigen. Die elektronische Karte kann aber muss nicht gleich der Papierkarte sein, die SOLAS fordert.</p> <p>Carte électronique; désignation générique utilisé pour la description de données, de logiciels et du système électronique capable d'afficher des informations cartographiques. La carte électronique ne doit pas nécessairement être identique à la carte imprimée exigée par SOLAS.</p> <p>Electronische kaart; een brede term voor de beschrijving van data, de software en het electronische systeem in staat kaart informatie weer yte geven. Een electronische kaart ikan maar moet niet gelijkwaardig aan een papieren kaart zijn die vereist is door SOLAS.</p>	2.1
Exchange Format	<p>A specification for the structure and organization of data to facilitate exchange between computer systems.</p> <p>Austauschformat; eine Beschreibung für die Struktur und Organisation von Daten zur Erleichterung des Austausches zwischen Computersystemen.</p> <p>Format d'échange; une spécification pour la structure et l'organisation de données visant à faciliter l'échange entre des systèmes informatiques.</p> <p>Wissel format; een beschrijving voor de structuur en organisatie van gegevens ter vereenvoudiging van een wisseling tussen computersystemen.</p>	2.1

Term or Abbreviation	Definition	Source
	English	
	Deutsch	
	Francais	
	Nederlands	
Exchange set	<p>Set of files representing a complete, single purpose (i.e. product specific) data transfer. For example, the ENC product specification defines an exchange set which contains one catalogue file and at least one data set file.</p> <p>Austauschsatz; Satz von Dateien für einen kompletten zweckgebundenen Datentransfer (z.B. produktsspezifisch); z.B. definiert die ENC-Produktbeschreibung einen Austauschdatensatz, der eine Katalogdatei und eine Datensatzdatei enthält.</p> <p>Fichier d'échange; série de données pour un transfert de complet et déterminé de données (par ex. spécifique au produit), ainsi, la spécification de produit ENC définit un fichier d'échange comportant un fichier catalogue et un fichier de données.</p> <p>Wisselset; Serie van gegevens voor een complete doelgebonden datatransfer (bijv. product specifiek). Bijv definieert de ENC product specificaties een wisselset die een catalogus bestand en een gegevens bestand bevat.</p>	1
Face	<p>A two dimensional spatial object. A face is a continuous area defined by a loop of one or more edges which bound it.</p> <p>(Ober-)Fläche; zweidimensionales räumliches Objekt; durchgängige Fläche definiert durch einen Linienzug (Schleife) von einem oder mehr Rändern, die diese begrenzen.</p> <p>Aire (surface); un objet bidimensionnel; une aire continue définie par un ligne (boucle) et délimitée par une ou plusieurs lignes.</p> <p>Vlak; een twee dimensionaal ruimte object. Een vlak is een continu gebied gedefinieerd door een lus van een of meer randen die deze verbinden.</p>	1
Feature Object	<p>An object which contains the non-locational information about real world entities. Feature Objects are defined in Appendix A, IHO Object Catalogue.</p> <p>Merkmals-Objekt; Objekt, das nicht-örtliche Information über die realen Gegebenheiten enthält; definiert in Anhang A, IHO Objektkatalog.</p> <p>Objet caractéristique; un objet qui contient des informations non-locales sur le contexte réel; défini à l'appendice A du catalogue d'objets de l'IHO.</p> <p>Karakteristiek object; een object dat de niet plaatselijke informatie over de werkelijkheid bevatten, gedefinieerd in Appendix A, IHO objecten catalogus.</p>	3
File	<p>An identified set of S-57 records collected together for a specific purpose. The file content and structure must be defined by a product specification.</p> <p>Datei; ein übereinstimmender Satz von S-57-Aufzeichnungen, zusammengestellt für einen bestimmten Zweck; Inhalt und Aufbau müssen durch eine Produktbeschreibung definiert sein.</p> <p>Fichier; une série d'enregistrements S-57 compilée pour un usage donné; le contenu et la structure doivent être définis par une spécification de produit.</p> <p>File; een overeenstemmende set van S-57 gegevens, samengesteld voor een speciaal doel; inhoud en opbouw moeten door een productbeschrijving gedefinieerd worden.</p>	1
Geometric primitive	<p>One of three basic geometric units of representation: point, line and area.</p> <p>Geometrisches Grundelement; eines der drei geometrischen Darstellungselemente: Punkt, Linie und Fläche.</p> <p>Elément géométrique de base; l'une des trois unités géométriques de représentation : point, ligne et aire.</p> <p>Geometrisch basiselement; een van de drie weergave elementen: punt, lijn en vlak.</p>	1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Geo Object	<p>Type of feature objects containing the descriptive characteristics of a real world entity.</p> <p>Eine Art des Merkmals-Objektes; enthält beschreibende Eigenschaften der realen Welt.</p> <p>Un type d'objet caractéristique; contient les caractéristiques descriptives du monde réel.</p> <p>Een type van karakteristiek object, inhoudende het beschrijvende karakter van de werkelijkheid</p>	4.2.1
Heading	<p>The direction in which the longitudinal axis of a craft is pointed, usually expressed in degrees from north (true, magnetic or compass).</p> <p>Fahrtrichtung; Richtung in die die Längsachse eines Schiffes zeigt; üblicherweise ausgedrückt in Grad (°) abweichend von Nord (tatsächlich, magnetisch oder Kompass).</p> <p>Sens de navigation; sens dans lequel pointe l'axe longitudinal d'un bateau, généralement exprimé en degrés (°) par rapport au nord (effectif, magnétique ou du compas).</p> <p>Vaarrichting; De richting waarin de lengte as van een schip wijst; gewoonlijk uitgedrukt in graden van de noord (Daadwerkelijk, magnetische of Kompas)</p>	2.1
Head-up display	<p>The information shown on the display (radar or ECDIS) is directed so that the vessel's heading is always pointing upward. This orientation corresponds to the visual view from the bridge in direction of the ship's heading. This orientation may require frequent rotations of the display contents. Changing the ship's course, or yawing of the vessel may render this unstabilized orientation mode unreadable.</p> <p>Kurs-Voraus-Anzeige; die Bildschirmanzeige (Radar oder ECDIS) ist so ausgerichtet, dass der Kurs des Schiffes immer nach oben zeigt. Diese Ausrichtung stimmt mit dem Ausblick von der (Schiffs-)Brücke in Kursrichtung des Schiffes überein. Diese Ausrichtung kann häufige Drehungen des Anzeigeninhaltes erfordern. Änderungen des Schiffsverlaufs oder plötzliches Gieren können dazu führen, dass diese instabile Ausrichtungsart unlesbar wird.</p> <p>Affichage cap à l'avant; affichage à l'écran (radar ou ECDIS) orienté de façon à ce que le cap du bateau pointe toujours vers le haut de l'écran. L'orientation correspond à la vue depuis le pont (du bateau) dans le sens de navigation. Cette orientation peut nécessiter de fréquentes rotations du contenu affiché. La modification du cap ou un virage soudain peuvent rendre illisible ce mode d'orientation instable.</p> <p>Koersvoor weergave; Een beeldschermweergave (radar of ECDIS) is zo ingracht dat de koers van het schip altijd naar boven wijst. Deze oriëntatie stemt overeen met het uitzicht vanuit de stuurhut in de koersrichting van het schip. Deze oriëntatie kan frequente draaiing van het beeld vereisen. Veranderingen van de scheepskoers, of plotseling gieren kan deze instabiele oriëntatie onleesbaar weergeven.</p>	2.1
HO-Information	<p>Information content of the SENC originated by hydrographic offices. It consists of the ENC content and updates to it.</p> <p>Informationsinhalt von SENC hergestellt durch hydrografische Büros. Er besteht aus ENC und Aktualisierungen dazu.</p> <p>Information contenue dans le SENC et fournie par les services hydrographiques. Elle se compose des ENC et de leurs actualisations.</p> <p>Informatieinhoud van SENC vervaardigd door hydrografische bureos. Het bestaat uit ENC en actualisering daarvan.</p>	2.1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
IEC	<p>International Electrotechnical Commission: An international organization which produces world standards for electrical and electronical engineering with the objective of facilitating international trade.</p> <p>Internationale Elektrotechnische Kommission; internationale Organisation, die weltweite Standards für Elektrik und Elektrotechnik zur Erleichterung des internationalen Handels herausgibt.</p> <p>Commission Electrotechnique Internationale; une organisation internationale de normalisation sur le plan mondial dans le domaine de l'électricité et de l'électrotechnique visant à faciliter le commerce international.</p> <p>Internationale elektronische commissie; Een internationale organisatie, die wereldwijd standaarden voor electriciteit en elektrotechniek voor vereenvoudiging van de internationale handel uitgeeft.</p>	2.1
IHO	<p>International Hydrographic Organization: Coordinates the activities of national hydrographic offices; promotes standards and provides advice to developing countries in the fields of hydrographic surveying and production of nautical charts and publications.</p> <p>Internationale Hydrografische Organisation; koordiniert die Aktivitäten der nationalen hydrographischen Institutionen, verbreitet Standards und berät Entwicklungsländer auf dem Gebiet der hydrographischen Vermessung und Produktion von nautischen Karten und Veröffentlichungen.</p> <p>Organisation hydrographique internationale; coordonne les activités des institutions hydrographiques nationales, publie des standards et conseille des pays en voie de développement dans le domaine de l'étude hydrographique ainsi que de la production de cartes nautiques et de publications.</p> <p>Internationale hydrografische organisatie; coördineert de activiteiten van de nationale instituten, bevordert standaarden en geeft advies aan ontwikkelingslanden op het gebied van hydrografische metingen en productie van nautische kaarten en publicaties.</p>	2.1
(IHO-) S-52	<p>Specifications for chart content and display aspects of ECDIS.</p> <p>Beschreibung für Karteninhalt und Gesichtspunkte der Darstellung von ECDIS.</p> <p>Spécification du contenu des cartes et des aspects de visualisation ECDIS.</p> <p>Specificaties voor de kaartinhoud en de aspecten van de weergave van kaarten.</p>	2
(IHO-) S-52 App. 1	<p>Guidance on updating the Electronic Navigational Chart of the IHO.</p> <p>Leitlinie für das Aktualisieren der ENC der IHO.</p> <p>Lignes directrices pour l'actualisation des CEN de l'IHO.</p> <p>Richtlijnen voor actualisering van de ENC van de IHO</p>	2
(IHO-) S-52 App. 2	<p>Colours & symbols specifications for ECDIS.</p> <p>Farb- und Symbolbeschreibungen für ECDIS.</p> <p>Description des couleurs et symboles pour ECDIS.</p> <p>Kleur- en symboolbeschrijving voor ECDIS</p>	2
(IHO-) S-57	<p>IHO Transfer standard for digital hydrographic data.</p> <p>IHO-Übertragungsstandard für digitale hydrografische Daten.</p> <p>Norme de l'OHI pour la transmission digitale de données hydrographiques.</p>	3

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
	IHO overdrachtsstandaard voor de digitaler hydrografische kaarten.	
(IHO-) S-57 App. A	IHO Object Catalogue. IHO-Objektkatalog für ECDIS. Catalogue d'objets de l'OHI pour le système ECDIS. IHO objecten catalogus	3
(IHO-) S-57 App. B	Product Specifications. Produktbeschreibung für ECDIS-Daten. Spécification de produit pour les données ECDIS. Product beschrijvingen voor ECDIS gegevens	3
IMO	International Maritime Organization: Formerly called IMCO, the IMO is the specialized agency of the United Nations responsible for maritime safety and efficiency of navigation. Internationale Seefahrtsorganisation; früher IMCO, die IMO ist die Behörde der Vereinten Nationen, die sich mit der Sicherheit und Wirtschaftlichkeit der Navigation auf See befasst. Organisation Maritime Internationale; anciennement IMCO, l'IMO est l'institution spécialisée des Nations-Unies chargée de la sécurité et de la l'efficacité de la navigation maritime. Internationale Maritime Organisatie; vroeger IMCO; de IMO is de autoriteit van de Verenigde naties, verantwoordelijk voor de veiligheid en de efficiëntie van de navigatie ter zee.	2.1
Information Mode	means the use of the Inland ECDIS for information purposes only without overlaid radar image. Informationsmodus; Verwendung des Inland ECDIS nur für Informationszwecke ohne überlagertes Radarbild. Mode information; utilisation du système ECDIS intérieur limitée à l'information sans super position de l'image radar. Informatiemodus; Gebruik van de Inlanmd ECDIS alleen voor infomatie doeleinden zonder overlapt radarbeeld.	4.1
Inland ECDIS	An Electronic Chart Display and Information System for inland navigation, displaying selected information from a Inland System Electronic Navigational Chart (Inland SENC) and optionally, information from other navigation sensors. Binnen-ECDIS; System zur elektronischen Darstellung von Karten der Binnenschifffahrtsstraßen und damit verbundenen Informationen, das ausgewählte Informationen aus einer herstellerspezifischen elektronischen Binnenschifffahrtskarte (Inland SENC) und wahlweise Informationen anderer Messwertgeber des Schiffes darstellt. ECDIS intérieur; système de visualisation des cartes électroniques de navigation intérieure et d'information, affichant des renseignements sélectionnés d'une carte électronique de navigation intérieure fonctionnelle (SENC Intérieure) et, en option, les données fournies par d'autres capteurs de navigation. Binnen ECDIS; Systeem voor de elektronische weergave van binnenvaartkaarten en de daarvan verbonden informatie, die geselcteerde informatie uit een specifiek geproduceerde elektronische binnenvaartkaart (Inland SENC) en ter keuze informatie van aandere navigatie sensoren weergeeft.	4.1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Inland ENC	<p>Inland Electronic Navigational Chart; The database, standardised as to content, structure and format, issued for use with Inland ECDIS. The Inland ENC complies to the IHO standards S-57 and S-52, enhanced by the additions and clarifications of this standard for Inland ECDIS. The Inland ENC contains all essential chart information and may also contain supplementary information that may be considered as helpful for navigation.</p> <p>Elektronische Binnennavigationskarte; Datenbank, standardisiert bezüglich Inhalt, Struktur und Format, die zum Gebrauch mit Inland ECDIS herausgegeben wird; entspricht den IHO-Standards S-57 und S-52 mit den Ergänzungen und Klarstellungen dieses Standards für Inland ECDIS; enthält alle wesentlichen Karteninformationen und kann auch zusätzliche Informationen, die als hilfreich für die Schifffahrt angesehen werden können, enthalten.</p> <p>Carte Electronique de Navigation intérieure; base de donnée standardisée du point de vue de son contenu, de sa structure et de son format, publiée pour une utilisation avec le système ECDIS intérieur et conforme aux standards de l'IHO S-57 et S-52 complétés par des précisions relatives au système ECDIS intérieur; comporte toutes les informations cartographiques importantes et peut contenir d'autres informations susceptibles d'être utiles à la navigation.</p> <p>Elektronische binnenvaartkaarten voor de navigatie; De databank, gestandaardiseerd met betrekking tot inhoud, structuur en format, die voor gebruik met Inland ECDIS wordt uitgegeven. Inland ENC is in overeenstemming met de IHO standaard S-57 en S-52 met de aanvullingen en verduidelijkingen van deze standaard voor Inland ECDIS. Inland ENC bevat alle essentiële kaartinformatie en kan ook andere informatie bevatten die als hulp voor de scheepvaart kan worden gezien.</p>	4.1
Inland SENC	<p>Inland System Electronic Navigational Chart; a data base resulting from the transformation of the Inland ENC by Inland ECDIS for appropriate use, updates to the Inland ENC by appropriate means and other data added by the skipper. It is this data base that is actually accessed by the Inland ECDIS for the display generation and other navigational functions. The Inland SENC may also contain information from other sources.</p> <p>Herstellerspezifische Elektronische Binnenschiffahrtskarte; Datenbank, die sich aus der Transformation von Inland ENC durch Inland ECDIS für eine geeignete Anwendung ergibt und die durch Aktualisierungen der Inland ENCs mit geeigneten Mitteln und außerdem durch Daten des Schiffsführers ergänzt ist; Datenbank, auf die tatsächlich durch Inland ECDIS für die Erzeugung der Darstellung und anderer nautischer Funktionen zugegriffen wird. Inland-SENC kann auch Informationen aus anderen Quellen enthalten.</p> <p>Carte électronique pour la navigation intérieure configurée par le fabricant; une base de données résultant de la transformation de la ENC intérieure par le système ECDIS intérieur en vue d'une utilisation appropriée et complétée par l'actualisation des CEN intérieure par des moyens appropriés et par des données ajoutées par le batelier; base de données effectivement consultée par le système ECDIS intérieur pour l'élaboration des données affichées et pour d'autres fonctions nautiques. Le SCEN intérieure peut aussi contenir des informations provenant d'autres sources.</p> <p>Specifiek elektronische binnenvaartkaarten voor de navigatie; een databank, die het resultaat is van de transformatie van Inland ENC door Inland ECDIS voor een bepaald gebruik en die door actualisering van de Inland ENC met geëigende middelen en bovendien met data van de schipper aangevuld. Deze databank wordt feitelijk gebruikt door Inland ECDIS voor de ontwikkeling van de weergave en de andere nautische functies. De SENC kan ook informatie uit andere bronnen bevatten.</p>	4.1
INT 1	<p>Description entry for object classes and attributes; reference to the legend of paper charts. Beschreibung des Eintrages für Objektklassen und Attribute, Legende für Papier(see)karten. Description de classes d'objets et d'attributs, légende pour les cartes (maritimes) imprimées. Beschrijving van de aantekening voor objectklassen en attributen, referentie tot de legenda van papieren kaarten.</p>	4.2.1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Integrated display	<p>means a head-up, relative-motion picture consisting of the Inland SENC overlaid with the radar-image with matching scale, offset and orientation.</p> <p>Integrierte Darstellung; vorausorientiertes, relativ zum Schiff bewegtes Bild, bestehend aus der Inland-SENC und überlagert mit dem Radarbild mit angepasstem Maßstab, Exzentrizität und Ausrichtung.</p> <p>Visualisation intégrée; une image verticale de mobilité relative par rapport à la terre fournie par le SENC intérieur, à laquelle est superposée une image radar aux paramètres d'échelle, de distance et d'orientation adaptées.</p> <p>Geïntegreerde weergave; vooruitgeoriënteerd, relatief t.o.v. het schip bewegend beeld, bestaande uit de Inland SENC bedekt met het radarbeeld met aangepaste schaal, excentriciteit en orientatie.</p>	4.1
M-4	<p>Description entry for object classes and attributes; reference to the IHO-Publication M-4 (Chart Specifications of the IHO)</p> <p>Beschreibung des Eintrages für Objektklassen und Attribute, Verweis auf IHO-Publikation M-4 (Chart Specifications of the IHO)</p> <p>Description de l'entrée pour les classes d'objets et les attributs, renvoi à la publication IHO M-4 (Chart specifications of the IHO)</p> <p>Beschrijving van de aantekening voor objectklassen en attributen, referentie tot de IHO-publicatie M-4 (Chart Specifications of the IHO)</p>	2
Look-up table	<p>Look-up table</p> <p>Übersichtstafel, Nachschlagetafel</p> <p>Table de visualisation, table de recherche</p> <p>Overzichts tabel, Naslag tabel</p>	
Meta object	<p>Type of feature objects; additional area related information, e. g. survey source</p> <p>Eine Art des Merkmals-Objektes; enthält gebietsbezogene Zusatzinformationen z.B. Vermessungsgrundlage</p> <p>Un type d'objet caractéristique; contient des informations supplémentaires relatives à un secteur donné, par ex. source de références</p> <p>Type van karakteristieke objecten; aanvullende gebieds gebonden informatie, bijv. inspectie bron.</p>	4
Navigation Mode	<p>means the use of the Inland ECDIS for conning the vessel with overlaid radar image.</p> <p>Navigationsmodus; Verwendung des Inland ECDIS beim Steuern des Schiffes mit überlagertem Radarbild.</p> <p>Mode navigation; utilisation du système ECDIS intérieur durant la conduite du bateau avec super position de l'image radar.</p> <p>Navigatie modus; het gebruik van Inland ECDIS bij het sturen van het schip met overlaat radarbeeld.</p>	4.1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Object	<p>A digital representation of all or a part of an entity by its characteristics (attributes), its geometry, and (optionally) its relationships to other features (e.g., the digital description of a light sector specifying, amongst others, sector limits, the colour of the light, the visibility range, etc., and a link to a light tower, if any).</p> <p>Digitale (Daten und Informationen in Zeichenform enthaltende) Darstellung von Gegenständen (zu Gänze oder Teile davon) mit ihren Charakteristiken (Attribute), ihrer Geometrie, und Wahlweise in ihrer Beziehung zu anderen Merkmalen (z.B. verschlüsselte Beschreibung eines Leuchtfreuersektors, mit unter anderem Sektorgrenzen, Farbe des Lichts, Reichweite der Sichtbarkeit, Verbindung mit einem Leuchtturm).</p> <p>Représentation digitale (contenant des données et informations sous forme de symboles) d'objets (entiers ou partiels) avec leurs caractéristiques (attributs), leur géométrie et en option leur lien avec d'autres caractéristiques (par ex. description codée d'un secteur équipé de feux, avec notamment des limites de secteurs, la couleur du feu, la distance de visibilité et le lien avec un phare).</p> <p>Digitale (gegevens en informatie in de vorm van symbolen) presentatie van voorwerpen (geheel of gedeeltelijk) met karakteristieken (attributen), de geometrie en in relatie tot andere aspecten (bijv. digitale beschrijving van een licht sector, met onder andere sectorgrenzen, kleur van het licht, reikwijdte der zichtbaarheid en een verbinding met de vuurtoren)</p>	2
Object catalogue	<p>The comprehensive list of currently identified object classes (including cartographic objects and composite objects), their appropriate attributes and the full range of allowable attribute values. It can be compared to the Chart 1 (INT 1) as the legend of the paper chart, a collection of allowed hydrographic object classes.</p> <p>Zusammenfassung aller IHO-Objektklassen (einschließlich kartografischer und zusammengesetzter Objekte) mit zugelassenen Eigenschaften und Eigenschaftswerten; der Objektkatalog entspricht der Karte 1 für die Seeschiffahrtsstraßen (INT 1) und enthält zusätzlich die speziellen Objekte für die Binnenschifffahrt.</p> <p>Liste complète de toutes les classes d'objets de l'IHO (y compris les objets cartographiques et composites) avec des caractéristiques ou valeurs de caractéristiques autorisées; le catalogue d'objets intérieur correspond à la carte 1 pour les voies de navigation maritime (INT 1) et comporte en outre des objets spécifiques à la navigation intérieure.</p> <p>Samenvatting van alle IHO-objectenklassen (inclusief kartografische en samengestelde objecten) met toegepaste eigenschappen en de volle reeks van toegelaten attribuut waarden. Het kann worden vergeleken met kaart 1 (INT 1) als de legenda voor de papieren kaart, een collectie van toegelaten hydrografische objectklassen.</p>	4.2
Object class	<p>A defined group of entities to be considered equivalent to each other, e.g. the light-vessels.</p> <p>Definierte Gruppe von Einheiten, die als gleichwertig angesehen werden können, z.B. Feuerschiffe.</p> <p>Groupe défini d'unités pouvant être considérées comme étant équivalentes les unes par rapport aux autres, par exemple les bateaux-feu.</p> <p>Een gedefinieerde groep van eenheden, die als gelijkwaardig beschouwd kunnen worden, bijv lichtscheepen.</p>	2

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Object class copied	<p>S-57 object classes (with their complete set of attributes) which were extended according to the requirements of Inland ECDIS. All new object classes have the same name like their source, but are written in small case letters.</p> <p>Kopierte Objektklasse; S-57 Objektklassen (mit ihrem kompletten Satz von Attributen) erweitert gemäß der Anforderungen von Inland ECDIS. Alle neuen Objektklassen haben den gleichen Namen wie ihr Ursprung, allerdings in Kleinbuchstaben geschrieben.</p> <p>Classe d'objet copiée; classe d'objet S-57 (avec la liste complète des valeurs d'attributs) étendu conformément aux exigences du système ECDIS intérieur. Toutes les nouvelles classes d'objets portent le nom de l'attribut d'origine, mais écrit en minuscules.</p> <p>Gekopiéerde objectklasse: S 57 objectklasse (met de totale set attributen) uitgebreid overeenkomstig de vereisten van Inland ECDIS. Alle nieuwe objectklassen hebben dezelfde naam als haar oorsprong, maar klein geschreven.</p>	4.2.1
Other navigational information	<p>Navigational Information not contained in the SENC, that may be displayed by an ECDIS, such as radar information.</p> <p>Nautische Information, die nicht in der SENC enthalten ist, aber durch ECDIS angezeigt werden kann, wie Radarinformation.</p> <p>Information nautique non contenue dans le SENC mais pouvant être affichée par le système ECDIS, par exemple l'information radar.</p> <p>Nautische informatie, die niet in de SENC is opgenomen, maar door ECDIS kann worden weergegeven, zoals radarinformatie.</p>	2
Overscale	<p>Displaying data at a larger scale than it was compiled for.</p> <p>Datenanzeige in einem größeren Maßstab als ursprünglich bei der Herstellung benutzt.</p> <p>Affichage de données à une échelle supérieure à celle retenue lors de la réalisation.</p> <p>Gegevens weergave in een grotere schaal dan waarvoor het was gemaakt</p>	2
Own-ship	<p>The term which identifies the vessel upon which an ECDIS is operating.</p> <p>Eigenes Schiff; Begriff für das Schiff auf dem man sich gerade befindet und auf dem ECDIS ausgeführt wird.</p> <p>Bateau porteur; désigne le bateau sur lequel se trouve l'opérateur et à bord duquel le système ECDIS est en cours d'utilisation.</p> <p>Eigen schip; de term die het schip identificeert waarop man zich bevindt en waarop de ECDIS werkzaam is.</p>	2

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Own ship's safety contour	<p>The contour related to the own ship selected by the ship's master out of the contours provided for in the SENC, to be used by ECDIS to distinguish on the display between the safe and the unsafe water, and for generating anti-grounding alarms.</p> <p>Schiffseigene Sicherheitskontur, Sicherheitstiefenlinie; die Tiefenlinie, die der Schiffsführer im Hinblick auf den Tiefgang des eigenen Schiffes aus den Tiefenlinien ausgewählt hat, die in der SENC enthalten sind; verwendet, um in ECDIS auf der Anzeige zwischen sicherem und unsicherem Fahrwasser unterscheiden zu können und zum Erzeugen von Fehltiefen-Alarmen.</p> <p>Contours de sécurité du bateau porteur , ligne de profondeur de sécurité; la ligne de profondeur sélectionnée par le conducteur en fonction de l'enfoncement de son propre bateau parmi les lignes de profondeur disponibles dans le SENC; utilisé afin de faire la distinction dans le système ECDIS entre les eaux sûres ou présentant un risque et pour la génération d'alarmes en présence de hauts-fonds.</p> <p>Veiligheidscontour van het eigen schip, veiligheids dieptelijn, de dieptelijn, die de schipper met het oog op de diepgang van het eigen schip, uit de dieptelijnen in de SENC heeft gekozen, om te worden gebruikt in ECDIS om bij de weergave veilig en onveilig vaarwater te kunnen onderscheiden en om alarmen te genereren te oorkoming van aan de grondlopen.</p>	2
Performance standard	<p>Standard developed under the authority of IMO to describe the minimum performance requirements for navigational devices and other fittings required by the SOLAS Convention.</p> <p>Leistungsstandard; unter Federführung der IMO entwickelter Standard zur Beschreibung der Mindestleistungsanforderungen für Navigationsgeräte und andere Ausrüstungen laut Anforderung aus der SOLAS-Vereinbarung.</p> <p>Standard de performances; standard élaboré dans le cadre de l'IMO pour décrire les exigences minimales relatives aux performances pour les appareils de navigation et d'autres équipements conformément aux exigences de la convention SOLAS.</p> <p>Prestatiestandaard; standaard ontwikkeld onder de bevoegdheid van de IMO ter beschrijving van de minimum prestatie vereisten voor navigatieapparatuur en andere uitrusting overeenkomstig de SOLAS conventie.</p>	2
Pick report (Object report)	<p>Short information; a window in which additional information regarding the clicked-on objects of the ENC is shown.</p> <p>Kurzinformation, Objektbericht; Fenster, in dem ergänzende Informationen zu den jeweils angeklickten Objekten der ENCs angezeigt werden.</p> <p>Information succincte, rapport d'objet; fenêtre dans laquelle sont affichées des informations complémentaires relatives aux objets représentés sur les ENC après activation par le pointeur.</p> <p>Pick rapport, object rapport; korte informatie; een venster waarin aanvullende informatie voor de aangeklikte objecten van de ENC wordt weergegeven.</p>	

Term or Abbreviation	Definition	Source
English Deutsch Français Nederlands		
Presentation library	<p>A set of mostly digital specifications, composed of symbol libraries, colour schemes, look-up tables and rules, linking every object class and attribute of the SENC to the appropriate presentation of the ECDIS display. Published by IHO as Appendix 2 of its Special Publication 52 (S-52).</p> <p>Darstellungsbibliothek; Satz von meist in Zeichen und Zahlen verschlüsselten Anforderungen, zusammengestellt aus Symbolbibliotheken, Farbschemata, Nachschlagetafeln und Regeln, der jede Objektklasse und jedes Attribut der SENC zu einer nach IHO-S-57, Anhang 2 geeigneten Darstellung in der ECDIS-Anzeige verkettet.</p> <p>Bibliothèque des représentations; série d'exigences généralement codées en signes et en lettres, composées à partir de bibliothèques de symboles, de schémas de couleurs, de tables de recherche et de règles, associant chaque classe d'objets et attribut du SCEN à une représentation appropriée affichée par le système ECDIS conformément à l'appendice 2 au document S-57 de l'IHO.</p> <p>Weergave bibliotheek; een set van digitale specificaties, samengesteld uit symboolbibliotheken, kleurenschema's, naslagtabellen en regels, die elke objectenklasse en elk attribuut van de SENC voor de geeigende weergave van het ECDIS systeem, gepubliceerd door de IHO als appendix 2, S 52</p>	2
Product specification	<p>A defined subset of the entire specification combined with rules, tailored to the intended usage of the transfer data.</p> <p>Produktbeschreibung; definierter Teil einer vollständigen Beschreibung verbunden mit Vorschriften/Regeln und zugeschnitten auf die beabsichtigte Datenübertragung.</p> <p>Description de produit; partie définie d'une spécification complète associée à des prescriptions/règles et adaptée au transfert de données prévu.</p> <p>Produktbeschrijving; gedefinieerde deel van een volledige beschrijving verbonden met voorschriften/rgels en toegesneden op de beoogde ggevens overdracht.</p>	1
Range	<p>Sequential switchable distance of a radar.</p> <p>Sequentiell schaltbarer Entfernungsbereich bei Radaranlagen.</p> <p>Portée commutable de manière séquentielle sur les appareils radar.</p> <p>Sequentieel schakelbare afstand bij een radarinstallatie</p>	5
Reference INT 1	<p>The reference to the legend of the paper chart at the classification of the object class/of the attribute.</p> <p>Referenz auf die Legende der Papierkarte bei der Beschreibung der Objektklasse/des Attributs.</p> <p>Référence à la légende de la carte imprimée lors de la description de la classe d'objet/de l'attribut.</p> <p>Referentie tot de legenda van de papierkaart bij de beschrijving van de objectklasse/ van de attributen</p>	3
Reference M-4	<p>The reference to the legend of the IHO-Publication M-4 (Chart Specifications of the IHO) at the classification of the object class/of the attribute.</p> <p>Referenz auf die IHO-Publication M-4 (Chart Specifications of the IHO) bei der Beschreibung der Objektklasse/des Attributs.</p> <p>Référence à la publication IHO M-4 (Chart specifications of the IHO) pour la description de la classe d'objet/de l'attribut.</p> <p>Referentie tot te legenda van de IHO publicatie M-4 (kaart specifikatie van de IHO) bij de beschrijving van de objectklasse/ van de attributen.</p>	3

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Relative motion display	<p>A relative motion display shows the chart information, and radar targets, moving relative to the vessel position fixed on the screen.</p> <p>Anzeige der relativen Bewegung; zeigt Karteninformation und Radarobjekte in relativer Bewegung zur Schiffsposition, die auf dem Bildschirm fixiert ist.</p> <p>Affichage du mouvement relatif; affiche à l'écran en mouvement relatif des informations cartographiques et des objets détectés par le radar par rapport à la position du bateau présentée à l'écran.</p> <p>Weergave van de relatieve beweging; toont kaartinformatie en radarobjecten in relatieve beweging tot de scheepspositie, dat op het beeld is vastgelegd.</p>	2
Route monitoring	<p>The operational navigational ECDIS function in which the chart information is displayed, under control of the positioning sensor input, according to the vessel's present position (either in true motion or relative motion mode).</p> <p>Fahrtroutenüberwachung; operationelle ECDIS-Navigationsfunktion bei der die Karteninformation unter Kontrolle der Positionsangabe entsprechend der momentanen Schiffsposition (entweder in tatsächlicher oder relativer Bewegung) angezeigt wird.</p> <p>Surveillance de l'itinéraire; fonction de navigation opérationnelle du système ECDIS avec laquelle l'information cartographique est affichée avec un contrôle de la position déterminée par rapport à la position actuelle du bateau (en mouvement réel ou relatif).</p> <p>Route monitoring; de operationele ECDIS navigatiefunctie waarbij de kaart informatie, onder controle van de positie weergave overeenkomstig de huidige scheepspositie (of in werkelijke beweging danwel relatieve beweging) wordt weergegeven.</p>	1
Route planning	<p>An ECDIS function in which the area is displayed which is needed to study the intended route, to select the intended track, and to mark the track, its way points and navigational notes.</p> <p>Fahrtroutenplanung; ECDIS-Funktion, in der das Gebiet angezeigt wird, was benötigt wird um die vorgesehene Route zu studieren, die vorgesehene Fahrspur auszuwählen und zu markieren, ihre Meilensteine (Brechpunkte) und navigatorisch bedeutsame Bemerkungen.</p> <p>Planification de l'itinéraire; une fonction ECDIS affichant le secteur requis pour l'étude de l'itinéraire, le choix du chenal et pour le marquage de la route, de ses repères et d'observations nautiques utiles.</p> <p>Route planning; een ECDIS functie waarin het gebied weergegeven wordt, dat nodig is om de geplande route te bestuderen, de geplande koers te kiezen en de way-points en de bemerkingen voor de navigatie te markeren.</p>	1
SCAMIN	<p>The minimum scale at which the object may be used e.g. for ECDIS presentation.</p> <p>Der kleinste Maßstab, in dem ein Objekt in ECDIS angezeigt werden darf.</p> <p>La plus petite échelle avec laquelle l'affichage d'un objet est autorisé dans une représentation ECDIS.</p> <p>De kleinste schaal waarin een object in ECDIS aangegeven mag worden.</p>	

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
SENC	<p>System Electronic Navigational Chart; a data base resulting from the transformation of the ENC by ECDIS for appropriate use, updates to the ENC by appropriate means and other data added by the mariner. It is this data base that is actually accessed by the ECDIS for the display generation and other navigational functions. The SENC may also contain information from other sources.</p> <p>Herstellerspezifische Elektronische Schifffahrtskarte; Datenbank, die sich aus der Transformation von ENC durch ECDIS für eine geeignete Anwendung ergibt und die durch Aktualisierungen der ENCs mit geeigneten Mitteln und außerdem durch Daten des Schiffsführers ergänzt ist; Datenbank, auf die tatsächlich durch ECDIS für die Erzeugung der Darstellung und anderer nautischer Funktionen zugegriffen wird. SENC kann auch Informationen aus anderen Quellen enthalten.</p> <p>Carte électronique pour la navigation intérieure fonctionnelle ; une base de données résultant de la transformation de la ENC par le système ECDIS intérieur pour un usage rationnel, de la mise à jour de la ENC intérieure par des moyens appropriés et de l'adjonction d'autres données par le batelier. C'est à cette base de données que le système ECDIS intérieur accède en fait pour engendrer l'image et pour d'autres fonctions de navigation. La SENC intérieure peut également contenir des renseignements émanant d'autres sources.</p> <p>Door de fabrikant vervaardige electronische kaart voor de binnenvaart. Databank die is gebaseerd op de vertaling van ENC naar ECDIS voor toegepast gebruik en die door actualisering van ENC en bovendien door gegevens van schippers vervolmaakt is. Juist deze informatie wordt gebruikt door ECDIS voor ontwikkeling, presentatie en voor andere nautische functionaliteiten. De SENC kan ook onderdelen uit andere informatiebronnen bevatten".</p>	4.1
Spatial object	<p>An object which contains locational information about real world entities.</p> <p>Räumliches Objekt; Objekt, das örtliche Informationen über reale Einheiten enthält.</p> <p>Objet de localisation; un objet contenant les informations locales relatives à des unités réelles.</p> <p>Ruimtelijk object; een object dat plaatselijke informatie over de werkelijkheid bevat.</p>	1
Set_Attribute A:	<p>A subset; the individual characteristics of the object.</p> <p>Attributgruppe A; individuelle Eigenschaften eines Objekts.</p> <p>Groupe d'attributs A; caractéristiques individuelles d'un objet.</p> <p>Attribuut set A; individuele eigenschappen van een object.</p>	4.2.1
Set_Attribute B:	<p>A subset; the information of the use of an object.</p> <p>Attributgruppe B; Information über den Gebrauch eines Objekts.</p> <p>Groupe d'attributs B; Information relative à l'utilisation d'un objet.</p> <p>Attribuut set B; informatie over het gebruik van de objecten.</p>	4.2.1
Set_Attribute C:	<p>A subset; the information about the administration on the origin of data.</p> <p>Attributgruppe C; administrative Informationen über die Herkunft der Daten.</p> <p>Groupe d'attributs C; Informations administratives relatives à la source des données.</p> <p>Attribuut set C; administratieve informatie over de herkomst van de gegevens.</p>	4.2.1

Term or Abbreviation	Definition	Source
	English Deutsch Français Nederlands	
Standard display	<p>Standard Information Density means the default amount of SENC information that shall be visible when a chart is first displayed on ECDIS first.</p> <p>Standardanzeige, bedeutet den Standardumfang an SENC-Informationen, der zuerst sichtbar sein muss, wenn die Karte in ECDIS angezeigt wird.</p> <p>Affichage standard; désigne la densité standard des informations du SENC devant être visibles en premier lors de l'affichage de la carte par le système ECDIS.</p> <p>Standaard weergave, betekent de omvang van de standaard van SENC informatie, die pas zichtbaar moet zijn wanneer de kaart in ECDIS wordt weergegeven.</p>	1
SOLAS	<p>International Convention for the Safety of Life at Sea developed by IMO. The contracting governments undertake to promulgate all laws, decrees, orders and regulations and to take all other steps which may be necessary to give the present convention full and complete effect, so as to ensure that, from the point of view of safety of life, a ship is fit for the service for which it is intended (Article Ib of SOLAS).</p> <p>Internationales Abkommen über die Sicherheit des Lebens auf See, entwickelt durch die IMO. Die Unterzeichnerstaaten verpflichten sich, alle Gesetze, Verordnungen, Ausführungsbestimmungen und sonstige Vorschriften zu erlassen und alle sonstigen Maßnahmen zu treffen, die erforderlich sind, um diesem Übereinkommen volle Wirksamkeit zu verleihen und dadurch zu gewährleisten, dass sich im Hinblick auf den Schutz des menschlichen Lebens ein Schiff für seinen Verwendungszweck eignet (Artikel Ib der SOLAS).</p> <p>Convention internationale pour la sauvegarde de la vie humaine en mer, élaborée par l'IMO. Les Etats contractants s'engagent à promulguer toutes lois, tous décrets, ordres et règlements et à prendre toutes autres mesures nécessaires pour donner à la Convention son plein et entier effet, afin de garantir que, du point de vue de la sauvegarde de la vie humaine, un navire est apte au service auquel il est destiné.</p> <p>Internationale conventie van Safety of life at Sea ontwikkeld door de IMO. De verdragsstaten verplichten zich alle wetten, verordeningen, uitvoeringsregelingen en overige voorschriften uit te vaardigen en alle overige maatregelen te treffen, die noodzakelijk zijn om deze overeenkomst volledig werkzaam te laten zijn en daardoor te verzekeren, dat met het oog op de bescherming van de mens een schip voor zijn doel geschikt is (Artikel 1b van SOLAS).</p>	2.1
User-defined settings	<p>Means the possibility to use and store a profile of display and operation controls-settings.</p> <p>Benutzerdefinierte Einstellungen; Möglichkeit, ein Profil von Anzeige- und Betriebseinstellungen zu verwenden und zu speichern.</p> <p>Configuration par l'utilisateur; la possibilité d'utiliser et d'enregistrer une configuration donnée pour les paramètres d'affichage et de fonctionnement.</p> <p>Voor de gebruiker gedefinieerde instellingen; betekent de mogelijkheid om een profiel van weergave en gebruiksininstellingen te gebruiken en vast te leggen.</p>	4.1
Vector	<p>Spatial information whose data model is based on graph theory.</p> <p>Räumliche Information deren Datenmodell sich auf eine Graphentheorie begründet.</p> <p>Information spatiale dont le modèle de données s'appuie sur une théorie graphique.</p> <p>Ruimtelijke informatie waarvan het gegevensmodel is gebaseerd op de grafische theorie.</p>	1
VRM	<p>Variable Range Marker.</p> <p>Variabler Entfernungsmessring.</p> <p>Cercle variable de mesure des distances.</p> <p>Variabele afstandsmeetring</p>	5

Term or Abbreviation	Definition	Source
	English Deutsch Francais Nederlands	
WGS 84	<p>WORLD GEODETIC SYSTEM: A global geodetic reference system developed by the USA for satellite position fixing and recommended by IHO for hydrographic and cartographic use.</p> <p>Weltweites Geodätisches System; von den USA entwickeltes globales geodätisches Referenzsystem für Satellitenpositionsbestimmung, von der IHO empfohlen für den hydrografischen und kartografischen Gebrauch.</p> <p>Système géodésique mondial; un système global de référence géodésique développé par les USA pour le positionnement par satellite, recommandé par l'IHO pour un usage hydrographique et cartographique.</p> <p>Wereldwijd geodatisch systeem; een door de USA ontwikkeld wereldomvattend geodatisch referentiesysteem voor satelliet positie bepaling, aanbevolen door de IHO voor hydrografisch en kartografisch gebruik.</p>	2.1